



MECHANICAL ENGINEERING TECHNOLOGY

DOI: 10.15587/2312-8372.2017.99883

DEVELOPMENT OF TECHNOLOGICAL SUPPORT OF QUALITATIVE THREADED JOINTS OF PARTS MADE OF ALUMINUM ALLOYS

page 4–8

Abdulkerimov Ilimdar, PhD, Department of Technology Engineering and Machine Tools, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: ilimdar23@mail.ru, ORCID <http://orcid.org/0000-0002-1890-6666>

Permyakov Alexander, Doctor of Technical Sciences, Professor, Head of Department of Technology Engineering and Machine Tools, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: perm_a@i.ua, ORCID <http://orcid.org/0000-0002-9589-0194>

Analysis of existing technological processes of manufacturing parts and assembly of hermetic threaded joints in pneumatic equipment reveals the main factors that determine the quality and productivity of the hole machining. It is shown that for such processes as maintenance of the necessary performance characteristics of the joints, it is necessary to control the parameters of the state of the surface layer in the process of their manufacturing. It is also necessary to be able to calculate them at the design stage of the technological process.

Research results of the technological properties of AK12M2 aluminum alloy obtained by die casting are given, namely, modeling of the surface plastic deformation (SPD) of AK12M2 cast aluminum alloy. Also, the properties of the surface before and after SPD and the effect of the deformation angle are compared, taking into account the number of SPD cycles for the surface quality.

An analytical and experimental study of machining method of threaded holes with the use of a deforming tool is carried out, taking into account the modeling of the shaping process of inch threads in blind holes by a deforming tool. Formation of a dense surface layer from the porous structure of the material is investigated as an option to increase the tightness. The constructive and technological parameters of the deforming tool for blind holes for pipe cylindrical threads (up to 2") in parts made of aluminum alloys with gas and shrinkage porosity are developed. A possibility of providing a qualitative surface layer of blind holes after PPD of AK12M2 alloy due to the application of a deforming tool in the technological process machining is theoretically proved. New tool designs and practical recommendations on the selection of machining regimes are proposed, ensuring the number of loading cycles – 12–13, the deformation angle – 4 degrees, the deformation rate – $\zeta=3.77$ m/min with a cross-feed rate – $S=0.05$ mm/rev. A comparison of the quality of threaded joints, obtained by the basic and new machining method and evaluation of economic efficiency is carried out. This allows to reduce the technological cost and obtain economic benefit by reducing the labor intensity of machining and the cost of tools and process fluids.

Keywords: technological process, threaded joint, aluminum alloy, gas and shrinkage porosity, deforming tool.

References

1. Sheikin, S. E. (2007). *Nauchnye osnovy tehnologicheskogo upravleniia mikrorel'efom poverhnosti i uprochneniem poverhnostnogo sloia pri deformiruiushchem protiaivanii*. Kyiv, 337.
2. Tsehanov, Yu. A. (1993). *Mehanika deformiruiushchego protiaivaniia kak nauchnaia osnova otsenki kachestva detalei i rabotosposobnosti instrumenta s iznosostoikimi pokrytiiami*. Kyiv, 385.
3. Riabko, O. O., Kritskii, A. D., Lobanova, L. V., Tsehanov, Yu. A., Sheikin, S. E. (30.11.1990). Deformiruiushchii element protiazhki. *Patent of the USSR № 1609623, MKI5 V 24 V 39/02, B 23 D 43/02*. Appl. № 4640784/31–2. Filed 20.01.1989. Bull. № 44, 36.
4. Abdulkerimov, I. D., Tsekanov, Yu. O., Paderin, V. M., Kurkchy, E. U. (10.01.2011). Instrument for processing dead openings in parts made of aluminum alloys by casting. *Patent of Ukraine № 56193*. Appl. № u201005976. Filed 18.05.2010. Bull. № 1. Available: <http://uapatents.com/2-56193-instrument-dlya-obrobki-glukhikh-otvoriv-v-detalyakh-z-alyumniehvikh-splaviv-otrimanikh-littyam.html>
5. Eremenkova, I. V. (2005). *Tehnologicheskoe obespechenie germetichnosti nepodviznykh raziemnykh metallicheskih soedinenii*. Briansk, 13.
6. Kondakov, L. A. et al.; In: Golubev, A. I., Kondakov, L. A. (1994). *Uplotneniia i uplotnitel'naia tehnika*. Ed. 2. Moscow: Mashinostroenie, 445.
7. Karl, C., Feldhaus, U. (2008). CFD-Simulation für den Kühlkreislauf eines Lkw-Dieselmotors. *MTZ – Motortechnische Zeitschrift*, 69 (2), 116–123. doi:10.1007/bf03227279
8. Yu, Q. M., Zhou, H. L. (2015). Finite Element Study on Pre-Tightening Process of Threaded Connection and Failure Analysis for Pressure Vessel. *Procedia Engineering*, 130, 1385–1396. doi:10.1016/j.proeng.2015.12.307
9. Araujo, A. C., Mello, G. M., Cardoso, F. G. (2015). Thread milling as a manufacturing process for API threaded connection: Geometrical and cutting force analysis. *Journal of Manufacturing Processes*, 18, 75–83. doi:10.1016/j.jmapro.2015.01.002
10. Vail, J. R., Mills, R. S., Stephen, J. T., Marshall, M. B., Dwyer-Joyce, R. S. (2013). An ultrasonic method for measuring fluid penetration rate into threaded contacts. *Tribology International*, 67, 21–26. doi:10.1016/j.triboint.2013.06.011
11. Bratan, S., Novikov, P., Roshchupkin, S. (2016). Application of Combined Taps for Increasing the Shaping Accuracy of the Internal Threads in Aluminium Alloys. *Procedia Engineering*, 150, 802–808. doi:10.1016/j.proeng.2016.07.115
12. Permyakov, A., Abdulkerimov, I.; In: Solomentsev, Yu. (2015). *Obespechenie kachestva izgotovleniia gluhikh rez'bovykh otverstii v korpusnykh detaliah iz aliuminievykh splavov s gazosadochnoi poristost'iu deformiruiushchim instrumentom*. *Sbornik nauchnykh trudov «Problemy proektirovaniia i avtomatizatsii v mashinostroenii»*. Seria: «Proektirovanie i primeneniie rezhushchego instrumenta v mashinostroenii». Irbit: ZAO «ONIKS», 84–91.
13. Permyakov, A., Abdulkerimov, I. (2015). *Tehnologicheskoe obespechenie germetichnosti rez'bovykh soedinenii detalei na osnove poverhnostno-plasticheskogo deformirovaniia*. *Naukovi notatky*, 52, 48–53.
14. Abdulkerimov, I. (2016). *Tehnologiiia polucheniia kachestvennykh rez'bovykh soedinenii detalei iz siluminovykh splavov deformiruiushchim instrumentom*. *Tavricheskii nauchnyi obozrevatel'*, 11 (16), 207–211.

METALLURGICAL TECHNOLOGY

DOI: 10.15587/2312-8372.2017.99130

PARAMETRIC IDENTIFICATION IN THE PROBLEM OF DETERMINING THE QUALITY OF DUSULFUSATION AND DEPHOSPHORATION PROCESSES OF Fe-C ALLOY

page 9–15

Mourad Aouati, Chief Commissioner of Police, Central City Police Department of Constantine, Algeria, ORCID: <http://orcid.org/0000-0003-2744-3592>

It is established that an algorithm for parametric methods of pattern recognition can be used to build a classifying rule that allows to identify a section of the duplex-melting process «cupola – electric arc furnace», which has a lower index of parametric reliability. It is shown that in this case it is sufficient to build a linear discriminant function.

The resulting classifying rule provides a high recognition rate (91.4 % and 97.1 %) of object belonging to class A (melting in cupola) and class B (melting in electric arc furnace), respectively. This allows it to be recommended for decision support systems for desulphurization and dephosphorization control in the duplex-melting process «cupola – electric arc furnace». The application of this rule opens the possibility of improving the quality of desulphurization and dephosphorization control due to the correct choice of control actions.

Additional opportunities for using the above results in industrial conditions are associated with the use of the classifying rule in decision support information systems. It can be implemented by integration of the appropriate mathematical description into the melting information control system (ICS).

Keywords: parametric methods of pattern recognition, classifying rule, desulfurization, dephosphorization.

References

1. Trufanov, I., Liutyi, A., Chumakov, K., Andriias, I., Kazanskaia, T., Dzhihev, V. (2010). Scientific bases of the permission of innovative problems identifications in processes automation systems of electrometallurgy of the steel and alloys. *Eastern-European Journal of Enterprise Technologies*, 3(10(45)), 8–23. Available: <http://journals.uran.ua/eejet/article/view/2898>
2. Razzhivin, A., Sagaida, I. (2000). Informatsionnoe obespechenie sistem avtomaticheskogo upravleniia dugovoi staleplavil'noi pech'iu po temperature metalla. *Visnik SUDU*, 3 (25), 215–220.
3. Demin, D. (2014). Mathematical description typification in the problems of synthesis of optimal controller of foundry technological parameters. *Eastern-European Journal of Enterprise Technologies*, 1(4(67)), 43–56. doi:10.15587/1729-4061.2014.21203
4. Trufanov, I., Chumakov, K., Bondarenko, A. (2005). Obshche-teoreticheskie aspekty razrabotki stohasticheskoi sistemy avtomatizirovannoi ekspertnoi otsenki dinamicheskogo kachestva proizvodstvennykh situatsii elektrostaleplavleniia. *Eastern-European Journal of Enterprise Technologies*, 6(2(18)), 52–58.
5. Demin, D. (2014). Quality Control at foundries technological aspects in selection of optimal strategies for technical reequipment. *Bulletin of NTU «KhPI». Series: New desicions of modern technologies*, 7 (1050), 42–52.
6. Dembovskii, V. (1989). *Avtomatizatsiia liteinykh protsessov*. Leningrad: Mashinostroenie, 264.
7. Demin, D. (2010). Priniatie reshenii v protsesse upravleniia elektroplovkoi s uchetom faktorov nestabil'nosti tehnologicheskogo protsessa. *Bulletin of NTU «KhPI». Series: New desicions of modern technologies*, 17, 67–72.
8. Vasenko, Yu. (2012). Technology for improved wear iron. *Technology Audit and Production Reserves*, 1(1(3)), 17–21. doi:10.15587/2312-8372.2012.4870
9. Demin, D., Bozhko, A., Zraichenko, A., Nekrasov, A. (2006). Identifikatsiia chuguna dlia opredeleniia ratsional'nykh rezhimov legirovaniia. *Eastern-European Journal of Enterprise Technologies*, 4(1(22)), 29–32.
10. Ponomarenko, O., Trenev, N. (2013). Computer modeling of crystallization processes as a reserve of improving the quality of pistons of ICE. *Technology Audit and Production Reserves*, 6(2(14)), 36–40. doi:10.15587/2312-8372.2013.19529
11. Manikaeva, O., Arsirii, E., Vasilevskaja, O. (2015). Development of the decision support subsystem in the systems of neural network pattern recognition by statistical information. *Eastern-European Journal of Enterprise Technologies*, 6(4(78)), 4–12. doi:10.15587/1729-4061.2015.56429
12. Frazze-Frazenko, A. (2012). Algorithm of study neural network for image recognition. *Technology Audit and Production Reserves*, 4(1(6)), 33–34. doi:10.15587/2312-8372.2012.4781
13. Unglert, K., Radić, V., Jellinek, A. M. (2016). Principal component analysis vs. self-organizing maps combined with hierarchical clustering for pattern recognition in volcano seismic spectra. *Journal of Volcanology and Geothermal Research*, 320, 58–74. doi:10.1016/j.jvolgeores.2016.04.014
14. Fakhar, K., El Aroussi, M., Saidi, M. N., Aboutajdine, D. (2016). Fuzzy pattern recognition-based approach to biometric score fusion problem. *Fuzzy Sets and Systems*, 305, 149–159. doi:10.1016/j.fss.2016.05.005
15. Demin, D. (2015). Mathematical modeling in the problem of selecting optimal control of obtaining alloys for machine parts in un-certainty conditions. *Problems Of Mechanical Engineering*, 16 (6), 15–23. Available: <http://journals.uran.ua/jme/article/view/21309>
16. Hartmann, K., Lezki, E., Schafer, W. (1974). *Statistische Versuch-splanung und-auswertung in der Stoffwirtschaft*. Leipzig, 552.
17. Anderson, W. K. (1979). Computer-assisted studies of chemical structure and biological function (Stuper, Andrew J.; Brugger, William E.; Jurs, Peter C.). *Journal of Chemical Education*, 56 (12), A380. doi:10.1021/ed056pa380.4
18. Mourad, A. (2016). Localization of vectors–patterns in the problems of parametric classification with the purpose of increasing its accuracy. *Eastern-European Journal of Enterprise Technologies*, 4(4(82)), 10–20. doi:10.15587/1729-4061.2016.76171

MATERIALS SCIENCE

DOI: 10.15587/2312-8372.2017.98125

INVESTIGATION OF THE CURRENT STATE OF ISOSTATIC GRAPHITE PRODUCTION TECHNOLOGY

page 16–21

Karvatskii Anton, Doctor of Technical Sciences, Professor, Department of Chemical, Polymer and Silicate Engineering, National Technical University of Ukraine «Igor Sikorsky Kyiv

Polytechnic Institute», Ukraine, e-mail: anton@rst.kpi.ua, ORCID: <http://orcid.org/0000-0003-2421-4700>

Leleka Serhii, PhD, Researcher, Scientific Research Center «Resource-Saving Technologies», National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: sleleka@rst.kpi.ua, ORCID: <http://orcid.org/0000-0002-4372-9454>

Pedchenko Anatolii, Research Fellow, Scientific Research Center «Resource-Saving Technologies», National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: anatolek@rst.kpi.ua, ORCID: <http://orcid.org/0000-0001-5065-5003>

Lazarev Taras, PhD, Researcher, Scientific Research Center «Resource-Saving Technologies», National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: t_lazarev@rst.kpi.ua, ORCID: <http://orcid.org/0000-0001-8260-1683>

The study of isostatic graphite production process and its development trends in the world market was conducted.

It was established that the isostatic graphite production is a complex and multistage process that requires careful preparation of raw materials, the usage of powerful specialized pressing equipment, the use of elaborate heat treatment modes etc. As a result, it creates a high final price comparing to other brands of graphite materials.

Methods of synthesis, analysis and systematization of available information regarding the isostatic graphite production were used for the study.

The peculiarities of foreign isostatic graphite production technology were determined, which allows to set directions of improvement by Ukrainian producers, namely:

- choice of components and their composition for coke and pitch mixture;
- adding special modifiers;
- optimization of particle size distribution of the filler;
- setting the pressure for pressing moulding powder;
- choice of modes of blanks thermal processing etc.

The level of future growth in global demand is determined for isostatic graphite materials and products based on it, which is more than 5 % of the annual global volume of production.

The results enable further research in order to develop equipment and rational modes of grinding, mixing and pressing coke-pitch compositions using available Ukrainian brand coke and pitch. Furthermore, it will allow in the future to conduct a study of pressed billets heat treatment to reduce the unit cost of electricity and improve the process of isostatic graphite material manufacturing.

Keywords: isostatic graphite, isostatic pressing, photogalvanic industry, heat-resistant material, coke-pitch composition.

References

1. Kostikov, V. I., Samoilo, V. M., Beilina, N. Yu., Ostronov, B. G. (2004). Novye vysokoprochnye uglerodnye materialy dlia vysokih tehnologii. *Rossiiskii himicheskii zhurnal*, XLVIII (5), 64–75.
2. Ranjan, R., Donald, W. S.; assignee: Santoku America, Inc. (05.10.2004). Castings of metallic alloys with improved surface quality, structural integrity and mechanical properties fabricated in finegrained isotropic graphite molds under vacuum. *Patent US 6799626 B2, Int. Cl.⁷ B22C 9/00, B22C 3/00*. Appl. No. 10/143,920. Filed 14.03.2002. 36.
3. *Global Isostatic Graphite Market 2015 Industry Trends, Analysis & Forecast to 2020*. (2015). Florida: QY Research, 153.
4. Inagaki, M., Kang, F., Toyoda, M., Konno, H. (2014). *Advanced Materials Science and Engineering of Carbon*. Oxford: Butterworth-Heinemann, 440. doi:10.1016/c2012-0-03601-0
5. Eliseev, Yu. S., Poklad, V. A., Shutov, A. N., Vasilev, Yu. N., San-kin, A. E.; assignee: JSC «GTERPC «SALUT». (20.05.2005). Sposob polucheniia grafitirovannogo materiala. *Patent RU 2252190 C1, MPK⁷ C 01 B 31/02, S 04 B 35/52*. Appl. No. 2004107239/15. Filed 12.03.2004. Bull. № 14, 6.
6. Sviridov, A. A., Seleznev, A. N., Podkopaev, S. A., Gnedin, Yu. F., Sherriuble, V. G., Sherriuble, V. G.; assignee: «Cheliabinsk Electrode Plant» OJSC. (27.02.2005). Sposob polucheniia vysokoplotnyh melkozernistyh uglegrafitovyh materialov. *Patent RU 2256610 C2, MPK⁷ C 01 B 31/04, S 04 B 35/52*. Appl. No. 2003116383/15. Filed 04.06.2003. Bull. № 20, 5.
7. Beilina, N. Yu., Lipkina, N. V., Petrov, A. V., Roshchina, A. A., Starichenko, N. S.; assignee: State Research Institute of Structural Materials Based on Graphite «NIGRAFIT». (20.07.2010). Nanostrukturirovannyi kamennougol'nyi pek i sposob ego polucheniia. *Patent RU 2394870 C1, MPK (2006.01) C10C 3/10, B82B 1/00*. Appl. No. 2008148549/04. Filed 10.12.2008. Bull. № 20, 8.
8. Klimenko, A. A., Morozov, S. M., Filippova, L. I. (27.07.2013). Sposob izgotovleniia zagotovok iz melkozernistogo grafitu. *Patent RU 2488554 C2, MPK (2006.01) C01B 31/04, S 04 B 35/52*. Appl. No. 2011142450/05. Filed 21.10.2011. Bull. № 21, 8.
9. Lavrenov, A. A., Fokin, V. P.; assignee: LLC «Doncarb Graphite». (20.09.2013). Sposob polucheniia zagotovok iz melkozernistogo grafitu. *Patent RU 2493098 C1, MPK (2006.01) C01B 31/04, B82B 3/00, (2011.01) B82Y 30/00*. Appl. No. 2012100051/05. Filed 11.01.2012. Bull. № 26, 11.
10. Nonishneva, N. P., Frolov, A. V. (2015). Issledovaniia v oblasti razrabotki otechestvennoi tehnologii polucheniia izostaticeskogo grafitu. *Proceedings of the 67th Scientific Conference. Nauka YuUrGU. Seksii estestvennykh nauk*. Cheliabinsk: Izdatelskii tsentr YuUrGU, 364–368.
11. Asao, O.; In: Marsh, H., Heintz, E. A., Rodrigues-Reinoso, F. (1997). *High density isotropic graphites and glassy carbons. Japanese situation: production, properties and applications*. Alicante: Universidad de Alicante. Secretariado de Publicaciones, 564.
12. Randall, T. (13.06.2016). *The world nears peak fossil fuels for electricity*. Available: <https://www.bloomberg.com/news/articles/2016-06-13/we-ve-almost-reached-peak-fossil-fuels-for-electricity>. Last accessed: 01.02.2017.
13. Freik, D. M., Chobanyuk, V. M., Galuschak, M. O., Krunutcky, O. S., Mateik, G. D. (2012). Photovoltaic Converters of Solar Radiation. Achievements, Current Status and Trends (Review). *Physics and Chemistry of Solid State*, 13 (1), 7–20.
14. Hoffmann, W. R., Hüttinger, K. J. (1994). Sintering of powders of polyaromatic mesophase to high-strength isotropic carbons – I. Influence of the raw material and sintering conditions on the properties of the carbon materials. *Carbon*, 32 (6), 1087–1103. doi:10.1016/0008-6223(94)90218-6
15. Samoilo, V. M., Streletskii, A. N. (2004). Vliianie sverhtonkogo izmel'cheniia na kristallicheskuuu strukturu i grafitiruemost' tonkodispersnyh uglerodnih napolnitelei. *Himiia tverdogo topliva*, 2, 53–59.
16. Samoilo, V. M.; State Research Institute of Structural Materials Based on Graphite «NIGRAFIT». (2006). *Poluchenie tonkodispersnyh uglerodnih napolnitelei i razrabotka tehnologii proizvodstva tonkozernistyh grafitov na ih osnove*. Moscow, 56.
17. Timoshchuk, E. V., Samoilo, V. M., Timoshchuk, E. I., Smirnov, V. K. (2011). Vliianie dlitel'nosti sovместnogo vibroizmel'cheniia i davleniia pressovaniia na plotnosti i usadki zagotovok grafitu. *Himiia tverdogo topliva*, 1, 60–64.
18. Chard, W., Conaway, M., Niesz, D. (1976). Advanced High Pressure Graphite Processing Technology. *Petroleum Derived Carbons*, 21, 155–171. doi:10.1021/bk-1976-0021.ch014
19. Timoshchuk, E. I., Samoilo, V. M., Lyapunov, A. Ya., Balakliencko, Yu. M., Borunova, A. B. (2012). Determination of the Particle Size of Fine Powders of the Artificial Graphite by Laser Diffraction. *Industrial laboratory. Materials diagnostics*, 78 (11), 25–28.
20. Samoilo, V. M. (2010). Udel'naia poverhnost', razmery i forma chastits tonkodispersnyh uglerodnih napolnitelei. *Neorganicheskie materialy*, 46 (8), 913–918.
21. Ucar isostatic molded graphite. *MatWeb*. Available: <http://www.matweb.com/search/QuickText.aspx?SearchText=UCAR%20Isostatic%20Molded%20Graphite>. Last accessed: 01.02.2017.
22. Technical Data Sheets: SIGRAFINE Isostatic Graphite. *SGL Group – The Carbon Company*. Available: <https://www.sgl-group.com/cms/international/infokorb/Downloadcenter/products/fgg/technical-data-sheets/iso/index.html>. Last accessed: 01.02.2017.

23. Main graphite grades. *MERSEN*. Available: https://www.mersen.com/fileadmin/user_upload/pdf/ht/19-graphite-grades-mersen.pdf. Last accessed: 01.02.2017.
24. Special Graphite (Isostatic Graphite). *TOYO TANSO*. Available: http://www.toyotanso.com/Products/Special_graphite/data.html. Last accessed: 01.02.2017.
25. Property Data. *IBIDEN Fine Graphite Material*. Available: <https://www.fgm.ibiden.co.jp/multilanguage/english/list.html>. Last accessed: 01.02.2017.
26. Butyrin, G. M. (2015). Plotnost', poristaiia struktura i gazo-dinamicheskie karakteristiki tonkozernistyh grafitov (obzor). *Himiia toerdogo topliva*, 5, 40–53.
27. Tracy, L. A., Doug, J. M. (2007). The characterization of highly crystalline, isotropic graphite. *Carbon 2007 Conference, 15–20 July 2007, Seattle, Washington, USA*. Available: http://acs.omnibooksonline.com/data/papers/2007_D021.pdf
28. Lgalov, V. V., Tokarev, A. M. (2015). Izuchenie ekspluatatsionnoi stoikosti detalei iz iskusstvennogo grafita pri izgotovlenii metallostekliannykh soedinenii. *Proceedings of the V All-Russian Scientific Conference with International Participation. Zhiznennyi tsikl konstruktivnykh materialov*. Irkutsk, 56–64.
29. Dodoo-Arhin, D., Howe, R. C. T., Hu, G., Zhang, Y., Hiralal, P., Bello, A. et al. (2016). Inkjet-printed graphene electrodes for dye-sensitized solar cells. *Carbon*, 105, 33–41. doi:10.1016/j.carbon.2016.04.012
30. Liu, Z., You, P., Xie, C., Tang, G., Yan, F. (2016). Ultrathin and flexible perovskite solar cells with graphene transparent electrodes. *Nano Energy*, 28, 151–157. doi:10.1016/j.nanoen.2016.08.038

DOI: 10.15587/2312-8372.2017.99894

EFFECT OF SURFACE ROLLING ON MECHANICAL PROPERTIES OF Ti–Al SYSTEM ALLOY

page 21–24

Berdova-Bushura Olha, Postgraduate Student, Department of Physical and Chemical Bases of Technology Metals, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: olja-berdova@mail.ru, ORCID: <http://orcid.org/0000-0002-7741-1663>

Taking into account the problem of modern aircraft engine building, new materials are being actively introduced to increase the service and reliability of products while reducing their material consumption. Namely, nickel alloys are replaced by lighter intermetallic alloys of the Ti–Al system, which is the object of the research. However, the use of a new class of alloys is complicated because of the high demands placed on these materials. Consequently, the intermetallic alloys used in the critical components of the aircraft must be not only strong, but super-strong.

To solve the problem of increasing the level of strength, it is suggested to use the roller burnishing, which consists in the fact that the rollers are pressed against the surface of the processed material, which leads to plastic deformation in the surface zone. As a result of deformation, changes in the structure of the surface layers of the material occur, which, in turn, leads to an increase in the mechanical characteristics.

Experiments have been carried out to strengthen the alloy of the Ti–Al system. The effect of roller burnishing on alloy Ti-45Al-5Nb (at %) is studied and it is established that after surface roller burnishing, the fatigue strength of alloy Ti-45Al-5Nb (at %) is increased by 4 %, from 675 to 725 MPa. It is shown that surface roller burnishing reduces the maximum surface roughness by 0.4 μm (from 2.4 μm to 2.0 μm).

Keywords: roller burnishing, intermetallic alloys, Ti–Al alloys, fatigue cracks.

References

1. Dimiduk, D. M. (1999). Gamma titanium aluminide alloys – an assessment within the competition of aerospace structural materials. *Materials Science and Engineering: A*, 263 (2), 281–288. doi:10.1016/s0921-5093(98)01158-7
2. In: Peters, M., Leyens, C. (2002). *Titan und Titanlegierungen*. Wiley, 528. doi:10.1002/9783527611089
3. Appel, F., Paul, J. D. H., Oehring, M. (2011). *Gamma Titanium Aluminide Alloys*. Wiley, 745. doi:10.1002/9783527636204
4. Imayev, V. M., Imayev, R. M., Oleneva, T. I. (2011). Current status of γ -TiAl intermetallic alloys investigations and prospects for the technology developments. *Letters On Materials*, 1, 25–31.
5. Hoffmeister, J. (2009). *Beschreibung des Eigenspannungsabbaus in kugelgestrahltem Inconel 718 bei thermischer, quasistatischer und zyklischer Beanspruchung*. Karlsruher Institut für Technologie. Available: <https://publikationen.bibliothek.kit.edu/1000014996/1336083>
6. Tehnologii shot peening i peen forming. *Blastservis*. Available: <http://blastservis.ru/kat/kabiny-drobestrurnye/kabiny/kabiny-naklep-iuprochnenie/tehnolo-gii-shot-peening-i-peen-forming8143/>
7. *OSK-Kiefer GmbH Oberflächen- & Strahltechnik*. Available: <http://osk-kiefer.de/>
8. Lindemann, J., Kutzsche, A., Oehring, M., Appel, F. (2007). Influence of Mechanical Surface Treatments on the Fatigue Performance of the Gamma TiAl Alloy Ti-45Al-9Nb-0.2C. *Materials Science Forum*, 539-543, 1553–1558. doi:10.4028/www.scientific.net/msf.539-543.1553
9. *LLC «Transet»*. Available: <http://www.transet-tool.com/>
10. Nochovnaia, N. A., Panin, P. V., Alekseev, E. B., Novak, A. V. (2015). Zakonomernosti formirovaniia strukturno-fazovogo sostoianiia splavov na osnoveorto- i gamma-aluminidov titana v protsesse termomechanicheskoi obrabotki. *Vesnik Rossiiskogo fonda fundamental'nykh issledovanii*, 1. Available: http://www.rfbr.ru/rffi/ru/bulletin/o_1932892
11. Kulykovskiy, R. A., Pakholka, S. N., Pavlenko, D. V. (2015). Prospects for industrial use titanium aluminide in aeroengine. *Stroitel'stvo. Materialovedenie. Mashinostroenie. Seriya: Starodubovskie chteniia*, 80, 369–372.
12. Nathal, M. V., Darolia, R., Liu, C. T., Martin, P. L., Miracle, D. B. (1997). *Second International Symposium on Structural Intermetallics*. Warrendale PA: Minerals Metals and Materials Society, 952.
13. Hénaff, G., Gloanec, A.-L. (2005). Fatigue properties of TiAl alloys. *Intermetallics*, 13 (5), 543–558. doi:10.1016/j.intermet.2004.09.007
14. Steinert, R., Lindemann, J., Berdova, O., Glavatskikh, M., Leyens, C. *Surface effects on mechanical properties of materials for elevated temperature applications*. Cottbus: Brandenburg University of Technology. Available: <http://www.extremat.org/ib/site/documents/media/6cb655a4-c1e9-0d9a-25b4-6651c3edec1a.pdf/STEINERT.pdf>
15. Berg, A., Lindemann, J., Wagner, L. (1996). Elevated Temperature Fatigue Behavior of Timetal 1100. *Fatigue '96*, 879–884. doi:10.1016/b978-008042268-8/50025-3
16. Glavatskikh, M. (2011). *Improvement of fatigue behavior of γ -TiAl-Alloys by means of mechanical surface treatment*. Available: <https://opus4.kobv.de/opus4-btu/frontdoor/index/index/docId/%202207>
17. Lindemann, J., Glavatskikh, M., Leyens, C., Oehring, M., Appel, F. (2007). Influence of Mechanical Surface Treatments on the High Cycle Fatigue Performance of Gamma Titanium Aluminides. *Ti-2007 Science and Technology. Vol. II*. The Japan Institute of Metals, 1703.

ELECTRICAL ENGINEERING AND INDUSTRIAL ELECTRONICS

DOI: 10.15587/2312-8372.2017.97507

EFFECT OF PIECEWISE LINEAR CURRENT WAVEFORMS ON SURGE ARRESTER RESIDUAL VOLTAGE

page 25–31

Trotsenko Yevgeniy, PhD, Associate Professor, Department of High Voltage Engineering and Electrophysics, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: y.trotsenko@kpi.ua, ORCID: <http://orcid.org/0000-0001-9379-0061>

Brzhezitsky Volodymyr, Doctor of Technical Sciences, Professor, Department of High Voltage Engineering and Electrophysics, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: v.brzhezitsky@kpi.ua, ORCID: <http://orcid.org/0000-0002-9768-7544>

Masluchenko Igor, PhD, Associate Professor, Department of High Voltage Engineering and Electrophysics, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: i.masluchenko@kpi.ua, ORCID: <http://orcid.org/0000-0001-6073-9649>

The object of research is the magnitude and shape of the residual voltage that arises between the terminals of the surge arrester models when they are subjected to current and voltage pulses of a piecewise linear waveform. One of the most problematic places in this problem is the approximation of current switching pulses with a short duration and also steep front current pulses. With the help of the well-known double-exponential pulse, it is impossible to describe a pulse whose time-to-half duration T_2 is twice bigger the time-to-crest duration T_1 . At the same time, current pulses in the manufacturer catalogs of the surge arresters have exactly this ratio (1/2, 30/60 or 45/90 μ s).

With the help of piecewise linear approximation, it is possible, bypassing complex calculations, to describe pulses of almost any shape, including switching current pulses and steep front current pulses.

By means of evaluation version of Micro-Cap 11 circuit simulator the residual voltage on the surge arrester terminals is computed during a passage of the current pulses with different amplitude and wave shape. Current sources used in this research represent sources of simplified triangular (piecewise linear) current pulses. It is considered that the current wave rises linearly to its maximum value, and then also decays linearly to half its amplitude value. Comparison of the results suggests that proposed simplification of discharge current waveform has no significant effect on relative calculation error of residual voltage on surge arrester.

If it is necessary to estimate only maximum value of residual voltage on surge arrester, it is possible to use piecewise linear approximation of switching and lightning currents with any amplitude and shape without loss of accuracy.

Keywords: circuit simulation, surge arrester, residual voltage, piecewise linear waveform.

References

1. Trotsenko, Ye., Brzhezitsky, V., Masluchenko, I. (2016). Surge arrester modeling using Micro-Cap. *Technology Audit and Production Reserves*, 6(1(32)), 26–30. doi:10.15587/2312-8372.2016.86137
2. Heidler, F., Cvetic, J. M., Stanic, B. V. (1999). Calculation of lightning current parameters. *IEEE Transactions on Power Delivery*, 14 (2), 399–404. doi:10.1109/61.754080
3. Garcia-Gracia, M., Baldovinos, S., Sanz, M., Montanes, L. (1999). Evaluation of the failure probability for gapless metal oxide arresters. *1999 IEEE Transmission and Distribution Conference (Cat. No. 99CH36333)*, 2, 700–705. doi:10.1109/ttdc.1999.756136
4. Trotsenko, Ye., Brzhezitsky, V., Masluchenko, I. (2017). Study of surge arrester model under influence of various current pulses. *Technology Audit and Production Reserves*, 1(1(33)), 44–48. doi:10.15587/2312-8372.2017.92244
5. Gamerota, W. R., Elisme, J. O., Uman, M. A., Rakov, V. A. (2012). Current Waveforms for Lightning Simulation. *IEEE Transactions on Electromagnetic Compatibility*, 54 (4), 880–888. doi:10.1109/temc.2011.2176131
6. Nakada, K., Yokota, T., Yokoyama, S., Asakawa, A., Nakamura, M., Taniguchi, H., Hashimoto, A. (1997). Energy absorption of surge arresters on power distribution lines due to direct lightning strokes-effects of an overhead ground wire and installation position of surge arresters. *IEEE Transactions on Power Delivery*, 12 (4), 1779–1785. doi:10.1109/61.634205
7. Nakada, K., Yokoyama, S., Yokota, T., Asakawa, A., Kawabata, T. (1998). Analytical study on prevention methods for distribution arrester outages caused by winter lightning. *IEEE Transactions on Power Delivery*, 13 (4), 1399–1404. doi:10.1109/61.714514
8. Hassan, N. H. N., Bakar, A. H. A., Mokhlis, H., Illias, H. A. (2012). Analysis of arrester energy for 132 kV overhead transmission line due to back flashover and shielding failure. *2012 IEEE International conference on power and energy (PECon)*, 683–688. doi:10.1109/pecon.2012.6450302
9. Annamalai, A., Gulati, A., Koul, R. (2011). Sizing of surge arresters for 400 kV substation – A case study. *2011 International Conference on Emerging Trends in Electrical and Computer Technology*, 206–211. doi:10.1109/icetec.2011.5760117
10. Lantharhong, T., Rugthaicharoencheep, N., Supanus, K., Phayomhom, A. (2014). Effect of waveform and impulse resistance on lightning performance in distribution system. *2014 International Conference on Lightning Protection (ICLP)*, 1766–1769. doi:10.1109/iclp.2014.6973415
11. Hu, H., Mashikian, M. S. (1990). Modeling of lightning surge protection in branched cable distribution network. *IEEE Transactions on Power Delivery*, 5 (2), 846–853. doi:10.1109/61.53092
12. Durbak, D. W. (2001). Surge arrester modeling. *2001 IEEE Power Engineering Society Winter Meeting. Conference Proceedings (Cat. No. 01CH37194)*, 728–730. doi:10.1109/pesw.2001.916946
13. Martinez, J. A., Durbak, D. W. (2005). Parameter Determination for Modeling Systems Transients – Part V: Surge Arresters. *IEEE Transactions on Power Delivery*, 20 (3), 2073–2078. doi:10.1109/tpwr.2005.848771
14. *Micro-Cap 11. Electronic Circuit Analysis Program. Reference Manual. Ed. 11.* (2014). Sunnyvale, CA: Spectrum Software, 1040. Available: <http://www.spectrum-soft.com/down/rm11.pdf>
15. Pinceti, P., Giannetoni, M. (1999). A simplified model for zinc oxide surge arresters. *IEEE Transactions on Power Delivery*, 14 (2), 393–398. doi:10.1109/61.754079

DOI: 10.15587/2312-8372.2017.99929

INVESTIGATION OF PECULIARITIES OF DECOMPOSITION OF TRACTION ELECTRIC DRIVES OF MOBILE ELECTROTECHNICAL COMPLEXES

page 31–38

Kulagin Dmitro, PhD, Professor, Department of Power Supply of Industrial Enterprises, Zaporozhye National Technical University, Ukraine, e-mail: kulagindo@gmail.com, ORCID: <http://orcid.org/0000-0003-3610-4250>

Yatsenko Dmitro, Department of Power Supply of Industrial Enterprises, Zaporozhye National Technical University, Ukraine, e-mail: 19yatsenko94@mail.ru, ORCID: <http://orcid.org/0000-0001-6702-569X>

The object of this research is traction electric drive systems of mobile electrotechnical systems based on various types of motors. As a result of the system analysis of the object of research, it is established that it is possible to solve the problem of increasing the energy potential of an electromechanical system only in a complex manner. It is revealed that it is necessary to consider the established mode of operation of the entire system as a whole, taking into account the conditions for the rational operation of its individual components, provided that the interconnection between them is taken into account. It is shown that a practical situation is quite frequent where the rational operating mode of individual elements of an electromechanical system and optimal control of them does not lead to the operation of the entire system on the economic characteristics. This, as a consequence, increases the consumption level of diesel fuel. Conversely, the artificial compulsion of diesel operation on the economic characteristics leads to the operation of these electrical elements of the whole electromechanical system with significant power losses. To achieve the tasks of controlling the electromechanical system, the potential method is used. According to it, it is shown that the potential of not every individual element of the electric drive is important, but the potential of their aggregate in the interaction. With a successful combination of interaction and operating modes of each element and the whole structure in general, the total energy saving potential of the whole is greater than the sum of the energy saving potentials of individual elements of the electric drive. As a result, a synergy effect is obtained. It is also shown that the task of the control algorithm is to optimize the interaction of resources to obtain a positive synergy effect, the effect of reducing the level of losses in the system. As research result, a method of increasing energy efficiency for static and dynamic characteristics is proposed. The advantages of this method are the use of the synergetic properties of the system, the integrated provision of an energy-efficient operating mode. This leads to the achievement of the most rational specific level of fuel consumption and efficiency maximization of the electromechanical system.

Keywords: decomposition of electric drive, electrotechnical complex, traction drive, autonomous system, diesel-generator system.

References

1. In: Klepikov, V. B. (2014). *Vvedenie v mehatroniku*. Kharkiv: NTU «KhPI», 274.
2. Haken, H. (1990). *Synergetik*. Springer Berlin Heidelberg, 396. doi:10.1007/978-3-662-10186-5
3. Florentsev, S. N. (2009). Traction Electric Equipment Set for AC Electric Transmission Various Vehicles. *Proceedings of International Exhibition & Conference «Power Electronics, Intelligent Motion. Power Quality (PCIM-2009)»*. Nuremberg, Germany, 625–627.
4. Bazhinov, O. V., Smirnov, O. P., Serikov, S. A., Dvadenko, V. Ya. (2011). *Sinergetichnii avtomobil'. Teoriia i praktika*. Kharkiv: KhNADU, 235.
5. Jordan, H. E. (1994). *Energy-Efficient Electric Motors and their Applications*. Springer US, 188. doi:10.1007/978-1-4899-1465-1
6. Kulagin, D. O. (2014). The mathematical model of asynchronous traction motor taking into account the saturation of magnetic circuits. *Scientific bulletin of National Mining University*, 6, 103–110.
7. Kulagin, D. O. (2014). Mathematical model of asynchronous traction motor taking into account the saturation. *Tekhnichna Elektrodynamika*, 6, 49–55.
8. Boldea, I., Nasar, S. A. (2010). *The Induction Machine Handbook*. CRC Press, 968.
9. El-Sharkawi, M. A. (2000). *Fundamental of electric drivers*. Brooks: Cole production, 400.
10. Stone, G. C., Boulter, E. A., Culbert, I., Dhirani, H. (2003). *Electrical Insulation for Rotating Machines*. John Wiley & Sons, Inc., 392. doi:10.1002/047168290x
11. Sinchuk, O. N., Shevchenko, A. I. (2003). O tselesoobraznosti rekuperativnogo tormozheniia bol'shegruznyh kar'ernykh avtosamosvalov s elektromehani Cheskoj transmissiei. *Vestnik Natsional'nogo tehni Cheskogo universiteta «Kharkovskii politehni Cheskii institut»*, 10, 415–419.
12. Shydlovskiy, A. K., Skidanov, V. M., Pavlov, V. B., Yurchenko, O. M. (1998). Doslidzhennia efektyvnosti rekuperatyvnoho halmuvannia elektromobilia. *Tekhnichna Elektrodynamika*, 1, 22–30.
13. Bulhakov, V. M., Zaryshniak, A. S., Kiurchev, V. M., Nadykto, V. T. (2010). Obhruntuvannia ty pazhu silskohospodarskykh traktoriv v Ukraini. *Visnyk ahrarynoi nauky*, 11, 5–8.
14. Kosov, V. V., Lifshits, V. N., Shahnazarov, A. G. (2000). *Metodicheskie rekomendatsii po otsenke effektivnosti investitsionnykh proektov*. Moscow: Ekonomika, 421.
15. Kulagin, D. O. (2014). *Proektuvannia system keruvannia tiahovymy elektropredachamy motorvahonnykh poizdiv*. Berdiansk: FOP Tkachuk O. V., 154.

TECHNOLOGY AND SYSTEM OF POWER SUPPLY

DOI: 10.15587/2312-8372.2017.99914

INCREASING THE ENERGY EFFICIENCY OF WAREHOUSES USING DEMAND-SIDE MANAGEMENT MECHANISMS

page 39–45

Denysiuk Sergii, Doctor of Technical Sciences, Professor, Department of Power Supply, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: spdens@ukr.net, ORCID: <http://orcid.org/0000-0002-6299-3680>

Kotsar Oleg, PhD, Associate Professor, Department of Power Supply, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: koopers@ukr.net, ORCID: <http://orcid.org/0000-0002-7958-2335>

Opryshko Vitalii, Postgraduate Student, Department of Power Supply, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: livstrongtm@gmail.com, ORCID: <http://orcid.org/0000-0003-4963-2490>

The complex approach and expansion of the functionality of DSM programs is offered due to the application of services and criteria for classification of warehouses in terms of energy efficiency. When analyzing the effectiveness of the application of DSM programs, namely the optimality of power consumption modes, it is suggested to assess the power supply mode during the entire technological period.

Considering the electrical supply of warehouses as an electricity supply to the consumer with sharply variable nonlinear characteristics, the power of which is supplied from the generators, the operating voltage and current values of which are variable, it is proposed to use the modified Frieze inactive power index. The use of the Q_F index is advisable, since it will be located even in the absence of reactive elements in the consumer system. The influence of the consumption mode on the first harmonic is analyzed. The received characteristics are caused by presence of influence of consumption mode on the general characteristics of electricity supply mode optimality. The analysis of higher harmonics can also be used to assess the effect of unevenness. Such

analysis requires additional studies, but it can be argued that the use of the Frieze inactive power index allows to assess the degree of uneven electricity consumption in accordance with a given optimal level.

Keywords: demand-side management for energy resources, energy efficiency of buildings, transport and logistics infrastructure.

References

1. Davtyan, Y. V. (2012). The Theoretical Foundations of the International Transport Corridors and their Role in the Economy of Ukraine. *Business Inform*, 12, 151–155.
2. Cherniavskiy, Yu. I. (2013). Ekologichni aspekty rozvytku mizhnarodnoho transportnoho korydoru Yevropa-Aziia. *Ekonomika pryrodokorystuvannia i okhorony dokillia*, 227–234.
3. Stechenko, D. M. (2006). *Rozmishchennia produktyvnykh syl i rehionalistyka*. Kyiv, 396.
4. Kopylova, O. A., Rahmangulov, A. N. (2012). Metodika formirovaniia energoeffektivnoi transportno-logisticheskoi infrastruktury. *Sovremennye problemy transportnogo kompleksa Rossii*, 2, 45–53.
5. Rakhmanhulov, A. N., Kopylova, O. A., Autiv, Ye. K. (2012). Vybir mistv dlia lohistychnykh potuzhnostei. *Svit transportu*, 2, 19–22.
6. Razvitie logisticheskikh tsestrov. (2013). *Central Asia Regional Economic Cooperation (CAREC)*. Available: http://www.carecprogram.org/uploads/events/2013/CFCFA-training-KGZ/009_103_209_logistics-center-development-ru.pdf
7. Klassifikatsiia skladskikh pomeshchenii. *Commercial Property*. Available: <http://commercialproperty.ua/references/warehouse.php>
8. Profesiini rishennia dlia skladskoi lohistyky. «IMVO» COMPANY. Available: http://www.imvo.lviv.ua/uploads/files/IMVO_presentation_ukr.pdf. Last accessed: 12.12.2016.
9. Evteev, S. Aiti – logistika i sklad: kompleksnye resheniia dlia avtomatizatsii logistiki. *IT*. Available: <http://www.it.ru/itr/id/effect.pdf>
10. *Knight Frank*. Available: <http://www.knightfrank.ru/>
11. Directive 2012/27/EU of the European Parliament and of the Council of 25 October 2012. (2012). *Official Journal of the European Union*, L 315/1. Available: <http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2012:315:0001:0056:en:PDF>
12. *Sostoiannie, tranzitnyi potentsial, problemy i perspektivy razvitiia Sistemy mezhdunarodnykh transportnykh koridorov (MTK) Rossii na primere dostavki i tamozhennogo oformleniia mezhdunarodnykh ekspress-gruzov*. (2014, June). Riga. Available: http://www.rms-forum.lv/admuploads/file/3_shljapnikov_transbaltica_2014.pdf
13. Karpenko, O. A., Kovalchuk, S. O., Yefimova, Ye. O. (2012). Doslidzhennia perevah lohistychnoho pidkhotu pry orhanizatsii system materialno-tekhnicnoho zabezpechennia pidpriemstv. *Upravlinnia proektamy, systemnyi analiz i lohistyka. Tekhnichna seria*, 9, 82–85.
14. Nikolaichuk, V. (1999). Vzaimosviaz' i razlichia logistiki i marketinga. *Economy of Ukraine*, 4. Available: <http://masters.donntu.org/2003/fem/gavrischuk/library/index1.htm>
15. Krykavskiy, Ye. (1997). *Ekonomichniy potentsial lohistychnykh system*. Lviv: DU «Lvivska politekhnika», 168.
16. Oklander, M. A. (2000). *Kontury ekonomichnoi lohistyky*. Kyiv: Naukova dumka, 174.
17. Sergeev, V. I. (2001). *Logistika v biznese*. Moscow: INFRA-M, 608.
18. Harrison, A., Van Hoek, R. (2004). *Logistics Management and Strategy*. Ed. 2. Financial Times/Prentice Hall, 336.
19. Classification warehouse. (2014, April 11). *Bachfest Leipzig*. Available: <http://bachfest-leipzig.com/classification-warehouse/>
20. *SwissReal Group*. Available: <http://swissreal.com/>
21. Goswami, D. Y., Kreith, F. (2015). *Energy Efficiency and Renewable Energy*. Ed. 2. CRC Press, 1846.
22. *Energy Efficiency Indicators: Fundamentals on Statistics*. (2014). Paris: OECD/IEA, 388.
23. Ozadowicz, A., Grella, J. (2016). Energy saving in the street lighting control system – a new approach based on the EN-15232 standard. *Energy Efficiency*, 1–14. doi:10.1007/s12053-016-9476-1
24. Hernández-Santoyo, J., Sánchez-Cifuentes, A. (2003). Trigeneration: an alternative for energy savings. *Applied Energy*, 76 (1-3), 219–227. doi:10.1016/s0306-2619(03)00061-8
25. Ghicajanu, M. (2008). Programs of Energy Efficiency – Demand Side Management (DSM). *International conference on economics, law and management*. Available: <http://www.upm.ro/proiecte/EEE/Conferences/papers/S335.pdf>
26. Opryshko, V. (2016). Osoblyvosti intehratsii osnovnykh program i metodiv z keruvannia popytom spozhyvannia elektroenerhii. *III Mizhnarodna naukovo-tekhnicna ta navchalno-metodychna konferentsiia «Enerhetychnyi menedzhment: stan ta perspektivy rozvytku – PEMS16»*, 88–89.
27. Stognii, B. S., Kyrylenko, O. V., Prahovnyk, O. V., Denysiuk, S. P. (2012). The evolution of intelligent electrical networks and their prospects in Ukraine. *Tekhnichna Elektrodynamika*, 5, 52–67.
28. Drehsler, R.; Translation from Czech: Okin, A. A. (1985). *Izmerenie i otsenka kachestva elektroenerhii pri nesimmetrichnoi i nelinейnoi nagruzke*. Moscow: Energoatomizdat, 113.

DOI: 10.15587/2312-8372.2017.99919

OPTIMIZATION OF «FUEL ELECTRIC GENERATOR – ELECTRIC MOTOR» SYSTEM IN CAD

page 46–50

Stanovskiy Alexander, Doctor of Technical Science, Professor, Department of Oilgas and Chemical Mechanical Engineering, Odessa National Polytechnic University, Ukraine, e-mail: ostanovskiy@gmail.com, ORCID: <http://orcid.org/0000-0002-0360-1173>

Shvets Pavel, PhD, Associate Professor, Department of Energy Supply and Energy Management, Odessa National Polytechnic University, Ukraine, e-mail: pshvets@mail.ru, ORCID: <http://orcid.org/0000-0002-4213-0730>

Bondarenko Viktor, Senior Lecturer, Department of Energy Supply and Energy Management, Odessa National Polytechnic University, Ukraine, e-mail: snow_dog@ukr.net, ORCID: <http://orcid.org/0000-0001-5591-1504>

Naumenko Ievgeniia, Senior Lecturer, Department of Oilgas and Chemical Mechanical Engineering, Odessa National Polytechnic University, Ukraine, e-mail: jenyanaumenko@mai.ru, ORCID: <http://orcid.org/0000-0002-6963-3995>

Hussain Valid, Postgraduate Student, Department of Oilgas and Chemical Mechanical Engineering, Odessa National Polytechnic University, Ukraine, e-mail: walidsheer@hotmail.com, ORCID: <http://orcid.org/0000-0003-1375-6352>

Dobrovolskaya Victoria, Postgraduate Student, Department of Oilgas and Chemical Mechanical Engineering, Odessa National Polytechnic University, Ukraine, e-mail: dlv5@ukr.net, ORCID: <http://orcid.org/0000-0002-3372-4852>

The main problems of computer-aided design of «fuel electric generator – asynchronous electric motor» systems stem from the fact that these systems can't be considered separately during optimization. Theoretically, the increase in production efficiency due to CAD, which ensures the optimization of equipment parameters for global connectivity, is proved.

A computational model of «fuel electric generator – asynchronous electric motor» system with comparable energy parameters of the source and the consumer, which takes into account the processes that occur not only in the electric motor, but also in the generator is proposed. The concept of a «global connectivity» between the arguments of a projected object as a characteristic of the relationship between the parameters of subsystems is

suggested, when such connection dominates over others. In the sense that it is present in the largest number of computational models, in connection with which, its calculation has a decisive influence on the design object as a whole. The method of calculation of «fuel electric generator – asynchronous electric motor» systems in CAD is proposed, in which the intermediate objective function is not one of the consumer qualities of the object, but the nominal global connectivity between the elements of the system.

In Odessa, LLC «Specialized Energetic Enterprise «Energo-KOM» (Ukraine), a CAD test of electrical equipment «OPTIGLOC» is conducted, which is based on the proposed models and methods. As the object of computer-aided design, «diesel generator – asynchronous induction motor» system is used. As a result of the tests it is found that the use of the CAD «OPTIGLOC» allows to reduce the specific fuel consumption in the generator by 5.3 %. At the same time, the service life of the system and the stability of its technical tasks do not change, and the design time is reduced by an average of 13.7 %.

Keywords: fuel electric generator, slip of asynchronous electric motor, optimization in CAD, global connectivity.

References

1. Stanovskiy, O., Shvets, P., Toropenko, A., Bondarenko, V., Abu, S. O., Krasnozhan, O., Stanovskiy, A. (2016). Connectivity optimization of the elements in the tasks of computer-aided system design. *Bulletin of the National Technical University «Kharkiv Polytechnic Institute»: Mechanical-technological systems and complexes*, 49, 170–175.
2. Stanovskiy, O., Shvets, P., Bondarenko, V., Toropenko, A., Abu, S. O., Hussain, W. (2016). Mathematical modeling and optimization of complex systems on a global connection parameters in CAD. *Materials of IX Annual Scientific Conference «Information Technology and Automation – 2016»*. Odessa, 8–9.
3. Stanovskiy, O., Shvets, P., Toropenko, A. (2013). SAPR elektrotehnicheskogo oborudovaniia so slabosviazannymi elementami. *Suchasni tekhnologii v mashynobuduvanni*, 8, 133–143.
4. Induction (Asynchronous) Motors. (2012, December 2). *Mississippi State University Dept of Electrical and Computer Engineering, Course ECE 3183, 'Electrical Engineering Systems for non-ECE majors'*. Available: http://www.pssurvival.com/PS/Motors/Induction_Motor-2017.pdf
5. Wheel asynchronous traction motor with external rotor. (2001). *Neudorfer. Glasers Annalen*, 6/7, 237–242.
6. Stallcup, J. G., Stallcup, J. W. (2011). *Stallcup's® Generator, Transformer, Motor and Compressor*. Jones & Bartlett, 392.
7. Goldberg, O. D., Gurin, Ya. S., Sviridenko, I. S. (2001). *Proektirovanie elektricheskikh mashin*. Moscow: Vysshaya shkola, 431.
8. Silin, L. F. (2002). *Proektirovanie asinhronnykh dvigatelei*. Krasnoyarsk: IPTs KGTU, 236.
9. Ozyurt, C. H. (2005). *Parameter and Speed Estimation of Induction Motors from Manufacturers Data and Measurements*. Middle East Technical University, 156.
10. Say, M. G., Laughton, M. A. (2003). Units, Mathematics and Physical Quantities. *Electrical Engineer's Reference Book*. Elsevier, 1–32. doi:10.1016/b978-075064637-6/50001-0
11. Yeadon, W., Yeadon, A. (2001). *Handbook of Small Electric Motors*. McGraw-Hill, 1040.
12. Islam, R., Husain, I., Fardoun, A., McLaughlin, K. (2009). Permanent-Magnet Synchronous Motor Magnet Designs With Skewing for Torque Ripple and Cogging Torque Reduction. *IEEE Transactions on Industry Applications*, 45 (1), 152–160. doi:10.1109/tia.2008.2009653
13. Stanovskiy, O., Shvets, P., Bondarenko, V., Toropenko, A. (2016). The complex systems parameters mathematical modeling and optimization by global connectivity in CAD. *ScienceRise*, 9(2(26)), 6–12. doi:10.15587/2313-8416.2016.77768
14. *Sistemy avtomatizirovannogo proektirovaniia SAPR CAD/CAM/CAE. Ogranicheniia*. Available: <http://sapr-cad.ru/glava-optimizatsiya/ogranicheniya>. Last accessed: 13.01.2015.
15. Kim, K.-C., Lim, S.-B., Koo, D.-H., Lee, J. (2006). The Shape Design of Permanent Magnet for Permanent Magnet Synchronous Motor Considering Partial Demagnetization. *IEEE Transactions on Magnetics*, 42 (10), 3485–3487. doi:10.1109/tmag.2006.879077
16. Novikov, G. V. (2016). *Chastotnoe upravlenie asinhronnymi elektrodvigateliami*. Moscow: MSTU n.a. N. E. Bauman, 498.
17. Pravila i rekomendatsii po regulirovaniu chastoty i peretokov. *Protocol of the CIS Electric Power Council № 32 of October 12, 2007*. Available: http://so-ups.ru/fileadmin/files/company/rn-tpolitics/frequency/specdocs/sto_standard/Pravila_i_rekomendacii_po_regulirovaniju_chastoty_i_peretokov.pdf
18. *Ustroistvo zashchity generatora REG670 2.0. Product Guide*. (2016). ABB. Available: https://library.e.abb.com/public/fb4796d866104dd39be0a4df1d165821/1MRK502054-BRU_B_ru_____REG670_2.0.pdf. Last accessed: 22.07.2016.
19. Nakonechnyi, M. P., Ivanchenko, O. V. (15.08.2002). Device for measuring shaft rotation frequency. *Patent of Ukraine № 48585*. Appl. № 2001107119. Filed 19.10.2001. Bull. № 8. Available: <http://uapatents.com/3-48585-pristriij-dlya-vimiryuvannya-shvidkosti-obertannya-vala.html>
20. *IEEE 112. IEEE Standard Test Procedure for Polyphase Induction Motors and Generators*. (2004). New York: IEEE. Available: https://engineering.purdue.edu/~dionysis/EE452/Lab12/IEEEstd_112.pdf. doi:10.1109/ieeestd.2004.95394

DOI: 10.15587/2312-8372.2017.100058

RELIABLY-ORIENTED ANALYSIS OF A SINGLE STAGE COOLER THERMOELEMENT CONSTRUCTION

page 51–57

Zaykov Vladimir, PhD, Chief of Sector, Research Institute «STORM», Odesa, Ukraine, e-mail: gradan@i.ua, ORCID: <http://orcid.org/0000-0002-4078-3519>

Mescheryakov Vladimir, Doctor of Technical Sciences, Professor, Head of the Department of Informatics, Odessa State Environmental University, Ukraine, e-mail: gradan@ua.fm, ORCID: <http://orcid.org/0000-0003-0499-827X>

Zhuravlov Yurii, PhD, Senior Lecturer, Department of Technology of Materials and Ship Repair, National University «Odessa Maritime Academy», Ukraine, e-mail: zhuravlov.y@ya.ru, ORCID: <http://orcid.org/0000-0001-7342-1031>

The object of research is a model of the relationship between the reliability indicators of a single stage thermoelectric cooler and the geometry of the thermoelement, i.e., the ratio of its length to the cross-sectional area. Existing studies are limited to analyzing the influence of the geometry of thermoelements on the performance of cooling capacity, so the aim of the analysis is to determine the possibility of improving reliability in various modes of cooler operation. As a method of research, mathematical modeling is chosen, which allows to predict the reliability of coolers at the design stage. The influence of the geometry of thermoelements in the range from 4.5 to 20 on the power and structural parameters of the thermoelectric cooler is analyzed to select the best option for the criterion of the minimum failure rate. The analysis is performed for temperature differences in the range of the device's operability from 0 K to 60 K and operating modes from the maximum of the cooling capacity to the minimum of the failure rate taking into account energy and design constraints. An example of the use of the proposed analysis using unified thermoelectric modules is presented, which shows the possibility of reducing the relative failure rate of a thermoelectric cooler by more than 3 times due to the choice of the geometry of thermoelements. The main advantage of the proposed approach is that

it is possible to increase the reliability of thermoelectric coolers without changing the production technology and used materials.

Keywords: thermoelectric coolers, operating mode, reliability indicators, geometry of thermoelement branches.

References

1. Gromov, G. (2014). Obiemye ili tonkoplenochnye termoelektricheskie moduli. *Components & Technologies*, 8, 108–113.
2. Zebarjadi, M., Esfarjani, K., Dresselhaus, M. S., Ren, Z. F., Chen, G. (2012). Perspectives on thermoelectrics: from fundamentals to device applications. *Energy Environ. Sci.*, 5 (1), 5147–5162. doi:10.1039/c1ee02497c
3. Jurgensmeyer, A. L. (2011). *High Efficiency Thermoelectric Devices Fabricated Using Quantum Well Confinement Techniques*. Colorado State University, 54.
4. Zhang, L., Wu, Z., Xu, X., Xu, H., Wu, Y., Li, P., Yang, P. (2010). Approach on thermoelectricity reliability of board-level back-plane based on the orthogonal experiment design. *International Journal of Materials and Structural Integrity*, 4 (2/3/4), 170–185. doi:10.1504/ijmsi.2010.035205
5. Zaykov, V., Mescheryakov, V., Ignatovskaya, V. (2011). Thermal load influence on reliability parameters of two-stage thermoelectric cooling devices. *Eastern-European Journal of Enterprise Technologies*, 4(9(52)), 34–38. Available: <http://journals.urau.ua/eejet/article/view/1477>
6. In: Rowe, D. (2012). Materials, Preparation, and Characterization in Thermoelectrics. *Thermoelectrics and its Energy Harvesting, 2 Volume Set*. CRC Press, 1120. doi:10.1201/b11891
7. Sootsman, J. R., Chung, D. Y., Kanatzidis, M. G. (2009). New and Old Concepts in Thermoelectric Materials. *Angewandte Chemie International Edition*, 48 (46), 8616–8639. doi:10.1002/anie.200900598
8. Choi, H.-S., Seo, W.-S., Choi, D.-K. (2011). Prediction of reliability on thermoelectric module through accelerated life test and Physics-of-failure. *Electronic Materials Letters*, 7 (3), 271–275. doi:10.1007/s13391-011-0917-x
9. Wereszczak, A. A., Wang, H. (2011). Thermoelectric Mechanical Reliability. *Vehicle Technologies Annual Merit Review and Peer Evaluation Meeting*. Oak Ridge National Laboratory, 18.
10. Singh, R. (2008). *Experimental characterization of thin film thermoelectric materials and film deposition via molecular beam epitaxy*. Santa Cruz: University of California, 158.
11. *Thermoelectric modules market. Analytical review*. (2009). Moscow: RosBusinessConsulting, 92.
12. Zaykov, V. P., Kinshova, L. A., Moiseev, V. F. (2009). *Prognozovanie pokazatelei nadezhnosti termoelektricheskikh ohlazhdaiushchih ustroystv. Kniga 1. Odnokaskadnye ustroystva*. Odessa: Politehperiodika, 120.
13. Yampurin, N. P., Baranova, A. V. (2010). *Osnovy nadezhnosti elektronnykh sredstv*. Moscow: Akademiia, 240.