



ABSTRACTS AND REFERENCES

CHEMICAL AND TECHNOLOGICAL SYSTEMS

DOI: 10.15587/2312-8372.2017.112900

STUDY OF THE STRUCTURE OF ORGANO-MODIFIED PALYGORSKITE

page 4–8

Zhdanyuk Nataliya, Assistant, Department of Chemical Technology of Ceramics and Glass, National Technical University of Ukraine «Igor Sikorsky Kyiv Polytechnic Institute», Ukraine, e-mail: zhdanyukn.kpi@gmail.com, ORCID: <http://orcid.org/0000-0003-3771-5045>

The object of research is a natural silicate with a layer-band structure - palygorskite of the Cherkasy deposit (Ukraine). One of the problematic areas in the technology of sorption purification of aqueous media using palygorskite is the absence of kinship of the mineral in anionic forms of pollution. Therefore, its use as a sorbent to extract ions Cr(VI), U(VI), As(V), which are in aqueous media in anionic forms, is ineffective.

In the course of the study, XRD methods, thermal analysis and a spectrophotometric method are used to study the sorption properties of synthesized materials.

The structures of palygorskite and modified samples are studied using-ray diffraction analysis (XRD). After treatment with Na-PG, changes in its crystal structure are observed. There is a shift of the peaks toward large angles 2θ . Comparison of the diffractograms OPG-1 and OPG-2 allows to conclude that the reflection with the same indices is not relatively displaced, but their intensity is different. In OPG-2, the intensity of most peaks is higher.

The thermal properties of palygorskite and the resulting composites are studied. According to the results of sorption studies, it is established that palygorskite modified at a ratio of CEC/surfactant=1 can remove up to 97.8 % of Cr(VI) ions. This is 16.2 times more than adsorbing natural palygorskite.

As a result of studies of the Cr(VI) adsorption on Na-PG, OPG-1 and OPG-2, it has been shown that modifying the palygorskite surface by GDTMA can increase the adsorption of Cr(VI) from 0.45 mg/g and 9.2 mg/g, respectively. And for the initial concentration of the solution is 100 mg/l to 4.2 and 12.3 mg/l, respectively.

Increasing the volume of practical use of natural silicate materials contributes to a comprehensive solution of environmental issues, resource saving and technology for the production of sorbents for the extraction of anionic forms of Cr(VI) and U(VI) from aqueous solutions.

Keywords: palygorskite, hexadecyltrimethylammonium bromide, cationic surfactant, Cr(VI) adsorption.

References

- Holembiovskyi, A. O., Kovalchuk, I. A., Kornilovich, B. Yu., Zhdanyuk, N. V. (2011). Vylichennia spoluk U(VI) z vod iz vykorystanniam orhanohlyny. *Naukovi visti NTUU «KPI»*, 6, 154–158.
- Tarasevych, Yu., Ovcharenko, F. (1975). *Adsorbsii na glinistykh mineralakh*. Kyiv: Naukova dumka, 351.
- Bergaya, F., Theng, B. K. G., Lagaly, G. (2006). *Handbook of Clay Science*, Vol. 1. Elsevier, 1246.
- Swarnakar, V., Agrawal, N., Tomar, R. (2011). Sorption of Cr (VI) & As (V) on HDTMA – Modified Zeolites. *International Journal of Scientific & Engineering Research*, 2 (5), 1–9.
- Xu, S., Boyd, S. A. (1995). Cationic Surfactant Sorption to a Vermiculitic Subsoil via Hydrophobic Bonding. *Environmental Science & Technology*, 29 (2), 312–320. doi:10.1021/es00002a006
- Mittal, V., Herle, V. (2008). Physical adsorption of organic molecules on the surface of layered silicate clay platelets: A thermogravimetric study. *Journal of Colloid and Interface Science*, 327 (2), 295–301. doi:10.1016/j.jcis.2008.08.036
- Anderson, M. A., Trouw, F. R., Tam, C. N. (1999). Properties of Water in Calcium- and Hexadecyltrimethylammonium-Exchanged Bentonite. *Clays and Clay Minerals*, 47 (1), 28–35. doi:10.1346/ccmn.1999.0470103
- Majdan, M., Pukus, S., Rzaczynska, Z., Iwan, M., Maryuk, O., Kwiatkowski, R., Skrzypek, H. (2006). Characteristics of chabazite modified by hexadecyltrimethylammonium bromide and of its affinity toward chromates. *Journal of Molecular Structure*, 791 (1-3), 53–60. doi:10.1016/j.molstruc.2005.12.043
- Li, Z., Willms, C. A., Kniola, K. (2003). Removal of Anionic Contaminants using Surfactant-modified Palygorskite and Sepiolite. *Clays and Clay Minerals*, 51 (4), 445–451. doi:10.1346/ccmn.2003.0510411
- Zhdanyuk, N., Bykov, O. (2017). Characteristics of organofertilized palygorskite and of its affinity toward chromates. *Bulletin of NTU «KhPI». Series: Mechanical-technological systems and complexes*, 19 (1241), 11–16.
- Sarkar, B., Xi, Y., Megharaj, M., Krishnamurti, G. S. R., Rajarathnam, D., Naidu, R. (2010). Remediation of hexavalent chromium through adsorption by bentonite based Arquad® 2HT-75 organoclays. *Journal of Hazardous Materials*, 183 (1-3), 87–97. doi:10.1016/j.jhazmat.2010.06.110
- Zhdanyuk, N. V. (2017). Adsorbsii ioniv Cr (VI) ta Co (II) palyhorskitem modyifikovanym kationnymy poverkhnevo-aktyvnymy rechovynamy. *Vestnik Odesskogo natsionalnogo universiteta*, 22(3 (63)), 73–78.
- Lurie, Yu. Yu. (1989). *Analiticheskaiia himiia promyshlennyyh stochnyh vod*. Moscow: Khimiia, 448.
- Ivanova, V. P., Kasatov, B. K., Krasavina, T. N., Rozinova, E. L. (1974). *Termicheskii analiz mineralov i gornyh porod*. Leningrad: Nedra, 399.
- Yariv, S., Cross, H. (2001). *Organoclay Complexes and Interactions*. CRC Press, 680.

ECOLOGY AND ENVIRONMENTAL TECHNOLOGY

DOI: 10.15587/2312-8372.2017.112782

JUSTIFICATION OF THE CALCULATION METHODS OF THE MAIN PARAMETERS OF VORTEX CHAMBERS

page 9–13

Pitak Inna, PhD, Associate Professor, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: ipitak5@gmail.com, ORCID: <http://orcid.org/0000-0002-5073-2942>

Shaporev Valery, Doctor of Technical Sciences, Professor, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, ORCID: <http://orcid.org/0000-0003-1652-4688>

Briankin Serhii, Head of Course of the Faculty of Military Training, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: serzh2082@ukr.net, ORCID: <https://orcid.org/0000-0003-0444-9107>

Pitak Oleg, PhD, Associate Professor, Department of Labour Protection and the Environmental, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: opitak77@gmail.com, ORCID: <https://orcid.org/0000-0001-5912-4604>

The object of research is vortex dust collectors – apparatus in which hydrodynamic regimes are realized. Advantages of using vortex apparatus: work with gases of high temperature, high degree of purification; regulation of the process of gas cleaning from dust due to regulating the secondary air flow. Among the disadvantages of vortex dust collectors are: high hydraulic resistance, the need for powerful blowing apparatus, as well as difficult operation and installation. Apparatus for swirling the flow have a different design and, depending on the gas flow rate, pressure and physicochemical properties of the gas flow at the inlet to the cleaning apparatus, this or that hydrodynamic regime is created in it. When designing vortex chambers, the following design parameters must be observed: $D_s/D \approx 0.8$; $D_i/D_s \approx 0.5$; $D_w/D \approx 0.5 \pm 0.8$; the inclination angle of the vortex blades at the inlet of the main flow is $\beta \approx 30 \pm 60^\circ$; the inclination angle of the secondary flow nozzles is $\alpha \approx 30 \pm 45^\circ$. When calculating and designing a vortex chamber, it is necessary to fulfill the conditions for the constancy of the tangential velocity of the total flow along the entire length of the working cavity of the apparatus, ensuring the maximum possible efficiency of its functioning.

Analysis of the obtained results for justification of the methods for calculating the basic parameters of the vortex chambers indicates the expediency of using such methods for calculating gas cleaning equipment.

When implementing the process of cleaning dust-gas flows in vortex apparatus, not only the processes of agglomeration of dust are observed, but also the destruction of gas toxicants.

Mathematical dependencies are considered to allow make predictive estimations to select the conditions of the dry dust removal process and to select the design parameters of the vortex chamber. This opens prospects for the introduction of vortex apparatus in order to reduce the industrial negative impact on the environment, namely the atmosphere.

Keywords: vortex apparatus, environment, disperse flow, gas flow, gas velocity.

References

1. Konovalov, V. I., Orlov, A. Yu., Kudra, T. (2012). Design Calculation of Ranque-Hilsch Vortex Tubes. *Vestnik Tambovskogo gosudarstvennogo tehnicheskogo universiteta*, 18 (1), 74–107.
2. Batluk, V. A., Proskurina, I. V., Liashenky, A. V. (2010). Matematychna model protsesu ochyshchennia zapylenoho potoku u vidtsentrovo-inertsiiykh pylovloviuvachakh. *Promyslova hidravlika i pnevmatyka*, 1 (27), 31–36.
3. Landau, L. D. (1988). *Teoreticheskaya fizika. Vol. VI. Gidrodinamika*. Moscow: Nauka, 736.
4. Shakerin, S. (2010). Vortex Apparatus and Demonstrations. *The Physics Teacher*, 48 (5), 316–318. doi:10.1119/1.3393063
5. Iliescu, M. S., Ciocan, G. D., Avellan, F. (2008). Analysis of the Cavitating Draft Tube Vortex in a Francis Turbine Using Particle Image Velocimetry Measurements in Two-Phase Flow. *Journal of Fluids Engineering*, 130 (2), 021105. doi:10.1115/1.2813052
6. Turik, V. N., Babenko, V. V., Voskoboinikov, V. A., Voskoboinikov, A. V. (2009). Formirovanie vihrei gertlera v vihrevoi kamere. *Promyslova hidravlika i pnevmatyka*, 3 (25), 31–36.
7. Pirashvili, Sh. A. (2013). *Vihrevoi effekt. Vol. 1. Fizicheskoe iavlenie, eksperiment, teoreticheskoe modelirovanie*. Moscow: Nauchtehizdat, 337.
8. Proskurina, I. V. (2009). Pryntsypove nove v metodakh ochystky povitria vid pylu v protsesakh vydobuvannia koksu z kamer koksovych batarei. *Eastern-European Journal of Enterprise Technologies*, 4(9 (40)), 12–15. Available at: <http://journals.uran.ua/eejet/article/view/22271/19949>
9. Bona, C., Palenzuela-Luque, C., Bona-Casas, C. (2009). Elements of Numerical Relativity and Relativistic Hydrodynamics. *Lecture Notes in Physics*, 783. Berlin, Heidelberg: Springer, 214. doi:10.1007/978-3-642-01164-1
10. Pitak, I. V. (2010). Issledovaniya protsessa mokrogo ulavlivaniia pyli v rotornom vihrevom apparate. *Visnyk natsionalnoho tekhnichnoho universytetu «KhPI»*, 17, 135–140.
11. Thakare, H. R., Monde, A., Parekh, A. D. (2015). Experimental, computational and optimization studies of temperature separation and flow physics of vortex tube: A review. *Renewable and Sustainable Energy Reviews*, 52, 1043–1071. doi:10.1016/j.rser.2015.07.198
12. Bogomolov, A., Sergina, N., Kondratenko, T. (2016). On Inertial Systems, Dust Cleaning and Dust Removal Equipment, and Work Areas in the Production of Aerated Concrete from the Hopper Suction Apparatus CSF. *Procedia Engineering*, 150, 2036–2041. doi:10.1016/j.proeng.2016.07.290
13. Dekterev, A. A., Gavrilov, A. A., Minakov, A. A. (2010). Sovremennyye vozmozhnosti CFD SIGMAFLOW dlia resheniya teplofizicheskikh zadach. *Sovremennaya nauka*, 2 (4), 117–122.
14. Pitak, I. (2014). Study of experimental-industrial design of rotary vortex machine. *Technology Audit and Production Reserves*, 3 (2(17)), 33–38. doi:10.15587/2312-8372.2014.26212
15. Tovazhnianskyi, L. L., Shaporev, V. P., Pitak, I. V. et al. (2011). *Mashyny i aparaty u khimichnykh, kharchovykh i pererobnykh vyrabnytstvakh*. Kharkiv: Kolehium, 610.

DOI: 10.15587/2312-8372.2017.112786

INFLUENCE OF THE INLET FLOW SWIRLER CONSTRUCTION ON HYDRODYNAMICS AND EFFICIENCY OF WORK

page 14–22

Pitak Inna, PhD, Associate Professor, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: ipitak5@gmail.com, ORCID: <https://orcid.org/0000-0002-5073-2942>

Briankin Serhii, Head of Course of the Faculty of Military Training, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: serzh2082@ukr.net, ORCID: <https://orcid.org/0000-0003-0444-9107>

Pitak Oleg, PhD, Associate Professor, Department of Labour Protection and the Environmental, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: opitak77@gmail.com, ORCID: <https://orcid.org/0000-0001-5912-4604>

Shaporev Valery, Doctor of Technical Sciences, Professor, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, ORCID: <https://orcid.org/0000-0003-1652-4688>

Petrushin Serhii, PhD, Associate Professor, Department of Radiation, Chemical, Biological Protection, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: s_petrushin@ukr.net, ORCID: <https://orcid.org/0000-0003-4228-4622>

The object of research is construction of a vortex dust collector. To solve the problem of increasing the efficiency of dust cleaning in a vortex apparatus with revealing the features of the mechanism and the destructive forces of the process, the features of the hydrodynamic regime of rotation of the gas-dust flow in the zone of the swirl and immediately after it are used.

The influence of the swirl construction and the location of its installation in the gas duct for feeding the gas-dust flow on the efficiency of the vortex apparatus is studied. It is shown that the aerodynamic processes that determine the nature of the flow rotation and its flow in the flue after the swirl reach the maximum possible angular velocity of the gas flow rotation in the separation chamber for this construction. It is proved that the swirl construction under the appropriate conditions allows

a swirling flow leaving the duct to the separation chamber to reach the maximum possible angular velocity of the gas flow rotation for the given construction. The characteristic regimes of the gas-dust flow in the duct are established immediately after the swirler from its construction. It is shown that for a traditional vane swirler with a swirling flow in one direction, the most effective blade inclination angle corresponds to 45°. Its installation must be carried out in the duct from the end outlet to the separation chamber below by 1.4 + 1.6 of the swirler diameter. Before the gas-dust flow flows into the separator, the flow is agglomerated with dust particles. At the exit of the gas-dust flow from the end of the flue to the separation space, the maximum value of the angular velocity of the flow in the separator is ensured. It is established that the blade vortex, which provides for the organization of coaxial turbulent flows in the flue, twisted in opposite directions, will allow more efficient agglomeration of dust particles. A basic construction of the vortex dust collector is developed, which makes it possible to increase the cleaning efficiency with a vortex device to 98–99 %.

Keywords: swirler construction, dust agglomeration, angular velocity of gas flow rotation.

References

1. Halich, R. V., Yakuba, R. V., Sklabinskii, V. I., Storozhenko, V. Ya. (2013). Konstruktivnoe usovershenstvovanie vihrevykh apparatov so vtorichnymi zakruchennymi potokami. *Khimichna promyslovist Ukrayny*, 3, 75–83.
2. Akhesmeh, S., Pourmahmou, N., Sedgi, H. (2008). Numerical Study of the Temperature Separation in the Ranque-Hilsch Vortex Tube. *American Journal of Engineering and Applied Sciences*, 1 (3), 181–187. doi:10.3844/ajeassp.2008.181.187
3. Halich, R. V. (2014). *Vplyv vykhidnykh prystroiv na hidrodynamiku i efektyvnist vykhrovych pylcovloviuvachiv*. Sumy, 27.
4. Pourmahmound, N., Akhesmeh, S. (2008). Numerical investigation of the termal separation in a vortex tube. *Proceedings of world academy of science, engineering and technology*, 33, 409–415.
5. Pavlychenko, A. V., Kolesnyk, V. Ye. (2016). Rozrobka sposobiv znyzhennia rivnia ekolohichnoi nebezpeky vid pylovykh vykydiv v vuhihnykh shakhtakh. *Geo-Technical Mechanics*, 127, 141–150.
6. Nezhad, H., Shamsoddini, R. (2009). Numerical three-dimensional analysis of the mechanism of flow and heat transfer in a vortex tube. *Thermal Science*, 13 (4), 183–196. doi:10.2298/tsci0904183n
7. Kolesnyk, V. Ye., Dolhova, T. I., Kulikova, D. V., Pavlychenko, A. V. (2016). *Sposoby i zasoby pidvyshchennia ekolohichnoi bezpeky skydu shakhtnykh vod v poverkhnevi vodoimy*. Dnipro: Litohraf, 132.
8. Halich, R. V., Yakuba, A. R., Sklabinskii, V. I., Storozhenko, V. Ya. (2014). Razrabotka i vnedrenie vihrevykh pyleulovitelei so vstrechnymi zakruchennymi potokami. *Himicheskoe i neftegazovoe mashinostroenie*, 3, 12–15.
9. Kolesnyk, V. E., Yurchenko, A. A., Lytvynenko, A. A., Pavlychenko, A. V. (2014). *Sposoby i zasoby pidvyshchennia ekolohichnoi bezpeky masovykh vybukhiv v zaliyorudnykh karierakh za pylomy chynnykom*. Dnipropetrovsk: Litohraf, 112.
10. Zuikov, A. L., Orehov, G. V., Volshanik, V. V. (2013). Raspredeniye azimutal'nyh skorostei v laminarnom kontrvihrevom techenii. *Vestnik MGSU*, 5, 150–161.
11. Kalashnik, M. V. (2008). Tsiklotroficheskoe prispobolenie v zakruchennyh gazovyh potokah i vihrevoi effekt Ranka. *ZhETF*, 133 (4), 935–947.

DOI: 10.15587/2312-8372.2017.112791

INVESTIGATION OF THE TREATMENT EFFICIENCY OF FINE-DISPERSED SLIME OF A WATER ROTATION CYCLE OF A METALLURGICAL ENTERPRISE

page 22–29

Shkop Andrii, PhD, Director, LTD «Scientific and Technical Center «Ecomash», Kharkiv, Ukraine, e-mail: shkop_ecomas@ukr.net, ORCID: <https://orcid.org/0000-0002-1974-0290>

Briankin Oleksandr, Postgraduate Student, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: bryankin@i.ua, ORCID: <https://orcid.org/0000-0002-7897-4417>

Shestopalov Oleksii, PhD, Associate Professor, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: shestopalov.it@khp.edu.ua, ORCID: <https://orcid.org/0000-0001-6268-8638>

Ponomareva Natalya, PhD, Associate Professor, Department of Integrated Technologies, Processes and Devices, National Technical University «Kharkiv Polytechnic Institute», Ukraine, ORCID: <https://orcid.org/0000-0001-8931-5882>

The features of the water rotation cycle and the slime treatment system of the oxygen-converter shop of metallurgical production are investigated. During the audit, it is revealed that the concentration of suspended solids in the water cycle system varies in time up to 500 g/l for the condensed slime and up to 85 g/l in the pre-clarified water. It is established that the slimes of the metallurgical enterprise contain a finely dispersed solids fraction in the slime up to 93 % of a size of less than 20 µm and the residues of a cationic flocculant that impede effective treatment of the slime in the sedimentation tanks. This leads to the following drawbacks: a decrease in the slime treatment efficiency, removal of the fine fraction of solids together with clarified water of radial thickeners, regular replenishment of clean water, discharge of part of the flow into the slime collector. It is proposed to install an additional treatment module and use a more efficient anionic flocculant. It is recommended to monitor the efficiency of treatment and dosing of the flocculant depending on the solids concentration in the slime by continuous sampling and testing of slime flocculation. It is established that effective treatment up to 99 % can be achieved on the treatment module using anionic flocculant, thin-layer sedimentation tanks and sedimentation horizontal screw centrifuges.

Keywords: gas treatment of metallurgical enterprise, fine-dispersed slimes, gas treatment slimes, treatment module.

References

1. Melnikov, I. T., Kutlubaev, I. M., Putalev, I. A., Shevtcov, N. S., Vasiliev, K. P. (2013). Investigation of sludge thickening for mining and metallurgical production. *Scientific World*, 14 (3), 18–25.
2. Radovic, N., Kamberovic, Z., Panias, D. (2009). Cleaner metallurgical industry in Serbia: A road to the sustainable development. *Chemical Industry and Chemical Engineering Quarterly*, 15 (1), 1–4. doi:10.2298/ciceq0901001r
3. Kovalenko, A. (2012). About gas purification sludges of domain and steel-smelting manufactures. *Eastern-European Journal of Enterprise Technologies*, 2(12 (56)), 4–8. Available at: <http://journals.uran.ua/ejet/article/view/3919/3587>
4. Shkop, A., Tseitlin, M., Shestopalov, O., Raiko, V. (2017). Research of ways to reduce mechanical influence on flocs in a centrifuge. *Technology Audit and Production Reserves*, 1(3 (33)), 39–45. doi:10.15587/2312-8372.2017.93690
5. Atamaniuk, A. A., Kasimov, A. M. (2012). K voprosu sgushcheniya suspenzii zhelezosoderzhashchih vzvesei stochnyh vod metallurgicheskogo kombinata «Zaporozhstal». *Metallurgicheskaya i gornorudnaya promyshlennost*, 5 (227), 95–97.
6. Sulimova, M. A., Litvinova, T. E. (2016). Metallurgical production waste treatment efficiency increase. *16th International Multidisciplinary Scientific GeoConference SGEM 2016, Conference Proceedings*, 2, 569–576.
7. Sun, Y. Y., Xu, C. Y., Nie, R. C., Zheng, J. H. (2013). Application of Flocculant and Coagulant to Coal Slime Water. *Advanced Materials Research*, 781–784, 2170–2173. doi:10.4028/www.scientific.net/amr.781-784.2170

8. Tripathy, T., De, B. R. (2006). Flocculation: A New Way to Treat the Waste Water. *Journal of Physical Sciences*, 10, 93–127.
9. Bolto, B., Gregory, J. (2007). Organic polyelectrolytes in water treatment. *Water Research*, 41 (11), 2301–2324. doi:10.1016/j.watres.2007.03.012
10. Heller, H., Keren, R. (2002). Anionic Polyacrylamide Polymers Effect on Rheological Behavior of Sodium-Montmorillonite Suspensions. *Soil Science Society of America Journal*, 66 (1), 19. doi:10.2136/sssaj2002.0019
11. Wang, W.-D., Wang, H.-F., Sun, J.-T., Sun, Y. (2013). Experimental study on slime water flocculation sediment based on the montmorillonite hydration expansion inhibition. *Journal of Coal Science and Engineering (China)*, 19 (4), 530–534. doi:10.1007/s12404-013-0414-y
12. Lopez-Maldonado, E. A., Oropeza-Guzman, M. T., Ochoa-Teran, A. (2014). Improving the Efficiency of a Coagulation-Flocculation Wastewater Treatment of the Semiconductor Industry through Zeta Potential Measurements. *Journal of Chemistry*, 2014, 1–10. doi:10.1155/2014/969720
13. Petzold, G., Mende, M., Lunkwitz, K., Schwarz, S., Buchhammer, H.-M. (2003). Higher efficiency in the flocculation of clay suspensions by using combinations of oppositely charged polyelectrolytes. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 218 (1–3), 47–57. doi:10.1016/s0927-757(02)00584-8
14. Shkop, A., Tseitlin, M., Shestopalov, O. (2016). Exploring the ways to intensify the dewatering process of polydisperse suspensions. *Eastern-European Journal of Enterprise Technologies*, 6(10 (84)), 35–40. doi:10.15587/1729-4061.2016.86085
15. Shkop, A., Tseitlin, M., Shestopalov, O., Raiko, V. (2017). Study of the strength of flocculated structures of polydispersed coal suspensions. *Eastern-European Journal of Enterprise Technologies*, 1(10 (85)), 20–26. doi:10.15587/1729-4061.2017.91031
16. Konduri, M. K. R., Fatehi, P. (2017). Influence of pH and ionic strength on flocculation of clay suspensions with cationic xylan copolymer. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 530, 20–32. doi:10.1016/j.colsurfa.2017.07.045

DOI: 10.15587/2312-8372.2017.112792

INVESTIGATION OF FLOCCULATION EFFICIENCY IN TREATMENT OF WET GAS TREATMENT SLIME OF FERROALLOYS PRODUCTION

page 29–39

Shkop Andrii, PhD, Director, LTD «Scientific and Technical Center «Ecomash», Kharkiv, Ukraine, e-mail: shkop_ecomass@ukr.net, ORCID: <https://orcid.org/0000-0002-1974-0290>

Briankin Oleksandr, Postgraduate Student, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: bryankin@i.ua, ORCID: <https://orcid.org/0000-0002-7897-4417>

Shestopalov Oleksii, PhD, Associate Professor, Department of Chemical Technique and Industrial Ecology, National Technical University «Kharkiv Polytechnic Institute», Ukraine, e-mail: shestopalov.it@khipi.edu.ua, ORCID: <https://orcid.org/0000-0001-6268-8638>

Ponomareva Natalya, PhD, Associate Professor, Department of Integrated Technologies, Processes and Devices, National Technical University «Kharkiv Polytechnic Institute», Ukraine, ORCID: <https://orcid.org/0000-0001-8931-5882>

The object of research is the process of wastewater treatment from suspended solids, formed as a result of wet gas treatment of the exhaust gases of ferroalloys production shop. As a result of the audit, it is revealed that the flocculation of slimes in the current water circulation cycle scheme does not occur with due

efficiency, since the dosing of the flocculant is made at one point in the slime water pipe, without adjusting its dose when the slime concentration, dispersion and chemical composition change. It is found that the gas treatment slimes have a high content of dissolved salts up to 26 g/l, a variable chemical composition and pH of 8 to 10, as well as a high proportion of fine particles of less than 40 µm in size. It is established that the peculiarities of mixing slimes with flocculant play an important role in flocculation. For effective treatment of slimes and elimination of these drawbacks, it is suggested to introduce flocculant not once but in two portions 35–40 % and 60–65 %, respectively, with a mixing time of up to 30 seconds of the first dose and about 10 seconds of the second dose. The possibilities of effective treatment of slime waters of wet gas treatment up to 0.35 g/l are established using sedimentation centrifugal plants. It is recommended to take the slime intake directly at the outlet from the ferrosilicon production shop with the solids phase fraction with a size larger than 40 µm in excess of 80 % and a concentration of up to 10 g/l.

Keywords: slime flocculation; fine slime, gas treatment slime, treatment module, ferroalloys production.

References

1. Kovalenko, A. (2012). About gas purification sludges of domain and steel-smelting manufactures. *Eastern-European Journal of Enterprise Technologies*, 2(12 (56)), 4–8. Available at: <http://journals.uran.ua/eejet/article/view/3919/3587>
2. Bolto, B., Gregory, J. (2007). Organic polyelectrolytes in water treatment. *Water Research*, 41 (11), 2301–2324. doi:10.1016/j.watres.2007.03.012
3. Ghimici, L., Dinu, I. A., Dragan, E. S. (2007). Application of polyelectrolytes in phase separation processes. *New Trends in Ionic (Co) Polymers and Hybrids*. NY, USA: Nova Science, Hauppauge, 31–64.
4. Zeng, D., Wu, J., Kennedy, J. F. (2008). Application of a chitosan flocculant to water treatment. *Carbohydrate Polymers*, 71 (1), 135–139. doi:10.1016/j.carbpol.2007.07.039
5. Schwarz, S., Petzold, G., Geissler, U., Smolka, N. (2004). Influence of humic acid on the flocculation of clay. *Colloid & Polymer Science*, 282 (7), 670–676. doi:10.1007/s00396-003-0989-8
6. Mende, M., Schwarz, S., Petzold, G., Jaeger, W. (2006). Destabilization of model silica dispersions by polyelectrolyte complex particles with different charge excess, hydrophobicity, and particle size. *Journal of Applied Polymer Science*, 103 (6), 3776–3784. doi:10.1002/app.25573
7. Tzoupanos, N. D., Zouboulis, A. I. (2011). Preparation, characterisation and application of novel composite coagulants for surface water treatment. *Water Research*, 45 (12), 3614–3626. doi:10.1016/j.watres.2011.04.009
8. Lee, K. E., Teng, T. T., Morad, N., Poh, B. T., Hong, Y. F. (2010). Flocculation of kaolin in water using novel calcium chloride-polyacrylamide (CaCl₂-PAM) hybrid polymer. *Separation and Purification Technology*, 75 (3), 346–351. doi:10.1016/j.separpur.2010.09.003
9. Lopez-Maldonado, E. A., Oropeza-Guzman, M. T., Ochoa-Teran, A. (2014). Improving the Efficiency of a Coagulation-Flocculation Wastewater Treatment of the Semiconductor Industry through Zeta Potential Measurements. *Journal of Chemistry*, 2014, 1–10. doi:10.1155/2014/969720
10. Shkop, A., Tseitlin, M., Shestopalov, O., Raiko, V. (2017). Research of ways to reduce mechanical influence on floccules in a centrifuge. *Technology Audit and Production Reserves*, 1(3 (33)), 39–45. doi:10.15587/2312-8372.2017.93690
11. Shkop, A., Tseitlin, M., Shestopalov, O. (2016). Exploring the ways to intensify the dewatering process of polydisperse suspensions. *Eastern-European Journal of Enterprise Technologies*, 6(10 (84)), 35–40. doi:10.15587/1729-4061.2016.86085
12. Shkop, A., Tseitlin, M., Shestopalov, O., Raiko, V. (2017). Study of the strength of flocculated structures of polydispersed coal suspensions. *Eastern-European Journal of Enterprise Technologies*, 1(10 (85)), 20–26. doi:10.15587/1729-4061.2017.91031

FOOD PRODUCTION TECHNOLOGY

DOI: 10.15587/2312-8372.2017.112912

RESEARCH OF THE EFFECTS OF TECHNOLOGICAL FACTORS ON THE QUALITY INDICES OF HIGH OLEIC SUNFLOWER OIL

page 40–48

Dichtyar Aliona, Assistant, Department of Food Technology, Kharkiv State University of Food Technology and Trade, Ukraine, e-mail: alenadikhtyar@ukr.net, ORCID: <http://orcid.org/0000-0003-3629-3688>

Fedak Natalia, PhD, Professor, Department of Food Technology, Kharkiv State University of Food Technology and Trade, Ukraine, e-mail: fedaknv@ukr.net, ORCID: <http://orcid.org/0000-0002-7460-3213>

Povovarov Yevgen, Doctor of Technical Sciences, Professor, Department of Food Technology, Kharkiv State University of Food Technology and Trade, Ukraine, e-mail: pcub@ukr.net, ORCID: <http://orcid.org/0000-0002-4964-1568>

Stepankova Galyna, PhD, Senior Lecturer, Department of Bread, Confectionary, Pasta and Food Concentrates, Kharkiv State University of Food Technology and Trade, Ukraine, e-mail: stepankova_galina@ukr.net, ORCID: <http://orcid.org/0000-0002-7969-5671>

Yarantseva Yevgeniia, PhD, Senior Lecturer, Department of Food Technology, Kharkiv State University of Food Technology and Trade, Ukraine, e-mail: Korotayeva1990@gmail.com, ORCID: <http://orcid.org/0000-0003-3166-0282>

The object of research is high oleic sunflower oil (HOSO) and refined deodorized sunflower oil (RDSO) as a control. The distinguishing characteristic of HOSO consists in the changed fatty acid composition, has a high content of triglycerides of oleic acid more than 89 %. HOSO has the following characteristics: ($\rho=915\ldots920 \text{ g/cm}^3$, $\eta=0.0180\pm0.0009 \text{ Pa}$, $t_{(\text{solidification})}=0\ldots-6^\circ\text{C}$, refractive index $1.466\ldots1.468$; TbN= $0.0100\pm0.0003 \text{ mg MA}/1000 \text{ g}$, PN= $0.83\pm0.02 \text{ mmol } \frac{1}{2} \text{ O/kg}$, SN= $184\ldots194 \text{ mg KOH}$, AN= $=0.112\pm0.003 \text{ mg KOH/g}$; IN= $105\pm5 \% I_2$; E $1\%/\text{1 cm} = 3.00\pm0.09$). One of the most problematic places for using oils is that they are faster than solid fats, refreshing products has less shelf life. In the course of the study, the influence of technological factors on the HOSO properties and the scientific basis for the HOSO use as a prescription component of food systems is determined. It is proved that during the storage HOSO is more resistant to processes in comparison with RDSO, since glycerides of polyunsaturated fatty acids oxidize faster than monounsaturated, confirming the experimental data of physicochemical parameters, fatty acid composition and dynamics of the content of tocopherols. HOSO stability for oxidation processes under conditions of prolonged thermal action in comparison with RDSO (control) by functional numbers (acid, peroxide, iodine, thiobarbituric) is studied. It is found that the oxidation rate in HOSO is lower than in the RDSO (control) by 2 times at the beginning of the heat treatment and by 1.23 times with the maximum duration of heat treatment. The coefficient of extinction grows to the limit of maximum permissible values at 6 hours in RDSO and 18 hours in HOSO, which confirms the HOSO thermal stability that is 3 times greater. Essential changes in the fatty acid composition and in the complex of tocopherols of oils under heat treatment conditions, the nature of which depends on the type of oil and the duration of heat treatment, are also shown, which also indicates a greater stability of HOSO for oxidation processes in comparison with

RDSO (control). On the basis of the research, recommendations are developed on the HOSO use in the technology of custard products and as a medium for frying. Rational conditions of the brewing process are $t=95\ldots100^\circ\text{C}$, $\tau=(3\ldots5)\times60 \text{ s}$, hydromodule «HOSO-water» – 1:2.5. Recommended parameters for the HOSO use as a medium for frying, in particular deep-fried: $t=160\ldots180^\circ\text{C}$, duration of continuous use $\tau=(0\ldots18)\times60^2 \text{ s}$, ratio «HOSO – semi-finished product» is 4:1, HOSO storage time is 24 months.

Thus, HOSO use will ensure the use of domestic raw materials; the maximum realization of the functional and technological properties of HOSO with obtaining high-quality products; reduction of energy costs and labor intensity of the process; introduction of resource-saving technologies using the newest principles of food production.

Keywords: high oleic sunflower oil, fatty acid composition, thermal effect, custard dough.

References

1. Kyrychenko, V. V., Kolomatska, V. P., Makliak, K. M., Syvchenko, V. I. (2010). Vyrobnytstvo soniashnyku v Ukrainsi: stan i perspektyvy. *Visnyk TsNZ APV Kharkivskoi oblasti*, 7, 281–287.
2. Davydovych, O. Ya., Palko, N. S. (2012). Netradytsiini vydy olii u vyrobnytstvi boroshnianykh kondyterskykh vyrobiv. *Produkty & ingredyenty*, 3, 8–9.
3. Tkachenko, A. S. (2015). Improvement of fatty-acid composition of sugar cookies by using of alternative oils. *Visnyk Lvivskoi komertsii no akademii: Seriia tovaroznavcha*, 15, 114–119.
4. Drobot, V. I., Pysarets, O. P. (2014). Vplyv kompleksnykh polipshuvachiv na perebih tekhnolohichnykh protsesiv ta yakist vyrobiv z kukurudzianym boroshnom. *Prodovolchi resursy*, 2, 40–42.
5. Topchii, O., Kotliar, Ye. (2015). Principles of blending fatty acid balanced vegetable oils. *Eastern-European Journal of Enterprise Technologies*, 1(6 (73)), 26–32. doi:10.15587/1729-4061.2015.35997
6. Karpova, A., Kunitsa, K., Biletskiy, E. (2017). *The technology of flour confectionery product using new prescription components*, 175.
7. Lozovaia, T. M. (2017). Ustanovka vliianiia netraditsiinnogo prirodnogo syria na protsessy okisleniia v konditerskom zhire. *Aktualnye nauchnye issledovaniia v sovremennom mire*, 6 (1), 52–57.
8. Rios, R. V., Pessanha, M. D. F., de Almeida, P. F., Viana, C. L., Lannes, S. C. da S. (2014). Application of fats in some food products. *Food Science and Technology (Campinas)*, 34 (1), 3–15. doi:10.1590/s0101-20612014000100001
9. Belingheri, C., Giussani, B., Rodriguez-Estrada, M. T., Ferrillo, A., Vittadini, E. (2015). Oxidative stability of high-oleic sunflower oil in a porous starch carrier. *Food Chemistry*, 166, 346–351. doi:10.1016/j.foodchem.2014.06.029
10. Roman, O., Heyd, B., Broyart, B., Castillo, R., Maillard, M.-N. (2013). Oxidative reactivity of unsaturated fatty acids from sunflower, high oleic sunflower and rapeseed oils subjected to heat treatment, under controlled conditions. *LWT – Food Science and Technology*, 52 (1), 49–59. doi:10.1016/j.lwt.2012.12.011
11. Aladedunye, F., Przybylski, R. (2013). Frying stability of high oleic sunflower oils as affected by composition of tocopherol isomers and linoleic acid content. *Food Chemistry*, 141 (3), 2373–2378. doi:10.1016/j.foodchem.2013.05.061
12. In: Talbot, G. (2015). *Specialty Oils and Fats in Food and Nutrition*. Elsevier, 384. doi:10.1016/c2014-0-01770-4
13. Awatif, I. I., Shaker, M. A. (2014). Quality Characteristics of High-Oleic Sunflower Oil Extracted from Some Hybrids Cultivated under Egyptian Conditions. *Helia*, 37 (60), 113–126. doi:10.1515/helia-2014-0010
14. Ghazani, S. M., Marangoni, A. G. (2016). Healthy Fats and Oils. *Encyclopedia of Food Grains*. Elsevier, 257–267. doi:10.1016/b978-0-12-394437-5.00100-5

15. Oke, E. K., Idowu, M. A., Sobukola, O. P., Adeyeye, S. A. O., Akinsola, A. O. (2017). Frying of Food: A Critical Review. *Journal of Culinary Science & Technology*, 1–21. doi:10.1080/15428052.2017.1333936
16. Hrynenko, O., Neklesa, O., Mironov, O. (2015). Udosoknennia tekhnolohii nachynok dla boroshnianykh kondystryktyvnykh kulinarnykh vyrobiv. *Prodovolcha industriia APK*, 1–2, 19–25.
17. Dichtyar, A. (2017). *Tekhnolohiia produktsii iz zavarnoho tista z vykorystanniam olii soniashnykovo vysokooleinovo typu*. Kharkiv: KhDUKhT, 23.

DOI: 10.15587/2312-8372.2017.112939

PROCESSING OF DAIRY RAW MATERIALS IN HEALTHY FOOD PRODUCTS

page 49–59

Chabanova Oksana, PhD, Associate Professor, Department of Technology of Milk, Fats and Perfumes and Cosmetic Products, Odessa National Academy of Food Technologies, Ukraine, e-mail: oksana_chabanova17@ukr.net, ORCID: <http://orcid.org/0000-0002-1455-2987>

Vikul Svitlana, PhD, Associate Professor, Department of Food Chemistry, Odessa National Academy of Food Technologies, Ukraine, e-mail: vizaj_vik@ukr.net, ORCID: <http://orcid.org/0000-0002-6753-5769>

Sharakhmatova Tetyana, PhD, Associate Professor, Department of Technology of Milk, Fats and Perfumes and Cosmetic Products, Odessa National Academy of Food Technologies, Ukraine, e-mail: sharahmatova@ukr.net, ORCID: <http://orcid.org/0000-0001-6080-6995>

Bondar Sergii, PhD, Associate Professor, Department of Ecology and Environmental Technologies, Odessa National Academy of Food Technologies, Ukraine, e-mail: sergej.nik.bondar@gmail.com, ORCID: <http://orcid.org/0000-0002-7908-2074>

Trubnikova Anastasiia, Postgraduate Student, Department of Technology of Milk, Fats and Perfumes and Cosmetic Products, Odessa National Academy of Food Technologies, Ukraine, e-mail: sc228004@ukr.net, ORCID: <http://orcid.org/0000-0001-6971-136X>

The object of research is whey-based beverages. The most problematic areas are the limited shelf life of beverages and the risk of product stratification during storage.

In the course of the study, whey pasteurization regimes are used: 84 ± 2 °C, waiting time 15–20 s, so the shelf life of beverages is limited, since sterilization of whey beverages is impossible due to loss of biologically active substances. To prevent delamination of the beverages during the storage of the formulation, pectin is added and an additional operation – homogenization is introduced.

Whey beverages with functional properties for individuals controlling body weight are obtained with improvement of organoleptic characteristics of the product. The resulting beverage is suitable, as a result of the introduction of plant components, to improve the metabolism in the body, block the synthesis of fat in adipose tissue, reduce the absorption of carbohydrates and fats in the digestive tract and remove excess fluid, accelerate the cleavage of fat molecules and transform fat into free energy. This is confirmed by the activation of pancreatic lipase. The activity of pancreatic lipase increases in 3.8...4.0 times in comparison with the control (whey).

Components of the whey, as the basis of beverages, have low energy value and high biological value. L-carnitine, α-lipoic acid,

stevia, gingerol and bromelain stimulate the breakdown of fats. Cinnamon increases metabolism in the body. This helps to accelerate the breakdown of fat.

To increase the nutritional value and biological activity to the beverages, the introduction of fruit and berry juices (lemon, cranberry, orange, pumpkin, yostaberry juice). Biologically active substances of juices show antisclerotic, antistress, tonic, immunostimulating, antioxidant effect. Antisclerotic action of juices is associated with the antioxidant properties of vitamins C, E, β-carotene. Juices reduce the oxidation degree of the most dangerous fraction of lipoproteins, thereby slowing the growth process of atherosclerotic plaques in the vessels. Antistress, tonic, immunostimulating and antioxidant effects of juices are due to the content of polysaccharides, sulfur-containing proteins, minerals, vitamins A, E, C, group B, bioflavonoids.

Whey beverages for people who control body weight are not toxic, their frequent consumption does not lead to addiction. Beverages do not contain substances prohibited by the Ministry of Health of Ukraine. Shelf life of beverages is 14 days. Beverages can be made on traditional equipment using traditional technology.

Keywords: cottage cheese whey, vegetable raw materials, recipes for new beverages, quality indicators, storage regimes.

References

1. Obesity and overweight. (2014). *Fact sheet of the World Health Organization*. Available at: <http://www.who.int/mediacentre/factsheets/fs311/en/>
2. Perederii, V. G., Tkach, S. M., Kutovoi, V. M., Rotter, M. N. (2013). *Izbytochnyi ves i ozhirenie. Posledstviia dla zdorov'ia i zhizni, sovremennoye rekomendatsii po dostizheniiu i podderzhaniu normal'noi massy tela*. Kyiv: Start-98, 240.
3. Rodionova, T. I., Tepaeva, A. I. (2012). Ozhirenje – global'naia problema sovremennoego obshchestva. *Fundamental'nye issledovaniia*, 12–1, 132–136.
4. Bessesen, D., Kushner, R. F. (2002). *Evaluation & Management of Obesity*. Hanley & Belfus, 190.
5. Minina, S. A., Kauhova, I. E. (2004). *Himiia i tehnologija fitopreparatov*. GEOTAR-MED, 560.
6. In: Pokrovskii, A. A., Samsonov, M. A. (1981). *Spravochnik po dietologii*. Moscow: Meditsina, 611.
7. Chabanova, O. B., Vikul, S. I., Bondar, S. M., Niedova, O. F. (2014). Obgruntuvannia retseptur diietychnykh napoiv na osnovi syrovatky. *Naukovi pratsi ONAKhT*, 44, 185–192.
8. Hramtsov, A. G., Brykalov, A. V., Pilipenko, N. Yu. (2012). Napitki iz syvorotki s rastitel'nymi komponentami. *Molochnaia promyslylenost*, 7, 64–66.
9. Hramtsov, A. G., Nesterenko, P. G. (2004). *Tehnologija produktov iz molochnoi syvorotki*. Moscow: DeLi print, 768.
10. Telezhenko, L. N., Mikhailova, E. A. (2015). Human diet enrichment with physiologically active ingredients due to the consumption of juices and beverages. *Journal of Food Science and Technology*, 9 (3), 9–13. doi:10.15673/2073-8684.3/2015.50267
11. Mogilnyi, M. P. (2007). *Pishchevye i biologicheski aktivnye veshchestva v pitaniu*. Moscow: DeLi print, 240.
12. Yasmin, A., Butt, M. S., Yasin, M., Qaisrani, T. B. (2014). Compositional analysis of developed whey based fructooligosaccharides supplemented low-calorie drink. *Journal of Food Science and Technology*, 52 (3), 1849–1856. doi:10.1007/s13197-014-1535-z
13. Amaral, G. V., Silva, E. K., Cavalcanti, R. N., Martins, C. P. C., Andrade, L. G. Z. S., Moraes, J. et al. (2018). Whey-grape juice drink processed by supercritical carbon dioxide technology: Physicochemical characteristics, bioactive compounds and volatile profile. *Food Chemistry*, 239, 697–703. doi:10.1016/j.foodchem.2017.07.003
14. Panghal, A., Kumar, V., Dhull, S., Gat, Y., Chhikara, N. (2017). Utilization of Dairy Industry Waste-Whey in Formulation of Papaya RTS Beverage. *Current Research in Nutrition and Food Science Journal*, 5 (2), 168–174. doi:10.12944/crnfsj.5.2.14

15. Chavan, R. S., Shraddha, R. C., Kumar, A., Nalawade, T. (2015). Whey Based Beverage: Its Functionality, Formulations, Health Benefits and Applications. *Journal of Food Processing & Technology*, 6 (10), 495. doi:10.4172/2157-7110.1000495
16. Gajbhare, S. N., Pawar, V. N., Sawate, A. R. (2015). Utilization of Encapsulated Lycopene for the Preparation of Tomato Whey Beverage as Health Drink. *The Indian Journal of Nutrition and Dietetics*, 52 (1), 70–79.
17. Dias, M. de L. L. A., Salgado, S. M., Guerra, N. B., Livera, A. V. S., Andrade, S. A. C., Ximenes, G. N. da C. (2013). Phisicochemical, sensory, and microbiological evaluation and development of symbiotic fermented drink. *Food Science and Technology (Campinas)*, 33 (4), 805–811. doi:10.1590/s0101-206120130004000030
18. Pandiyar, C., Villi, R. A., Chandrasekaran, V. (2011). Development of Mango Flavoured Sweetened Whey Drink. *Journal of Indian Veterinary Association Kerala (JIVA)*, 9 (3), 35–37.
19. Pareek, N., Gupta, A., Sengar, R. (2014). Preparation of healthy fruit based carbonated whey beverages using whey and orange juice. *Asian Journal of Dairying & Foods Research*, 33 (1), 5–8. doi:10.5958/j.0976-0563.33.1.002
20. Jain, S. (2013). Development of Low Cost Nutritional Beverage from Whey. *IOSR Journal Of Environmental Science, Toxicology And Food Technology*, 5 (1), 73–88. doi:10.9790/2402-0517388
21. Tkachenko, N., Nekrasov, P., Vikul, S., Honcharuk, Y. (2017). Modelling formulae of strawberry whey drinks of prophylactic application. *Journal of Food Science and Technology*, 11 (1), 1–9. doi:10.15673/fst.v11i1.303
22. Brykalov, A. V., Pilipenko, N. Yu. (2014). Razrabotka tehnologii napitkov na osnove molochnoi syvorotki, obogashchennyh fitokomponentami. *KubGAU*, 98, 1–12.
23. Cherevach, E. I., Tenkovskaia, L. A. (2015). Razrabotka tehnologii funktsional'nyh napitkov na molochnoi syvorotke s rastitel'nymi ekstraktami. *Food Processing: Techniques & Technology*, 39 (4), 99–105.
24. Inihov, G. S., Brio, N. P. (1971). *Metody analiza moloka i molochnyh produktov*. Moscow: Pishchevaia promyshlennost, 424.
25. Marh, A. T., Zykina, T. F., Golubev, V. N. (1989). *Tehnicheskii kontrol' konservnogo proizvodstva*. Moscow: Agropromzdat, 304.
26. Honskyi, Ya. I. (2001). *Biolohichna khimiia: laboratornyi praktikum*. Ternopil: Ukrmedknyha, 288.
27. Lekarstvennoe rastitel'noe syr'e. Opredelenie antimikrobnoi aktivnosti antibiotikov metodom diffuzii v agar. (1989). *Gosudarstvennaia farmakopeia SSSR: Vol. 2. Obshchie metody analiza. Ed. 11*. Moscow: Meditsina, 210–225.
28. Khomych, H. P., Vikul, S. I., Kapreliants, L. V., Osypova, L. A., Lozovska, T. S.; assignee: Odessa National Academy of Food Technologies. (12.01.2015). Sposib vyznachennia biolohichnoi aktyvnosti obiektiv pryrodnoho pokhodzhennia. *Patent UA 107506 S2 MPK G01N 33/00 (2015.01)*. Appl. No. a201302626. Filed 04.03.2013. Bull. No. 1. Available at: <http://uapatents.com/7-107506-sposib-vyznachennya-biologichno-aktivnosti-obehktiv-prirodnogo-pokhodzhennya.html>