

THE INFLUENCE OF INHOMOGENETIES ON THE CANTILEVER BEAM STIFFNESS (p. 4-7)

Alexander Shamrovsky, Dmytro Kolesnyk, Olena Mikhailutsa

It is proposed in the paper to conduct a computational experiment on the determination of the influence of inhomogeneities on the cantilever beam stiffness using a discrete model of the continuous medium. This approach allows to consider the materials with arbitrary discrete inhomogeneity. Inhomogeneities are represented by various variants of the composition of two materials with different elastic modulus and Poisson's ratios. The study of the influence of these inhomogeneities is supposed to be conducted by studying the geometrically nonlinear deformation of the cantilever beam, subjected to the uniformly distributed load. Calculation of the discrete model is made by the method of successive displacements. Based on the obtained calculation results, it is proposed to construct the diagrams of the dependence of dimensionless movement of the end of the cantilever beam along the axes of abscissas and ordinates on the dimensionless load for different schemes of composition of two materials. The obtained dependences allow to draw conclusions on the changes of the stiffness characteristics of the beam depending on the scheme of materials composition. The obtained results completely correspond to the expected results, allowing to draw conclusions on the direct influence on the stiffness of the cantilever beam by the inclusion of material with much higher stiffness than the main. Herewith, the form of the composition of two materials also greatly affects the stiffness of the console as a whole.

Keywords: cantilever beam, inhomogeneities, large displacement, stiffness, discrete model, lattice model

References

- Chawla, K. K. (2012). *Composite Materials: Science and Engineering* (3rd ed.). Springer.
- Vasiliev, V. V., Morozov, E. (2013). *Advanced mechanics of composite materials and structural elements* (3rd ed.). Elsevier.
- Carlsson, L. A., Kardomateas, G. A. (2011). *Structural and failure mechanics of sandwich composites*. Springer.
- Bolotin, V. V., Novichkov, J. N. (1980). *Mechanics of sandwich structures*. Moscow: Mashinostroyeniye.
- Bilgili, E., Bernstein, B., Arastoopour, H. (2002). Influence of material non homogeneity on the shearing response of a neo hookean slab. *Rubber chemistry and technology*, 75, 2, 347-363.
- Paulino, G. H., Jeong-Ho Kim (2002). Isoparametric graded finite elements for nonhomogeneous isotropic and orthotropic materials. *Journal of Applied Mechanics*, 69, 4, 502-514. doi: 10.1115/1.1467094.
- Bayar, S., Delale, F. (2012). General plane elasticity solution for non-homogeneous materials. *Meccanica*, 47, 7, 1737-1759. doi: 10.1007/s11012-012-9551-4.
- Kosinskiy, V. V. (2011). Polucheniye kompozitsionnykh materii alov s napered zadannymi svoystvami sposobom gidrostaticheskoy propitki s nagrevom. *Novi materiali i tekhnologii v metalurgii ta mashinobuduvanni*, 2, 86-93.
- Miyamoto, Y., Kaysser W. A., Rabin, B. H., Kawasaki, A., Ford, R. G. (1999). *Functionally Graded Materials: Design, Processing and Applications*. Materials Technology Series, Vol. 5.
- Chawla, N., Chawla, K. K. (2006). *Metal Matrix Composites*. Springer.
- Birman, V., Byrd, L. W. (2007). Modeling and Analysis of Functionally Graded Materials and Structures. *Applied Mechanics Reviews*, 60, 195-216. doi: 10.1115/1.2777164.
- Markworth, A. J., Ramesh, K. S., Parks, W. P. (1995). Review: Modeling Studies Applied to Functionally Graded Materials. *J. Mater. Sci.*, 30, 2183-2193.
- Dong, M., Schmauder, S. (1996). Modeling of metal matrix composites by a self-consistent embedded cell model. *Acta mater*, 44, 6, 2465-2478.
- Reuter, T., Dvorak, G. J., Tvergaard, V. (1997). Micromechanical Models for Graded Composite Materials. *J. Mech. Phys. Solids*, 45, 1281-1302.
- Cho, J. R., Ha, D. Y. (2001). Averaging and Finite Element Discretization Approaches in the Numerical Analysis of Functionally Graded Materials. *Mater. Sci. Eng., A.*, 302, 187-196.
- Siu, Y. K., Tan, S. T. (2002). Modeling the material grading and structures of heterogeneous objects for layered manufacturing. *Computer-Aided Design*, 34, 10, 705-716. doi:10.1016/S0010-4485(01)00200-7.
- Saraev, D., Schmauder, S. (2003). Finite element modelling of Al/SiCp metal matrix composites with particles aligned in stripes – a 2D-3D comparison. *International Journal of Plasticity*, 19, 733-747.
- Chakrabortya, A., Gopalakrishnana, S., Reddyb, J. N. (2003). A new beam finite element for the analysis of functionally graded materials. *International Journal of Mechanical Sciences*, 45, 3, 519-539.
- Zhong, Z., Yu, T. (2007). Analytical solution of a cantilever functionally graded beam. *Composites Science and Technology*, 67, 3-4, 481-488.
- Shamrovsky, A., Lymarenko, Yu., Kolesnyk, D., Minyajlo, T., Krivulyak, V. (2011). Discrete models for a plane static elasticity problems. *Eastern-European Journal of enterprise technologies*, 51, 3/7, 11-18.
- Shamrovsky, A., Kolesnyk, D. (2012). Geometric nonlinearity consideration in the continuous medium discrete model. *Methods of solving applied problems in solid mechanics*, 13, 420-427.
- Volmir, A. S. (1956). *Flexible plates and shells*. Moscow: Gosudarstvennoye izdatel'stvo tekhniko-teoreticheskoy literatury.
- Timoshenko, S. P., Voinovskiy-Krieger, S. (1966). *Plates and Shells* (2nd ed.). Moscow: Nauka.
- Shamrovsky, A., Lymarenko, Yu., Kolesnyk, D. (2009). Rozrakhunok sterzhnevyykh konstruksiy metodom poslidovnykh peremishchen iz urakhuvannyam heometrychnoi neliniy nosti. *New materials and technologies in metallurgy and mechanical engineering*, 1, 78-85.

ASSESSMENT OF THE MARGIN OF SAFETY OF MACHINE PARTS SUBJECT TO ASYMMETRIC LOADING (p. 8-12)

Aleksandr Zheldubovskii, Anatolii Pogrebniak, Mikhail Regulskii, Alexandr Serditov, Yuriy Kliuchnikov, Pavel Kondrashev

Creation of engineering structures is closely related to the need of improving the methods for strength calculation. This task is especially relevant with regard to the parts subject to cyclic loadings, causing premature failure as a result of the development of the metal fatigue process. In this regard, it is important to develop the research aimed at finding adequate model approximations that describe the interrelation of durability of a construction material with the range of loading conditions and the number of structural features of parts made of it.

The method of calculating the safety margin of parts of engineering structures subject to the combined effects of static and cyclic loadings is considered in this paper. The focus is on assessing the maximum limit stresses characteristic of the asymmetric loading of structural materials, taking into account the stress concentration as one of the main factors inherent in real structural elements. The proposed approach provides more correct calculation of the margin of safety in the implementation of design works.

Thus, the research results given in this paper are of both scientific and practical interest. The authors proposed a method for assessing the margin of safety of constructional materials subject to asymmetric cyclic loading, based on the previously developed models of the limit state based on the use of power transcendental functions.

Keywords: margin of safety, static and cyclic loadings, maximum stresses, asymmetric loading.

References

- Afanasyev N.N. (1953). *Statistical theory of the fatigue strength of metals*. Kiev, Izd-vo AN USSR, 128.

2. Veibull V. (1964). Fatigue testing and analysis of results. Per. s angl., pod red., S. V. Serensena, M., Engineering, 276.
3. Gaf G. (1935). Metal fatigue. Per. s angl., pod red., N.A. Shaposhnikova, M., L., Home Edition literature on Steel, 304.
4. Davidenkov N. N. (1981). Dynamic strength and brittleness of metals. Izbr., trudy, Kiev, Nauk. dumka, (1), 704.
5. Ivanova V. S. (1963). Fatigue fracture of metals. M., Metallurgizdat, 258.
6. Forrest P. (1968). Metal fatigue. Per. s angl., pod red., S. V. Serensena, M., Engineering, 352.
7. Khevud R. B. (1969). Designing for fatigue. Per. s angl., pod red., ch.-kor. AN USSR I.F. Obratsova, M., Engineering, 504.
8. Soderberg C. R. (1930). Factor of safety and working stresses. Trans. ASME., (30), 13-28.
9. Serensen S. V. (1943). Determination of the safety margin when calculating machine parts. Bulletin of engineering, (6), 6-14.
10. Golub V. P. (1994). High-temperature fracture of materials under cyclic loading. Kiev, Nauk. dumka, 228.
11. Golub V. P. (2004). The method of calculating the fatigue strength of metallic and composite materials in the asymmetric multicyclic loading. Applied mechanics, (11), 106-116.
12. Golub V.P. (2006). Fatigue strength of metallic and composite materials in the asymmetric stress-strain. Applied mechanics, (1), 48-58.
13. Kuzmenko V.A. (1981). Influence of loading frequency, temperature and cycle asymmetry on endurance of heat-resistant steels 1X2M и X18H9. Problems of Strength, (2), 30-36.
14. Tsymbalistyi Ya.I. (1977). The study inelasticity and metal fatigue in asymmetric cycles of high tension and compression. Avtoref. dis. k-ta tekhn. nauk, 20.
15. Podzolov I.V. (1947). Calculation of allowable stresses for ferrous metals in mechanical engineering (actual margin of safety). Izd. 3-e, pererab. I dopoln., M, Oborongiz., 486.
16. Uzhik G.V. (1949). Strength steels under the simultaneous action of permanent and variable loads. Izv. AN USSR, OTN., (5), 657-665.

MICROSCOPIC DESTRUCTION OF A STRUCTURAL INHOMOGENEOUS BAR OF A FINITE LENGTH UNDER A LONGITUDINAL IMPACT (p. 13-16)

Rahim Guliyev, Alizade Seyfullayev, Afat Yuzbashiyeva

The majority of structures in modern technology, industry and production are subjected to the influence of loads. Nowadays, a wide use of polymers and composite materials requires the study of long preservation of hardness and a problem of destruction of the structures made of such materials and subjected to the influence of loads.

Using a characteristic method, the destruction of a structural inhomogeneous bar, which is subjected to an impact in its left end in the direction of its axis, was studied, and the dependences of the first and full moments of destruction after various mechanical characteristics were found by a numerical computation. Finding of an analytical solution, characterizing the study, is rather difficult and, therefore, the problem was solved approximately. The results show that the effect of proportions of mechanical characteristics of the bar parts on the destruction process is significant.

Keywords: polymer, longitudinal impact, nonlinear heredity, damage, healing of defects, durability

References

1. Suvorova, Yu. V., Osokin A. E. (1978). Spreading one-dimensional waves in the non-linear hereditary environment. Mechanics of polymers Volume number (3), 425-429.
2. Suvorova, Yu. V. (1977). Non-linear effects at the deformation of hereditary materials. Mechanics of polymers Volume number (6), 976-980.
3. Suvorova, Yu. V., Victorova, I. V., Mashinskaya G.P. (1980). Lasting firmness and destruction of organic plastics. Mechanics of composite materials Volume number (6), 1010-1011.
4. Rakhmatulin, Kh. A., Demyanov, Yu. A. (1966). Firmness at the short time intensive loadings. Moscow: p. 399.
5. Akundov, M. B., Sadykhov, F. M., Suvorova, Yu. V. (1994). Spreading of deformation waves and stresses in the piece- homogeneous

viscous elastic bar of a finite length with consideration of the material damaging. Transactions of Academy of Sciences of the Soviet Union. Mechanics of solids. Volume number (5), 113-120.

6. Brigadirov, G. B. (1981). Impact of the composite bar to a rigid barrier. Applied problems of firmness and plasticity. Collection of papers of Gorky University. Edition 19, 98-103.
7. Cravchook, A. S., Khokhlov, S. Ya. (1984). Investigation of the non-linear impact wave processes in the layer systems. Modern problems of Physics and applications, 52-59.
8. Suvorova, Yu. V., Victorova, I. V., Mashinskaya, G. P. (1979). Lasting destruction of non-elastic composites. Mechanics of composite materials Volume number (5), 794-798.
9. Akhundov, M. B., Guliyev, R. S. (1995). Non-linear dynamics of non-elastic destruction of damaging layer systems. Mechanics of composite materials Volume number (5), 640-645.
10. Akhundov, M. B., Guliyev, R. S., Sadykhov, F. M. (1996). Destruction of the non-linear hereditary elastic non-homogeneous bar of a finite length under the impact loading with the consideration of the processes of damaging and restoration of defects. Proceedings of the Institution for Mathematics and Mechanics at the Academy of Sciences of Azerbaijan Volume number (5), 108-115.
11. Akhundov, M. B. (1988). Deformation, scattering destruction and firmness criterion for a non-elastic composite. Transactions of Academy of Sciences of the Soviet Union Mechanics of solids. Volume number (2), 112-117.
12. Guliyev, R. S. (1995). Dynamic loading of the damaging non-homogeneous bar. Collection of papers of the First Republican conference on Mechanics and Mechanics. Baku. Part 1, 55-57.
13. Suvorova, Yu. V. (1979). On the strength criteria based on damage accumulation and its application to composites. Transactions of Academy of Sciences of the Soviet Union Mechanics of Solids Volume number (4), 107-111.
14. Courant, R., Isaacson, E., Rees, M. (1952). On the solution of non-linear hyperbolic differential equation by finite differences. Commun Pure Appl. Math., 243-254.

INVESTIGATION OF FREE OSCILLATIONS OF THE SPHERICAL SHELL CONTAINING A LIQUID BY THE INVERSE METHOD (p. 16-19)

Guldasta Mamedova, Mexseti Rustamova, Samir Aqasiev

The problems of free oscillations of shells, contacting with the continuous medium are considered in the known works of various authors. As a rule, the problems are reduced to the transcendental equations or the systems the solution of which by analytical methods is not possible. The results of the investigation are presented in the form of tables or graphs, obtained by numerical methods. The problem of axisymmetric free oscillations of elastic thin-walled spherical shell, containing a compressible liquid is considered in the paper. Herewith, the equations of motion are constructed in radial motions and with the use of special potential. The problem is reduced to the investigation of the homogeneous system of two equations with respect to the radial motion and the mentioned potential. The condition of non-triviality of the system solution leads to the transcendental equation. In the known works, the solution of the specified transcendental equations is found by numerical methods. The analytical solution, binding the frequency of the system shell - liquid with the frequency of the shell without the liquid is constructed by the inverse method. This solution allows to investigate the phenomenon of the analytical method and to build the frequency spectra.

The potential motion both of shell and liquid is considered. The equation of the shell motion in special potentials is used. The liquid motion equation is represented by the wave equation. The liquid motion is proposed as non-separable.

Keywords: oscillations, wave, frequency, density, shell, pressure, potential.

References

1. Chen, W. Q., Cai J. B., Ye G. R., Ding H. J. (2000). On eigen frequencies of an anisotropic sphere. Transactions of Azerbaijan National Academy of Sciences. Applied Mechanics, 2000.67, №2, pp. 422- 424.
2. Latifov F. S. (1999). Oscillations of shells with an elastic and liquid medium. Baku, Elm, 164.

3. Mamedova G. A. Seyfullayev A. I. & (2001). The influence of the medium density to the free oscillations of the cylinder containing a compressible liquid. *Mechanics: Engineering*. 2001. Volume 11, №1, 28-32.
4. Mikhasev G. I. (2009). Localized oscillations and waves in the thin-walled shells. Asymptotical methods. In the Mikhasev G.I. & Tovstik P.E. Moscow. Physical and Mathematical Literature. 292.
5. Smirnov V. N. (1974). The Course of Higher Mathematics. Volume 3, part 2. Moscow, Nauka, 672.
6. Balakirev G. (1967). To arrow symmetric oscillations shallow spherical shell with a liquid. *Journal of Engineering MTT*. - № 5. - S. 116123.
7. Eynatollah A. Taheri, Rustamova Mashati (2010) Investigation of Free Vibrations Of Spherical Inclusion Containing Elastically Suspended Mass Situated in Acoustic Medium by the Inverse Method. *International Journal of Nanosystems*, vol.3, p.23-25
8. Golovanov A.I. (1991). Investigation of free vibrations of the shells by finite element method. Investigations in the theory of plates and shells. MY. 23, Kazan, Kazan State University, p. 81-85.
9. Qribkov V.A. The main results of the study of dynamic characteristics of shells filled with fluid: analysis and fluid. *Proc. Scienc. of the symposium. Novosibirsk*, 1992. - p. 61 – 66
10. Huang H., Lu Y.P., Wang Y.F.F. (1974). Transient interaction of spherical acoustic waves a cylindrical elastic shell and it's internal multi-degree-of – freedom mechanical systems. *J. Acoust. Soc. America* vol 56, №1. p. 4-10.

MODELING AND PREDICTION OF MATERIAL WEAR BY UNFIXED ABRASIVE (p. 20-25)

Anatolii Kuzmenko, Ivan Bylokur, Oleg Vyshnevskiy

The generalized multifactor model of the interaction of friction surface with unfixed particles of abrasive, developed on the basis of similarity and dimension theory provides the determination of parameters of material wear. The use of the developed analytical dependences of determining the rate of linear wear of materials allowed significant reduction of the amount of basic experimental researches. The dimensionless multifactor criterion of similarity and the criterion equation allow estimating the influence of sliding distance, material hardness, sizes of particles of abrasive and abrasive pressure upon the sample on wear by unfixed abrasive. The correctness of the constructed model of abrasive wear in the unfixed abrasive was experimentally proved. The method of using the developed model for the prediction and evaluation of technical condition of operating supporting nodes of friction of cylindrical machine parts in the interesting point of time was justified.

Keywords: diagnostics, abrasive wear, test pattern, wear model, model parameters.

References

1. Kuz'menko, A. H. (2007). *Prikladnaia teoriia metodov ispytaniia na iznos. Khmel'nitskii: KhNU*, 579.
2. Pol'tser, H., Maissner, F. (1984). *Osnovy treniia i iznashivaniia*. M.: Mashinostroenie, 264.
3. Tenenbaum, M. M. (1976). *Soprotivlenie abrazivnomu iznashivaniiu*. M.: Mashinostroenie, 164.
4. Kostetskii, B. I. (1975). *Nadiozhnost' i dolhovechnost' mashin*. Kiev.: Tekhnika, 226.
5. Krahel'skii, I. V., Dobychin, M. N., Kombalov, V. S. (1977). *Osnovy raschiotov na treni i znos*. M.: Mashinostroenie, 526.
6. Malyshev, A. P. (1917). *Iznashivanie materialov ot treniia*. *Vestnik obshchestva sibirskikh inzhenerov*, T. 2, № 5-6.
7. Khrushchev, M. M., Babichev, M. A. (1970). *Abrazivnoe iznashivanie*. M: Nauka, 252.
8. Venikov, V. A. (1976). *Teoriia podobiia i modelirovaniia*. M.: Vyssh. Shk., 479.
9. Kuz'menko, A. H., Vishnevskii, O. A. (2011). *Teoreticheskie osnovy metoda ispytaniia na abrazivnyi iznos po skheme Malysheva – Vellinhera – Uettsa. Problemi tertia ta znoshuvannia: Naukovo-tekhnichnii zbirnik*, Vip. 55, 79-82
10. Kuz'menko, A. H., Vishnevskii, O. A. (2011). *Teoreticheskie osnovy i eksperimental'naia realizatsiia metoda ispytaniia na abrazivnyi znos s opredeleniem parametrov modelei iznashivaniia po skheme Malysheva – Vallinhera – Uettsa (MVU)*. *Visnik KhNU*, №3, 7-19

JUSTIFICATION OF PARAMETERS OF ELASTIC SYSTEM OF VIBROCONVEYOR MACHINE WITH COMBINED KINEMATIC VIBROEXCITATION (p. 25-30)

Igor Palamarchuk, Vladyslav Palamarchuk, Vadim Drachishin

Transport-technological machines due to combining several operations in one production cycle, providing treatment continuity and easy adherence to production lines are in wide demand in the fields of agro-industrial complex. The use of vibrating conveyor machines adds potential capabilities of technological action intensification to the noted features. Thus, the main problems remain, such as reduction of dynamic loads on supporting units and system balancing.

To solve such problems, the constructive and technological measures are substantiated in this research paper to reduce the dynamic loads on supporting units of the drive mechanism by defining the basic criteria of assessing the elastic system of technological machine and obtaining their analytical expressions, combining the elements of kinematic and force vibroexcitation. Calculation of the kinematic characteristics of mechanical vibroexciters of technological machines allows determining the main dependencies of parameters of transport-technological or conveyor vibrating systems, that is important in their design and construction of the elastic system of vibration equipment.

Based on the analysis of modern equipment of vibration technological and transport-technological machines, the classification of the main structural elements of their elastic system was developed. The effect of additional elastic component from the deformed transporting element in the design of vibroexciters was justified by the example of calculation of conveyor vibrating machine.

Keywords: vibroexciter, motion dynamics, kinematic drive, vibrating conveyor, elastic system.

References

1. Anan'ev, I. (1946). *Handbook for calculation of natural oscillations of elastic systems*. Moscow: Gostekhizdat, 223.
2. Bernik, P., Palamarchuk, I. (1996). *Conveyor Vibratory finishing machine - firming treatment*. Kyiv: High School, 237.
3. Bernik, P., Sereda, L., Palamarchuk, I. (1995). *Choosing a rational scheme of mechanical vibration exciter for the conveyor machines with flexible rail*. *Vibrations in engineering and technology*, 2, 15-20.
4. Del, G. (1978). *Technological mechanics*. Moscow: Mechanical Engineering, 174.
5. Palamarchuk, I., Misyura, T. (2007). *Justification of the main operating parameters of Mechanical Vibration machine with a flexible container for machining raw food*. *Proceedings of the National University of Food technology*, 1, 53-56.
6. Bachmann, D. (1940). *Locomotor system in vibration mills with dry grinding media filling bodies*. *Z.V.D.I-Beihert*, 2, 19-23.
7. Bachmann, D. (1942). *Development of vibration mills*. *The chemical technology*, 18, 11-16.
8. Josselin de Jong. (1959). *Static and Kinematics in the bailable zone of a granular material*. Delft.-Waltman.
9. Raasch, J. (1962). *The mechanics of the swing mills*. *Chemistry JNGR-tech*, 2.
10. Rose, H. (1962). *High Performance Mixer*. *Chemistry JNGR-tech*, 34.

SYSTEM OF VIBRO- AND SHOCK PROTECTION WITH DRY FRICTION (p. 31-33)

Yuri Kyrychuk

Despite the large number of discussions about the systems of shock- and vibroprotection, little attention has been paid to vibroprotection with dry friction. The single-axis system of vibro- and shock protection with dry friction, which at the given level limits the maximum acceleration of the isolated body at the single high-level shocks and at vibrations with the absent static zone of stagnation near the equilibrium, is first considered in the paper. The system is designed for providing the operational protection of the navigation device, installed on the aircraft, against shock overloads of large amplitude. The system design, principle of operation, the method for obtaining the mathematical model are given in the paper, components

of this model are shown. The obtained results prove the prospective of the new system of shock- and vibroprotection in use in navigation complexes of aircrafts, operating in extreme conditions.

Keywords: shock absorber, vibroprotection, vibration acceleration, damper, acceleration, mathematical model, shock protection, dry friction

References

1. Kolovskii, M.Z. (1976). Nonlinear theory of vibration isolation systems. - Moscow, USSR: "Science", 317.
2. Popov, E.P. (1986). Theory and Design of flexible elastic rods. - Moscow, USSR: "Science", 385.
3. Karpyshev, V. B. (1981). Vibrations and shocks in radio / Moscow, USSR: " Soviet radio", 344.
4. Klembezyk, Alan R. (2009). Introduction to Shock and Vibration Isolation and Damping Systems / IMAC-XXVII: Conference & Exposition on Structural Dynamics, 58 – 66.
5. Crocker, Malcolm J. (2007). Handbook of Noise and Vibration Control // John Wiley & Sons Inc., New York NY, 1569.
6. Yoon, S. W., Lee, S. W., Perkins, N. C., and Najafi, K. (2007). Vibration Sensitivity of MEMS Tuning Fork Gyroscopes. Proceeding of IEEE SENSORS 2007 Conference Atlanta, Georgia, USA, 115-119.
7. Balandin, Dimitry, V. Bolotnik, Nikolai N., Walter, Pilkey, D. (2001). Optimal Protection from Impact, Shock and Vibration // March 7, by CRC Press, 472.
8. Purtseov, S.V. (2003). Optimal protection of two-degree-of-freedom system from shock and vibration// PHYCON '03 Proceedings of the 2003 International Conference on Physics and Control - Volume 4, 1206 – 1208.
9. Vepruk, A.M. (2003). Vibration protection of critical components of electronic equipment in harsh environmental conditions, Journal of Sound and Vibration. 259 (1),161-175.
10. Bezveclina, Elena N., Kyrychuk, Yurii V. (2009). Systems of protection against vibration and shock / Monograph. - Zhytomyr, ZhSTU. 160.

RESEARCH OF THE PROCESS OF ELIMINATION OF LARGE NUTATION ANGLES BY PASSIVE AUTOBALANCERS (p. 34-38)

Gennadiy Filimonikhina, Vladimir Pirogov, Irina Filimonikhina

This paper studies the process of eliminating large nutation angles arising from inaccurate initial rotation or imbalance of the spin-stabilized spacecraft using passive auto-balancers (pendulum, ball and liquid). An analogy in the operation of various types of passive auto-balancers (nutation dampers) (pendulum, ball and liquid) during removal of large angles of nutation was established. For pendulum, ball and liquid auto-balancers approximate law of changing large nutation angles in the case of axisymmetric and non-axisymmetric lifting body was obtained. It was found that the rate of changing the nutation angle is significantly affected by the ratio between the axial moments of inertia of the lifting body and the coefficient of viscous drag forces. The empirical formula was proposed for estimating the residual nutation angle resulted from incorrect installation of passive auto-balancers (nutation dampers) on the spin-stabilized spacecraft, as well as an example of its application for a specific Brazilian satellite (SACI-2) was given. It is shown that improper installation of the auto-balancer (nutation damper) on the lifting body can cause residual nutation angle even in the case of "steady" lifting body. The results can be used in the design of passive auto-balancers (nutation dampers) (pendulum, ball and liquid) for spacecrafts or spin-stabilized artificial satellites of the Earth.

Keywords: passive auto-balancer, nutation angle, damper, spacecraft, lifting body.

References

1. Zinchenko, O. N. (2011). Small optical satellites DZZ. Retrieved from http://www.racurs.ru/www_download/articles/Micro_Satellites.pdf
2. Ovchinnikov, M. Y. (2007). Small this world. Kompyuterra, 15, 37-43.
3. Garbuk, S. V., Gershenzon, V. E. (1997). Space remote sensing system planet Earth. Moscow, Publishing house A and B, 296.
4. Gritsenko, A. A. (2001). Using stabilized rotation of small satellites in the satellite communication systems for GEO and HEO

orbits. Retrieved from <http://www.spacecenter.ru/Resurses/IEEE-2001-2.doc>

5. Efremov, G. A., Viter, V. V., Lipatov, A. A. et al. (2000). Small satellites in communication networks and broadcasting. Retrieved from <http://www.spacecenter.ru/Resurses/PGEO.pdf>
6. Carrió, L. (2005). Spin Stabilization and Release Mechanism. Retrieved from http://www.dartmouth.edu/~aiaa/public_html/Dartsat20AIAA20Presentation 202005.ppt
7. Fonseca, I. M., Santos, M. C. (2002). SACI-2 Attitude Control Subsystem. INPE, 3, 197–209. Retrieved from <http://www2.dem.inpe.br/ijar/CBDO2000FullPape SACI2ACS.pdf>
8. Gidlund, S. (2005). Design Study for a Formation-Flying Nano-satellite Cluster. Retrieved from <http://epubl.luth.se/1402-1617/2005/147/index.html>
9. Hambly, R. M. (2004). AMSAT OSCAR-51 (AO-51) and the New Eagle Satellite. Retrieved from <http://www.columbiaara.org/AMSAT-CARA-04-11.ppt>
10. Janssens, F. L., Van der Ha, J. C. (2011). On the stability of spinning satellites. Acta Astronautica. Vol. 68, Issues 7–8. 778-789.
11. Biggs, J. D., Nadjim, H. (2012). Optimal geometric motion planning for a spin-stabilized spacecraft. Systems & Control Letters. Vol. 61, Issue 4. 609-616.
12. Likins, P. W. (1966). Effects of energy dissipation on the free body motions of spacecraft. Retrieved from <http://www.aoe.vt.edu/~cdhall/courses/aoe4065/NASA DesignSPs/sp8016.pdf>
13. Reuter, G. S., Thomson, W. T. (1966). Rotational movement of passive spacecraft. Problems of the orientation of satellites, Moscow, Nauka, 336-350.
14. Filimonikhina, I. I., Filimonikhin, G. B. (2007). Conditions for balancing a rotating body in an isolated system with automatic balancers. International Applied Mechanics, vol. 43, no. 11, 1276-1282.
15. Filimonikhin, G. B. (2004). Balancing and vibration protection rotors avtobalancers with solid corrective weights. Kirovograd, KNTU, 352.
16. Pirogov, V. V. (2008). Stability of the main motion of the statically unstable spin body with two pendulums (balls). Bulletin of University of Kyiv, no. 3, 89-94.
17. Filimonikhin, G. B., Filimonikhina, I. I., Pirogov, V. V. (2012). The stability of steady motions of a satellite, spin-stabilized, with a passive autobalancer-damper nutation angle. MCS-2012, 151-153.

REDUCTION OF ACOUSTIC ERROR OF THE FLOAT DIFFERENTIATING GYRO BY PASSIVE METHODS (p. 39-41)

Viktorij Mel'nick, Volodimir Karachun

The subject of the research is one of simply implemented methods of passive acoustic isolation of two-stage float gyro from effects of penetrating high level acoustic radiation by giving a catenoidal shape to the moving part of suspension.

The research is based on solving the problem of optimizing the meridian line of the shell of suspension, which allows to minimize elastic displacements of the float suspension surface in acoustic fields and, thus reduce the value of acoustic errors of differentiating gyro to the level of sensitivity threshold.

Numerical analysis of the influence of δ deflection of the shell of float suspension in the midship frame proves the effectiveness of passive methods for correcting the value of acoustic error during flight operations.

The results can be used in industry to create inertial means of flight-navigation equipment of aircrafts. They can also find application in the bench certification of board equipment for functional capacity in the operational mode.

Giving the catenoidal shape to the moving part of float suspension of gyro is supported by simplicity of technical realization, effect of reducing the errors of device in acoustic fields of flight operations and prospect of further improvement on the basis of resonance phenomena.

Keywords: bias, two-stage gyro, catenoid, acoustic radiation, sensitivity threshold

References

1. Wrigley, W., Hollister, W., Denhardt, W. (1972). The theory, design and testing of gyroscopes. Moscow, USSR: Mir.
2. Crandall, S. (1967). Random fluctuations. Moscow, USSR: Mir.

- Mel'nick, V. N., Karachun, V. V. (2004). Determining Gyroscopic Integrator Errors to Diffraction of Sound Waves. *International Applied Mechanics*, 40 (3), 328-336.
- Karachun, V. V., Mel'nick, V. N. (2012). Influence of Diffraction Effects on the Inertial Sensors of a Gyroscopically Stabilized Platform: Three -Dimensional Problem. *International Applied Mechanics*, 48 (4), 458-464.
- Shybet'skii, V. Y. (2012). Ways to reduce navigational errors in difficult operating conditions on hypersonic aircraft. Kiev: «Actual problems of aircrafts», 120.
- Smith, P. W. (1962). Response and radiation of structural modes excited by sound. *Journal Acoustic Soc. Am.*, 34 (5), 640-647.
- Lyon, R. H. (1965). Vibration energy transmission in a three element structure. *Journal Acoustic Soc. Am.* 38 (2), 1344-1354.
- Maidanik, Ct. (1962). Response of ribbed panels to reverberant acoustic fields. *Journal Acoustic Soc. Am.* 34 (6), 809-826.
- Heckl, M. A. (1962). Vibrations of point-driven cylindrical shells. *Journal Acoustic Soc. Am.* 34 (10), 1553-1557.
- Dyer, I. (1960). Noise environments of flight vehicles. *NOISE Control.* 6 (1), 31-40.
- Johnson, K. (1989) *Mechanics of contact interaction.* Moscow. Mir. 510 p.
- Popat, P. B., Ghosh, A., Kishore, N. N. (1989) Finite -element analysis of the blanking process. *Journal of Mechanical Working Technology.* Amsterdam, 18, № 3, P. 269-282.
- Ghosh, A., Raqhu Ram, V., Popat, P.B. (1985) A new approach to the mechanics of the blanking operation: theoretical model and experimental verification. *Journal of Mechanical Working Technology.* № 2, P. 215-228.
- Kuich G. (1986) Applications of the Boundary Elements Method to Contact Problem. *Proc. BETEC 86. Computational Mechanics Publications,* P. 488-519.
- Cescotto, S., Zhu, Y.Y. (1994) Large Strain Dynamic Analysis Using Solid and Contact Finite Elements Based on a Mixed Formulation - Application to Metalforming. *Journal of Metals Processing Technology.* Vol. 45, P. 657-663.
- Wriggers, H., Van Vu, Stein, J. (1990) Finite Element Formulation of Large Deformation Impact-Contact Problems with Friction. *Computers and Structures.* Vol. 37, P. 319-331.

CALCULATION OF STRESS-STRAIN STATE OF STAMP RIGGING ELEMENTS (p. 41-44)

Natalia Dyomina

The approach to the study of the stress-strained state of stamp rigging elements, taking into account the contact interaction is proposed in the paper. For this purpose, the integrated mathematical model was proposed, differing by the new approach: to determine the stress-strain state, instead of the traditional single-level mathematical model, the integrated multi-level mathematical model is used, taking into account the contact interaction of punches, matrixes and punch-matrixes, blanks and base plates of stamps.

The first-level model is the most effective in terms of assessment of SSS (stress-strain state) of cutting elements of SD (shearing die). Each element of the technological system in it is considered separately from the others, and the interaction forces are known from previous experimental, analytical and numerical studies.

The second-level model considers the contact interaction of elements of stamps with the blank, but only up to the stage of plastic deformation of the stamped material.

The entire interaction process up to the modeling of the division of stamped material is investigated using the third-level mathematical model.

Undoubted advantage of the models of the second and third levels is the ability to determine the contact zones and contact forces, arising between the elements of stamps and blank.

The developed integrated mathematical model is realized in the form of the set of models using the method of finite elements, which allow to conduct a great number of multivariate studies of the stress-strained state of the shearing dies in the automated mode. This makes them valuable for carrying out scientific researches and practical calculations.

Keywords: stress-strain state, stamp, contact interaction, stamp rigging element, technological system

References

- Zayarnenko, E. I. (1992). Development of mathematical models and strength calculations of dividing re-adjusting stamps: diss... doctor of techn. sciences: spec. 01.02.06 and 05.03.05 / Zayarnenko Eugeniy Ivanovich. Kharkov, 280.
- Dyomina, N. A. (2011). Perfection of calculation methods for stamp rigging elements on the basis of analysis of their stress-strain state: diss candidate of techn. sciences: spec. 05.03.05/ Dyomina Natalya Anatolievna. Kharkov, 187.
- Tkachuk, N. A., Dyomina, N. A., Serdyuk, Y. D. [and oth.] (2010) Modeling of contact interaction of stamp rigging elements. Processing of materials by pressure: collection of scientific works. Kramatorsk: DSMA, № 2 (23), P. 240-248.
- Jiang, Pledgers O. (1988) Combined Lagrangian Multiplier and Penalty Function Finite Element Technique for Elastic Impact Analysis. *Computers and Structures*, Vol. 30, P. 1219-1229.
- Koltunov, M. A., Kravchuk, M.A., Mayboroda, V.P. (1983) Applied mechanics of deformed solid bodies. Moscow: Vys. shkola. 349 p.

SINGLE THEORY OF MOVERS ON THE CONTINUOUS FLOWS. SHORT THEORY OF CONCURRENT-ROTATING PROPELLERS (p. 45-52)

Borys Mamedov

In the concurrent-rotating propellers, the second rotor wheel has higher performance than the first one, so the gas flow is injected (absorbed) through the channels between the blades of the first rotor wheel, which in this mode does not compress the gas flow, and functions as rotating guiding device, which allows to obtain the sinusoidal characteristics of the axial velocity change with ensuring zero acceleration of the gas flow at the input edges of the second rotor wheel blades, which compresses the flow and produces thrust. Injection (absorption) of the gas flow through the channels between the blades of the first rotor wheel also promotes the swirling of the gas flow in the area H-B₁ and the emergence of additional gradient of static pressures, grad Pd, which pulls the flow into the bundle before and after the section B1-B1, while before the section B₁-B₁ this additional gradient of static pressure facilitates further acceleration, and in the B1-B₂ section slows down the gas flow, providing its sinusoidal characteristics in the H-B₂ section. Thus, the sinusoidal characteristics of the change of the axial velocity of the gas flow in the H-B₂ section allows to eliminate the kinematic zone of rigid (elastic) impact in the section B₂-B₂ that allows to increase the turnover, and, therefore, the thrust of the second rotor wheel of the concurrent-rotating propellers by 200-300 % as compared to the turnover and thrust of the one-row propellers.

Keywords: kinematic analysis, concurrent-rotating propellers, blown profile thrust and lifting capacity.

References

- Patent 26883, Ukraine, MIIK (2006) B64C 11/00, B64C 27/00, B64D 35/00, F02K 3/00. Turboprop engine. № U200705886, decl. 29.05.2007, publ. 10.10.2007, internet.
- Yourev, B.N. (1961). Selected works. Volum 1. Air propellers, helicopters. Printed by Academy of science of USSR, Moscow, 531.
- Mamedov, B. S. (2011). Chapter 2. Foundations of single theory of movers on the continuous flows. Blowing profile as a mover, formulas of thrust, flying (thrust) efficiency, theorem of raising force calculation. *National Technical University News, «KhPI»*. Scientific works collection. Topical issue: New solution in modern technologism, № 33, 146–153.
- Mamedov, B. S. (2012). Chapter 9. Single theory of movers on the continuous flows foundations. Calculation the formulas of thrust, flying (thrust) efficiency, theorem of raising force of blowing profile of aircraft wing as mover on the continuous flows (Shot theory of aircraft wing). *National Technical University News, «KhPI»*. Scientific works collection. Topical issue: New solution in modern technologies, NTU «KhPI», № 35 (950), 3–17.
- Kazandgan, P. K. (1983). Aviation engines theory. *Machinebuilding*, 233p.
- Mamedov, B. S. (2011). Chapter 1. Single theory of movers on the continuous flows foundations. Turbo-jet engines formulas of thrust, flying (thrust) efficiency calculation. *Eastern-European journal of Enterprise Technologies*, №4/7(52), 15–20.

7. Mamedov, B. S. (2012). Chapter 7. Single theory of movers on the continuous flows foundations. Blowing bird wing profile as a mover, formulas of thrust, flying (thrust) efficiency, theorem of raising force calculation. National Technical University News, «KhPI». Scientific works collection. Topical issue: New solution in modern technologies, NTU «KhPI», № 44, 11–20.
8. Mamedov, B. S. (2012). Single theory of movers on the continuous flows foundations. Sail formula of thrust calculation. Eastern-European journal of Enterprise Technologies, №5/7 (59), 11–17.
9. Mamedov, B. S. (2013). The use of Ayley's equation for calculation the formula of thrust and flying (thrust) efficiency on external parameters of gas flow for air-jet engines when $V_n \geq 0$. National Technical University News, «KhPI». Scientific works collection. Topical issue: New solution in modern technologies, № 4 (978), 3–15.
10. Mamedov, B. S. (2012). Single theory of movers. Rocket engine formula of thrust, flying (thrust) efficiency calculation. Eastern-European journal of Enterprise Technologies, №1/7 (61), 61–67.

ELASTIC DEFORMATION OF THE BEARING SURFACE OF A PLAIN JOURNAL BEARING OF TURBOCHARGER (p. 53-58)

Viktor Kravtsov, Miroslav Kindratshuk, Alexandr Didenko, Mehrdad Sadeghijalal

The methodology of studying the elastic deformation of the bearing surface at the simultaneous action of forces, gradually arising from start to stop, is proposed on the example of the operation of the journal thrust bearing of turbocharger of the gas compressor unit turbine. For that, the mathematical model was used, which describes the balance and deformation of spatially curved element, its external and internal geometry. The methodology of numerical solution of the problem is based on the combined application of the continuation method and Newton-Kantorovich method.

The problems, which arise in the operation of plain thrust bearings of the compressors of turbo generators are described in the paper, the analysis of the literature on this subject is given. It is shown that, as a rule, local problems, describing any separate process, are still considered in the problems of friction. In this respect, it was pointed out that the process of friction is inseparably linked with the large number of load factors, which have not yet been considered simultaneously. During the description of the methodology, its sense

was outlined, the ways of setting the possible loads, which can be applied or taken away during the bearing operation were shown. The possibility of investigating the bearing surface with a non-circular (oval) geometry of the axial line was shown on the example of the plain thrust bearing of the turbocharger. The research results are presented in the form of diagrams, which show the values of some characteristics of the stress-strain state of the bearing surface of the plain journal bearing of the turbocharger with specific physical and geometrical characteristics in dimensionless quantities.

Keywords: friction, bearing surface, elasticity, loads, mathematical model, numerical methods

References

1. Goryacheva, I. G., Checkina O. G. (1999) Wear of surfaces: from modelling of micro-destruction to the analysis of forming Goryacheva. Izvestiya RAS. MTT, No. 5. P. 131-147.
2. Kyndrachuk, M. V., Labunets, V. F., Pashechko, M. I., Korbut E. V. (2009) Tribology. Kiev. NAU-druk. - 392.
3. Chichinadze, A. V., Braun E. D., Ginsburg A. G. et al (1979). Calculation, matching and testing of frictional pairs. Moscow, USSR: Nauka, - 268.
4. Dmitriev, A. I., Smolin A. Yu, Popov V. L., Psahye S. G. (2008). Multilevel modelling of friction and wear processes on the basis of numerical methods of discrete mechanics and phenomenological theory. Physical mesomechanics. - P. 15-24.
5. Smolin, A. Yu., Konovalenko I. S. (2006). On generation and transmission of elastic waves by friction. Computer modelling. Physical mesomechanics. Vol. 9. - P. 45-48.
6. Psahye, S. G., Smolin A. Yu., Stefanov P. V. et al. (2003). Simulation of the complex media behavior based on the combined discrete-continuum approach. Physical mesomechanics. - Vol. 6, No. 6. P. 11-241.
7. Kravtsov, V. I. (1999) Mechanics of flexible sea constructions. Kiev. Naukova dumka. - 131.
8. Drokonov, A. M., Osipov A. M., Biryukov A. V. (2009). Bearings of turbine plants. Bryansk : BSTU, - 103.
9. Revzin, B. S., Larionov B. S. (1991) Gas turbine plants with superchargers for gas transportation. Moscow, Nedra. - 303.
10. Chernavskiy, S. A. (1963). Sliding bearings. Moscow, USSR: Mashghiz, - 245.
11. Sedykh, Z. S. (1990). Operation of gascompressor units with gas-turbine drive. Moscow, Nedra. - 203 p.
12. Vogelpohl, G. (1962). Geringste zulässige Schmierschichtdicke und Übenpangsdrehzahl. Konstruktion. № 12. - P. 461. – 468.