

THE DEVELOPMENT OF MODERN BIOECENOTIC CONTROL METHODS FOR THE ECOLOGICAL STATE OF AQUATIC ECOSYSTEMS OF RIVERS (p. 4-10)

Vera Udod, Igor Vildman, Elena Zhukova

Existing ecological-hygiene control methods for the AE state under the action of anthropogenic factors do not fully characterize the structural-functional changes in water bodies, and therefore do not characterize the degree of their transformation. Sanitary-hygienic standards (TLV, MPD) allow to determine the class of water pollution and changes in chemical composition. At the same time, in the process of self-purification of the water body, there is destruction of pollutants, which leads to the formation of new chemical compounds, which are not considered by the applied control methods. Therefore, for the characterization of biological regulation of aquatic ecosystems, it is advisable to use integrated environmental approaches, including the existing sanitary-hygienic standards and biocenotic methods were proposed. Biocenotic methods allow to determine ecotoxicokinetic processes in bio- and aquatic ecosystems and based on the analysis of the data obtained find out the cause-effect relations of AE, which lead to the transformation of AE.

Keywords: aquatic ecosystem, structure, properties, functions, interrelations, transformation, hydrochemistry, hydroecology, monitoring, development.

References

- Molchanov, Y. P., Zayka, E. A., Babkina, E. Y. (2007). Hydrohy-myeshkye Performance Status okruzhayushey environment, 192.
- Udod, V. M. (2009). The transformation of the components of the biosphere in the process of nature. Environmental security and environmental management, 3, 109–114.
- Falkenmark, M., Tropp, H. (2005). Ecosystem Approach and Governance Contrasting Interpretations. Stockholm Water Front, 2, 4–5.
- Tropp, H. (2005). Developing Governance Capacities. Stockholm Water Front, 2, 10–11.
- Pylylyuk, V. (2010). Dynamics of water chemistry in length p. Psyl and evaluation of its quality. Hydrology, hydrochemistry and hydroecology, 4 (21), 125–133.
- Yatsyk, A. (2011). Integrated ecological assessment of surface water (for example, rivers, Poltava region). Aquaculture Ukraine, 6, 13–18.
- Udod, V., Zhukova, O. (2014). Ecological characteristics of natural - anthropogenic hidroekosystem water basin. Kalmius. Environmental Security and Sustainable Natural Resources, 15, 145–151.
- Gonchar, O. (2007). Hydrochemical regime and assessment of water quality of the river Dniester (Podolsky part). Hydrology, hydrochemistry, hydro Ecology, 13, 152–158.
- Chunarov, A. (2007). Environmental assessment of the quality of river water basin of the Southern Bug at the appropriate categories, 13, 158–165.
- Alimov, A. (2010). Biological diversity and community structure of organisms. Biology of Inland Waters, 3, 3–10.
- Reshetnjak, O. S., Nikanorov, A. M., Kostenko, L. S. (2013). Antropogennaja transformacija vodnoj jekosistemy nizhnej Volgi. Vodnye resursy, 6, 623–632.
- Udod, V. M., Yatsiv, M. Y. (2013). Comprehensive criteria environmental assessment of the effectiveness modern processes (for example, basin river Prut). Water Chem. and Technol, 6, 287–294.
- Udod, V., Vildman, I. (2014). Heavy metals as contaminants, the water system. Inhulets. The problems of water supply, drainage and hydraulics, 23, 22–26.
- Udod, V., Vildman, I., Zhukov, O. (2014). The ecological approach to assessing the effectiveness vnurishnovodoyimnyh process water systems and rivers Kalmius Inhulets. Journal of National University of Kremenchug M. Ostrogradskiy, 2 (85), 161–166.
- Udod, V. M., Vil'dman, I. L. (2014). Naukove obg'runtuvannya vykorystannya pokaznykiv asimilacijnogo potencialu ta asimilacijnoi' jemnosti dlja ekologichnoi' ocinky stanu gidroekosystem richok, 1 (17), 50–53.
- Yatsyk, A. (2007). The method of calculation of anthropogenic load and classification of ecological status basins of small rivers in Ukraine, 71.
- Osadchiiy, V. (2007). Hydrochemical guide. Surface waters Ukraine. Hydrochemical calculations. Methods of analysis, 656.
- Udod, V. M. Patent 20 09 888 2013 and Ukraine, IPC (2006). 27 CO 3/32. Method indyfyfikatsiyi samovidnovnoyi ability y. Prut. Applicant and holder. Kyiv - № 88 143; appl. 09/03/2013; published. 11.03.2014, Bulletin № 5, 6.

ADSORPTION REMOVAL OF COPPER-CONTAINING WASTEWATER ON YAZUV SULFUR MINE BENTONITE (p. 11-15)

Marianna Petrova, Mariana Voitovych

The adsorption properties of bentonite clay of Yaziv mine (Lviv district, Ukraine) was investigated in the process of copper removal. Water contamination by copper originates from industrial wastewater discharge, thus effective methods for copper removal are required. Copper adsorption was effective in wide range of concentrations; the adsorbent saturation by copper ions did not take place. The assay boundary adsorption capacity was 31 mg/g. The kinetic characteristics of the adsorbent were defined and the time for copper removal did not exceed 2 hours. The pH range for the effective adsorption was determined, namely pH>4. The kinetic models were applied for the experimental data, namely pseudo-first, pseudo-second order, intraparticle diffusion, Bangham and Ritchie models. The process followed the pseudo-second order model, thus it was found to be limited by the chemical reaction between copper and functional groups of bentonite. When copper removal from solutions with high concentrations of potassium (up to 0.1 M) was performed, the insignificant adsorption retardation was observed. This confirmed the activity of functional adsorption sites selective for copper during adsorption process. The combination of high capacity and favourable kinetic characteristics, along with the selectivity, confirmed the prospective for bentonite application in waste water treatment technologies.

Keywords: effluent, purification, copper, adsorption, chemisorption, montmorillonite, bentonite, capacity, selectivity, kinetics.

References

- Ministry of Regional Development, Construction, Residential and Public Facilities (2013). National report about quality of drinking water and state of drinking water supply in Ukraine in 2012. Kyiv: Ministry of Regional Development, Construction, Residential and Public Facilities, 450.
- Stanko, O. M. (2012). Heavy metals in water: pollution of the river Dniester for the last 10 years (territory of Lviv district). Ecological Toxicology, 58–63.
- Lototska-Dudyk, U. B., Krupka, N. O., Halay, O. A., Stanko, O. M. (2013). Hygienic assessment of water quality in Lviv sources. Environment and Health, 2, 60–62.
- Andrusyshyna, I. M., Lampeka, O. H., Holub, I. O. (2010). Application of ICP–AES for determination of chemical elements in water of Kiev and Kiev district. Environment and Health, 2, 14–18.
- Madzha, S. M., Dmytrukha, T. I., Radomska, M. M., Trofimov, I. L. (2014). Assessment of ground water pollution by heavy metals near enterprises of commercial aviation. Environmental Safety, 1, 69–73.
- Likhachev, N. I., Larin, I. I., Khaskin, S. A., Alferova, L. A., Berhdichevskyy, D. A., Belostotskyy, M. D., Turovskyy, I. S. (1981). Wastewater disposal of residential areas and industrial enterprises. Moscow: Stroyizdat, 639.
- Shabliy, T. O. (2010). Removal of copper ions from heat-exchanging circulating systems water. Eastern-European Journal of Enterprise Technologies, 3/8(45), 10–13.
- Linnik, P. N., Zhezherya, V. A., Linnik, R. N., Ivanchenko, Ya. S. (2012). Levels and distribution of aluminium, ferric, and copper

- among their occurrence forms in water of some Shatsk lakes. *Environmental Chemistry*, 21 (2), 98–111.
9. Yermakov, D. V., Sviridov, A. V., Ibatulina, Yu. R. (2004). Copper (II) recovery with colloid adsorbents. *Proceedings of Chelyabinsk Scientific Center*, 1, 165–167.
 10. Vinogradov, S. S. (1998). *Environmentally safe electroplating industry*. Moscow: Hlobus, 302.
 11. Petrova, Ye. V., Astashkina, A. P., Filonenko, D. A., Otmakhov, V. I., Izaak, T. I. (2007). Research of perspective opportunities for application of hydrophobic fibrous sorbents in removal of metal ions from water. *Proceedings of Tomsk Polytechnic University*, 310 (2), 136–141.
 12. Kovalev, I. A., Sorokina, N. M., Tsizin, G. I. (2000). Selection of an effective adsorbent for heavy metals removal from effluents in dynamic conditions. *Transactions of Moscow University. Series 2. Chemistry*, 41 (5), 309–314.
 13. Markov, V. F., Formaziuk, N. I., Maskaeva, L. N., Makurin, U. N., Stepanovskikh, Ye. I. (2007). Removal of copper (II) from industrial effluents with composite sorbent of strongly acidic cation – ferric hydroxide. *Alternate Energetics and Ecology*, 3 (47), 144–149.
 14. Liu, Z., Zhou, S. (2010). Adsorption of copper and nickel on N-bentonite. *Process Safety and Environmental Protection*, 88 (1), 62–66. doi: <http://dx.doi.org/10.1016/j.psep.2009.09.001>
 15. Futralan, C. M., Kan C. C., Dalida, M. L. Hsien, K. J., Pascua, C., Wan, M.-W. (2011). Comparative and competitive adsorption of copper, lead, and nickel using chitosan immobilized on bentonite. *Carbohydrate Polymers*, 83 (2), 528–536. <http://dx.doi.org/10.1016/j.carbpol.2010.08.013>
 16. Bertagnolli, C., Kleinübing, S. J., Silva, M. G. C. (2011). Preparation and characterization of a Brazilian bentonite clay for removal of copper in porous beds. *Applied Clay Science*, 53 (1), 73–79. doi: <http://dx.doi.org/10.1016/j.clay.2011.05.002>
 17. Zhao, G., Zhang, H., Fan, Q., Ren, X., Li, J., Chen, Y., Wang, X. (2010). Sorption of copper (II) onto super-adsorbent of bentonite–polyacrylamide composites. *Journal of Hazardous Materials*, 173 (1–3), 661–668. <http://dx.doi.org/10.1016/j.jhazmat.2009.08.135>
 18. Karamanis, D., Assimakopoulos, P. A. (2007). Efficiency of alumina num-pillared montmorillonite on the removal of cesium and copper from aqueous solutions. *Water Research*, 41 (9), 1897–1906. doi: <http://dx.doi.org/10.1016/j.watres.2007.01.053>
 19. Petrushka, I. M., Tarasovych, O. D. (2013). Utilization of spent sorbents for production of construction materials. *Transactions of Lviv National Polytechnic University. Series: Theory and Practice of Construction*, 755, 305–308.
 20. El-Kamash, A. M. (2008). Evaluation of zeolite A for the sorptive removal of Cs⁺ and Sr²⁺ ions from aqueous solutions using batch and fixed bed column operations. *Journal of Hazardous Materials*, 151 (2–3), 432–445. doi: <http://dx.doi.org/10.1016/j.jhazmat.2007.06.009>
 21. Girol', A. M. (2011). Problema doochishhennja stichnih vod v Ukraïni ta shljahi її virishennja. *Ekologija. Ljudyna. Suspil'stvo*. Kiev: Nacional'nyj tehnologichnij universitet Ukraïni «KPI», 44–45.
 22. Krupko, V. A. (2013). Shljahi minimizacii zabrudnennja dovkillja. Novitni dosjagnennja geodezii, geoinformatiki ta zemlevporjadkuvannja–Evropejs'kij dosvid. *ChDIEU*, 9, 128–130.
 23. Bottril, P. (1997). Minimizing the sludge disposal problem. *Water and Waste treat*, 40 (9), 26.
 24. EN 12255-6 (2002). *Wastewater treatment plants – Part 6: Activated sludge process*, 14.
 25. Eikelboom, D. H. (2000). *Process Control of Activated Sludge Plants by Microscopic Investigation*. London: IWA Publishing, 156.
 26. ISO 26000: 2010. (2010). *Guidance on Social Responsibility (Nastanova z social'noi vidpovidal'nosti)*.
 27. Grycyna, O. O. (2011). Pidvyshhennja efektyvnosti roboty aerotenkiv dlja glybokoi' ochystky mis'kyh stichnyh vod vid spoluk azotu. *Ekologija. Ljudyna. Suspil'stvo*. Kiev: Nacional'nyj tehnologichnij universytet Ukraïny «KPI», 50–51.
 28. Bljashyna, M. V., Sablij, L. A. (2011). Anaerobne ochyshhennja stichnyh vod na pershij stadii' biologichnoi' ochystky. *Ekologija. Ljudyna. Suspil'stvo*. Kiev: Nacional'nyj tehnologichnij universytet Ukraïny «KPI», 33–34.
 29. Ternov's'ka, O. I., Erina, I. M. (2012). Doslidzhennja procesiv doochyshhennja mis'kyh stichnyh vod. *Ekologicheskaja y tehnogennaja bezopasnost'. Ochrana vodnogo y vozdušnogo basseinov. Utylyzacija othodov*. Sb.nauchn.trudov VODGEO. Kharkiv, YPP «Kontrast», 134–139.
 30. Mihajlovskaja, M. V. (2008). ANAMOKS – kak metod udalenija soedinenij azota iz stochnyh vod i perspektivy ego primenenija v Ukraine. *Himija i tehnologija vody*, 30 (6), 675–683.
 31. Myhajlovs'ka, M. V., Gvozdzjak, P. I. (2007). Porivnjal'nyj analiz biologichnogo ochyshhennja stichnyh vod vid spoluk azotu. *Naukovi visti NTU «KPI»*, 2, 109–117.
 32. Temperatura i sostav stochnyh vod. Available at: <http://domremstroy.ru/da/kanalizacia06.html>
 33. Jakovlev, S. V., Karelin, A. Ja., Laskov, Ju. M., Voronin, Ju. V. (1985). *Ochistka proizvodstvennyh stochnyh vod*. Moscow: Strojizdat, 162.
 34. Ajerobnye processy biokhimicheskoj ochistki stochnyh vod. Available at: http://libertydoc.net/books/-mikrobiologicheskoe_proizvodstvo_bavt.6___2.aerobnye_processy_biokhimicheskoi_ochistkistochnyh_vod
 35. Teorija i raschet kombinirovannyh sooruzhenij biologicheskoi ochistki stochnyh vod. Available at: http://www.mediana-eco.ru/information/stoki_biological/calculation
 36. Zhmur, N. S. (1997). *Upravlenie processom i kontrol' rezul'tata ochistki stochnyh vod na sooruzhenijah s ajerotenkami*. Moscow: Luch, 118.
 37. Drolka, M. (2001). The Results of Mathematical Model and Pilot Plant Research of Wastewater Treatment, Model and Wastewater Treatment. *Chem. Biochem. Eng. Q.*, 15 (2), 71–74.

MODELING OF BIOLOGICAL WASTEWATER TREATMENT PLANT EFFICIENCY (p. 16-20)

Olga Shevchenko, Vitaly Krupko, Leonid Klintsov, Inna Ivanova

The research explores the efficiency of wastewater treatment at a biological treatment plant with respect to the biochemical oxygen demand indicators within five days at the inlet and outlet of the treatment plant. Different seasons have been provided with the mathematical models of the plant's operational efficiency depending on the weather conditions that affect the load on the activated sludge and its treatability (taking into account the reliance on the air temperature, precipitation amount, and the presence of melting snow). The quality of the obtained models is evaluated with the determination coefficient *d*. The best determination coefficients are: for winter *d*=0.92, for spring *d*=0.98, for summer *d*=0.80, and for autumn *d*=0.82.

Accounting for the forecast and the obtained dependencies will contribute to the implementation of operational actions, which provide the wastewater treatment quality.

Keywords: wastewater, treatment efficiency, temperature, biological oxygen demand, biocenosis.

References

1. Shhetinin, A. I., Meshengisser, Ju. M., Esin, M. A., Malbiev, B. Ju., Regotun, A. A. (2011). Opyt rekonstrukcii ochisnih sooruzhenij s primeneniem tehnologii nitro-denitrifikacii. *Vodopostachannja ta vodovivvedennja*, 3, 41–49.

DEVELOPMENT OF A MATHEMATICAL MODEL OF THE SYSTEM OF INTEGRATED RADIO ECOLOGICAL MONITORING OF DNIPRODZERZHYN'SK TOWN (p. 21-25)

Valeriia Kovach

Seven tailings dams and two uranium waste storages were formed in the Dniprodzerzhynsk city (Ukraine) in the PA "Pridneprovsky Chemical Plant" (PA "PCP") influence zone after a long mining and processing of uranium ore (1949–1991). Protective covers of most tailings dams and engineering facilities of the uranium production infrastructure in the PA "PCP" territory are poor and getting worse every year under the influence of natural factors and because of the lack of remedial operations. Given the current difficult economic situation in Ukraine, least-cost creation of an effective system of integrated automated radioecological monitoring of the Dniprodzerzhynsk industrial-urban agglomeration area and influence zone of tailings dams is necessary. This was proposed to do by using a mathematical description of the monitoring system through the control loop, which describes the elements of influence on the management object in accordance with the received commands. The measurement results in the management object state are fixed by observation elements and a new management cycle begins. This differs from the systems, previously suggested for this area since the pro-

posed control loop can be used not only for fixed, but also for mobile posts. The developed mathematical model has allowed to justify the optimal number of posts that are placed in the Dniprodzerzhynsk industrial-urban agglomeration and the influence zone of tailings dams to control the difficult ecological situation in the given area.

Keywords: mathematical model, integrated monitoring, control loop, industrial-urban agglomeration.

References

- Lysychnenko, G. V. (2010). Uranium ores of Ukraine. Kyiv, Ukraine: Naukova Dumka, 221.
- Kulish, Ye. A., Mykhajlov, V. A. (2006). Geochemistry, mineralogy, genesis and classification of uranium deposits. Kyiv, Ukraine, 213.
- Shamshuchenko, Yu. S. (Ed.) (1999). Nuclear Legislation of Ukraine: Collection of normative - legal acts. Vol. 1. 2nd edition. Kyiv, Ukraine, 648.
- Sviraki, B. I., Olejnikov, A. G., Storozhenko, N. D., Durova, R. A. (1988). About storage tails recultivation Methodics, 1, 87–89.
- Kamzist, J. S., Kovalenko, A. V. (1991). Engineering Geocology Basics: Methodics of ecological and geological researches. Moscow, USSR, 113.
- Anisimova, L. I., Rogachevskaja, L. M. (1991). Assessment of migration of radionuclides from the repository of radioactive waste. Geocology: problems and solutions. Proc. Conf. and posts. All-Union Conf. nauchn.-tehn. Conference. Moscow, April 26–30, 1990 - h. Hydrogeological 2. aspects of the Ecole. Moscow, USSR, 115–116.
- Ukratom. Situation with storage tails in Ukraine. Available at: <http://ru.uatom.org/posts/28>
- Report on Nuclear and Radiation Safety in Ukraine in 2013. Available at: <http://www.snrc.gov.ua>
- Kovalko, M. P., Denysiuk, S. P. (1997). Energetic security – part of the national security of Ukraine. Kyiv, Ukraine, 197.
- Arapov, Yu. A. (1984). Uranium deposits of Czechoslovakia. Moshkow, USSR. Nedra, 445.
- Brosa, U., Grossmann, S., Müller, A. (1990). Nuclear scission. Physics Reports, 197 (4), 167–262. doi:10.1016/0370-1573(90)90114-h
- Mining and Milling the Uranium. Available at: <http://watd.wuthering-heights.co.uk/nuclear/gettinguranium.html>
- Cathy Vakil, M. D., C. C. F. P., F. C. F. P., Linda Harvey, B. Sc., M. Sc., M. D. (2009). Human Health Implications of Uranium Mining and Nuclear Power Generation. Available at: <http://uranium-network.org/images/pdfs-u-rad-health/VAKIL-HARVEY-Human-health-implications-LONG-2009-May.pdf>
- The Ux Consulting Company. Available at: <http://www.uxc.com>
- World Nuclear Association. Military Warheads as a Source of Nuclear Fuel. Available at: <http://www.world-nuclear.org/info/Nuclear-Fuel-Cycle/Uranium-Resources/Military-Warheads-as-a-Source-of-Nuclear-Fuel>
- Ukrainian Centre for Economic & Political Studies Named after Olexander Razumkov (2008). Nuclear energy in the world and in Ukraine: state and prospects of development, 3, 60.
- Shumlianskyj, V., Makarenko, M., Koliabina, I. (2007). Environmental monitoring after extraction method of underground leaching of uranium. Kyiv, Ukraine: Logos, 212.
- Nekliudov, I. M. (Ed.) (2006). Nuclear power. Handling of spent nuclear fuel and radioactive waste. Kyiv: Naukova dumka, 253.
- IAEA-(IAEA RS-G-1.7). International cooperation on rehabilitation (2013). IAEA, VIENNA. Available at: http://www-pub.iaea.org/MTCD/publications/PDF/te_1174_prn.pdf
- Pinner, A. V., Hemming, C. R., Hill, M. D. (1984). An assessment of the radiological protection of aspects at shallow underground burial place of radioactive waste. «Nat. Radiol. Prot. Board», 161 (81), 1–33.
- Hill, M. D., Mitchell, N. T. (1983). Principles used in assessing the input of radionuclide releases to the environment and in establishing of release limits. Radioact. waste manag, 109–125.
- processing the polymer fraction of solid domestic waste was developed. The polymer fraction was used to obtain nitrogen-containing organic compounds, which have a significant influence on the clinker grinding process and physico-mechanical properties of cements and products based on them in the composition of additive.
- It was found that additive effectively influences clinker grinding processes within the concentrations of 0,045–0,065 wt % and has almost no impact on the process of grinding active mineral additives. The additive in a broader concentration range (0,025–0,085 wt %) increases the strength of composite cements in all hardening periods and accelerates the setting time.
- Additive, obtained by chemical processing of polymer fraction of solid domestic waste can be used in the construction industry as clinker grinding activator and cement strength increasing additive. Thus, it is possible to reduce the energy consumption in grinding technology operation and improve the physico-mechanical properties of composite cements, which in turn reduces the content of the cement component in such cements.
- Keywords:** solid domestic waste, polymer fraction, additive, grinding, strength, composite cement.

References

- Jankovic, A., Valery, W. (2004). Cement grinding optimization. Minerals Engineering, Vol. 17, Issue 11–12, 1075–1081.
- Pashchenko, A. A., Myasnokova, E. A., Gumen, V. S., Evsyutin, U. R., Saldugy, M. M. (1991). Theory of cement. K.: «Budivelnik», 168.
- Jolicoeur, C., Morasse, S., Sharman, J., Tagnit-Hamou, A., Slim, F., Page, M. (2007). Polyol-type compounds as clinker grinding aids: influence on powder fluidity and on cement hydration. 12th International congress on the chemistry of cement, Vol. 12. Available: <https://getinfo.de/app/Polyol-Type-Compounds-as-Clinker-Grinding-Aids/id/BLCP%3ACN073877220>.
- Farobie, O., Achmadi, S. S., Darusman, L. K. (2012). Utilization of glycerol derived from Jatropha's biodiesel production as a cement grinding aids. World Academy of Science, Engineering and Technology, Vol. 6, Issue 3, 791–796.
- Fleysher, H. U., Tokarchuk, V. V., Vasylykevich V. I., Sviderskiy, V. A. (2014). Effect of alcohols as hardening-accelerating admixtures on the cement properties. Technology Audit And Production Reserves, 4(1(18)), 31–36. doi:10.15587/2312-8372.2014.26219.
- Klimpel, R. R., Leonard, D. E., Fee, B. S.; The Dow Chemical Company. (1992). Alkanolamine grinding aids. Available: <https://search.rpxcorp.com/pat/US5131600A1>.
- Myers, D. F., Gartner, E. M.; W. R. Grace & Co.-Conn. (1991). Strength enhancing additive for certain Portland cements. Available: <https://search.rpxcorp.com/pat/US4990190A1>.
- Montecelo, I., Viles, R. E., Inamdar, M.; Fosroc International Limited. (2013). Grinding aid. Available: <http://worldwide.espacenet.com/publicationDetails/biblio?CC=EP&NR=2582643A1&KC=A1&FT=D>.
- Struk, O., Nagieva, A. What can we do to solve the problem of garbage invasion in Ukraine? Ukraine without garbage. Available: http://www.novi.org.ua/news/email_golosuvannia_2vikova/Nagijeva_Struk.pdf.
- Tokarchuk, V. V., Sokoltsov, V. U., Sviderskiy, V. A. (2014). Influence of composition mineral additives on cement properties. Technology Audit And Production Reserves, 3(5(17)), 19–22. doi:10.15587/2312-8372.2014.25355.
- DSTU B V.2.7-185:2009. (2009). Cements. Cements. Standard consistency, setting times and sounding test methods. K.: Minrehionbud, 11.
- DSTU B V.2.7 – 187:2009. (2009). Cements. Compressive and shear strength test methods. K.: Minrehionbud, 22.

STUDYING THE NATURE OF MATERIAL SORPTION BASED ON PEAT MOSS SPHAGNUM (p. 30–35)

Olena Matvyeyeva, Iuliia Bondarets

INFLUENCE OF THE NITROGEN-CONTAINING COMPOSITIONS ON THE GRINDING PROCESS AND PHYSICO-MECHANICAL PROPERTIES OF CEMENTS (p. 26–30)

Hanna Fleysher, Volodymyr Sokoltsov, Volodymyr Tokarchuk, Valentin Sviderskiy

To utilize the waste, accumulated in Ukraine, and optimize the clinker grinding process, chemical additive, which is a product of

The paper considered the existing methods of using sphagnum moss as a liquid sorbent, including oil and oil products for identifying regularities of sorption processes on the material. The existing data on the studies of the absorptive capacity of sphagnum moss was analyzed. It was found that the existing studies investigated the dependence of the adsorptive capacity on the processing method (grinding, thermal modification, encapsulation, etc.). However, the

nature and mechanism of sorption have not been studied at all, but there is a set of theoretical assumptions that have not been checked. The characteristic of the existing descriptions of the sorption processes on the material made of sphagnum moss was given. The need for further research for defining the nature and the mechanism of the sphagnum moss interaction with a substance absorbed in the sorption process was determined.

Keywords: sorption, sphagnum moss, sorbent structure, adsorption, adsorption, oil, oil spills, water treatment.

References

- Bondarets, Y., Matvyeyeva, O. (2013). Analysis oil spill treatment technologies with using of sorbents based on peat moss genus Sphagnum. Problems of environmental biotechnology, 1. Available at: <http://jrn1.nau.edu.ua/index.php/ecobiotech/article/view/4732>
- Kamenshekoy, F. A., Bohomolnyi, E. (2005). Oil sorbents. Moskva-Yzhevsk: NYC «Reguljarnaja y haotycheskaja dynamyka», 268.
- State Statistical Yearbook of Ukraine (2013). Kiev: Derzhavna sluzhba statystyky Ukrainy, 552.
- Assessing the needs of Ukraine in the post-accident period. Oil spill in the Kerch (2008). Summary report of the United Nations Environment Programme. European Commission, 10.
- Hrynchyshyn, N. M., Babadzhanyan, A. F. (2008). Rehabilitation of soils contaminated with petroleum emergency effusion. Science Bulletin NLTU Ukraine, 22.7, 43–49.
- Adebadjo, M. O., Frost, R. L., Klopogge, J. T., Cambody, O. (2003). Porous Materials for Oil Spill Cleanup: A review of Synthesis and Absorbing Properties. Journal of Porous materials, 10, 159–170.
- Fingas, M. (2010). Oil Spill Science and Technology - Prevention, Response, and Cleanup. Elsevier, USA, 1192.
- Chandrasekar, S., Sorial, A. W., Weaver, J. W. (2006). Dispersant effectiveness on oil spills. ICES Journal of Marine Science, 63, 1418–1430. doi: 10.1016/j.icesjms.2006.04.019
- Zadverniuk, G. P. (2011). Acquisitions of oil and petroleum products clays Cherkassy deposit. Scientific Papers of the Institute of Environmental Geochemistry, 19, 109–114. Available at: <http://dspace.nbuv.gov.ua/handle/123456789/32262>
- Solovyov, V. I., Gubanov, V. V., Kozhanova, G. A., Gudzenko, T. V., Semina, N. V. (2002). Using sorbent boms for Prevention and elimination of oil pollution. Environmental problems of the Black Sea, 327.
- Vincent Wong, K.-F., Stewart, H. O. (2003). Oil spill boom design for waves. Spill Science and Technol, B 8 (5–6), 543–548. doi: 10.1016/s1353-2561(03)00129-4
- Antoniuk, S. I., Pyrog, T. P., Sorokina, A. I. (2009). Prospects for the use of surfactants Acinetobacter calcoaceticus K-4 for degradation of oil pollution. Food industry, 8, 8–11.
- Veprykova, E. V., Tereshchenko, N. V., Chesnokova, N. V. (2010). Features water purification from petroleum with using sorbents, filter of materials and activated coal. Journal of Siberian Federal University. Chemistry, 5, 285–304.
- Syrotkina, E. Y., Novoselova, L. Y. (2005). Materials for the adsorption of water purification from oil products. Chemistry for Sustainable Development, 13, 359–377.
- Zope, I. S., Joshi, V. S., Venugopalan, P., Hambir, S. S. (2013). Pat. WO 2013/140420 Hydrocarbon absorbing materials and a process for the preparation thereof.
- Karnozhitskiy, P. V., Zhilina, M. V., Svirentko, L. P., Handogina, O. V. (2010). Perspective of using a walnut shell as an adsorbent for water purification from oil products. Communal services cities, 95, 73–77.
- Lim, T.-T. (2007). Evaluation of hydrophobicity/oleophilicity of kapok and its performance in oily water filtration: Comparison of raw and solvent-treated fiber. Chemosphere, 66 (5), 955–963.
- Pavliuh, L. I., Boychenko, S. V. (2012). Pat. 72785 Method of treating oily wastewater. V 12.
- Benes, E. (2002). Pat. 2183501. Sorbents containing sphagnum.
- Pastuhova, N. O., Pastuhov, O. V. (2007). Sorbents osnovi peat. Journal of National University of Water Management and Nature. Collected Works, 4 (40), part. 3, 146–152.
- Just, P., Valor, L. (2003). Pat. WO 200308253. Method and apparatus for productind plant container liners particularly from sphagnum moss.
- Levesque, Y., Cote, S., Gallagher, D. (1996). Pat. 199407463 ZA. Sphagnum moss composition for the production of sheeted absorbent and method for evaluating the potential of sphagnum moss material for adsorbing liquid.
- Berdnikov, V.S. (1996). Pat. 94001178. Tampon.
- Gaetan, C., Martin, R. (1996). Pat. 0779066. Liquid absorbent sphagnum moss article and method for manufacturing the absorbent article.
- Dmitruk, S. E., Babeshina, L. H., Kelus, N. V. (2010). Pat. 02391998. Enterosorbent of plant origin and its production method.
- Ivasishin, P. L. (2009). Dealing with the consequences of oil spills by biodegradable sorbents. Oil Industry, 5, 112–113.
- Bilkey, P. C. (2004). Pat. 6890651 (US20040161606) Water- and oil-absorbent medium comprising milled sphagnum, sphagnum moss, and/or sphagnum peat.
- Mihalevskaya, T. V., Fokin, A. V., Franchuk, G. M., Kramarenko, R. M. (2009). Pat. 49293 Method of cleaning water from oil.
- Zonova, L. D., Horelov, V. V., Basov, V. N., Hodiasev, M. B., Balkov, V. A. (2006). Pat. 02286208. A method for producing a sorbent for cleaning oil from water and solid surfaces.

ADSORPTION AND BARRIER PROPERTIES OF YAZIV MINE BENTONITE AS MATERIAL FOR LANDFILL LINERS (p. 36-41)

Marianna Petrova, Mariia Postnikova, Kateryna Stepova

The properties of natural bentonite clay of Yaziv mine (Lviv region, Ukraine) as a material for landfill liners and solid household and industrial waste storages were investigated. Copper and ammonium were selected as components that imitate the filtrate composition. Filtration coefficient, which is 10.9 m/s was experimentally found. Based on the porosity analysis, it was determined that the mineral belongs to the microporous materials with an average pore radius of 5 Å. It was revealed that bentonite is able to irreversibly absorb large amounts of copper by the ion exchange mechanism. The full capacity of the mineral by copper is 115 mg/g. Ammonium adsorption proceeds according to the physical adsorption mechanism; maximum adsorption capacity is 0.175 mg/g. Saturation of the adsorbent is reached on the first day due to the high specific surface area. Remobilization ability of components when applying different desorbing agents was examined. The data obtained suggest that the adsorption ability of bentonite clay liners is not enough to ensure the environmental safety of ground and surface waters. Barriers, made of several materials with low permeability, different porosity, specific surface area and high adsorption ability of the filtrate components must be used.

Keywords: adsorption, desorption, bentonite, filtrate, migration, copper, ammonium, waste, landfills, dumps.

References

- Thompson, T. P. (2007). Chemical safety of drinking-water: Assessing priorities for risk assessment. Geneva: World Health Organization. Available at: http://whqlibdoc.who.int/publications/2007/9789241546768_eng.pdf
- Kreith, F., Tshobanoglous, G. (Ed.) (2002). Handbook of solid waste management. New York: McGraw-Hill, 950.
- Godovska, T. B., Feshchenko, V. P. (2010). Ecological and economical analysis of solid waste management on the example of Zhytomyr region. Transactions of Zhytomyrskii National Agroecological University, 2, 220–227.
- Nikolaiev, A. M. (2014). The impact of municipal solid waste of Chernivtsi on ground and surface waters, soils and bottom sediments of water courses. Scientific Transactions of Chernivtsi University: Collected Works, 10 (2), 664–667.
- Voloshyn, P. (2014). Analysis of Lviv landfill impact on the environment. Transactions of Lviv University. Geological Series, 26, 139–147.
- Kiselev, N. N., Filatov, V. F., Dubrova, N. A., Kvashuk, O. Yu. (2008). Survey of contamination process on industrial landfills of Horlovka chemical plant. Scientific works of UkrNDMI NAN, 2, 199–210.
- Yeroshyina, D. M., Khodin, V. V., Zybrickii, V. S., Demidov, A. L. (2010). Environmental aspects of municipal solid waste disposal on landfills. Minsk: BelNITS “Ecology”, 152.
- Koch, D. (2002). Bentonites as a basic material for technical base liners and site encapsulation cut-off walls. Applied Clay Science, 21 (1–2), 1–11. doi: 10.1016/S0169-1317(01)00087-4
- Golubev, V. S., Harbiants, A. A. (1968). Heterogeneous processes of geochemical migration. Moscow: Nedra, 192.
- Voronkova, T. V. (2009). Improvement of an impervious barrier for pollutants emission reduction of municipal solid waste landfills. Perm Polytechnic University, Perm, Russian Federation, 17.
- Varank, G., Demir, A., Top, S., Sekman, E., Akkaya, E., Yetilmezsoy, K., Bilgili, M. S. (2011). Migration behavior of landfill leachate contaminants through alternative composite liners. Science of the

- Total Environment, 409 (17), 3183–3196. doi: 10.1016/j.scitotenv.2011.04.044
12. Kononenko, L. V., Manicev, V. I., Koliabina, I. L., Koromyslichenko, T. I. (2010). Sorption kinetics of cesium-137 and strontium-90 by clay. *Journal of Mineralogy*, 32 (3), 88–95.
 13. Bergaya, F., Theng, B. K. G., Lagaly, G. (2006). *Handbook of clay science*. Amsterdam: Elsevier, 1224. doi: 10.1016/B978-0-08-098259-5.00023-8.
 14. Guney, Y., Cetin, Y. B., Aydilek, A. H. (2013). Utilization of sepiolite materials as a bottom liner material in solid waste landfills. *Waste Management*, 34 (1), 112–124. doi: 10.1016/j.wasman.2013.10.008
 15. Kaya, A., Durukan, S. (2004). Utilization of bentonite-embedded zeolite as clay liner. *Applied Clay Science*, 25 (1-2), 83–91. doi: 10.1016/j.clay.2003.07.002
 16. Kruempelbeck, J. G. (1999). Long-term behaviour of municipal solid waste landfills in Germany. *Proceedings of Sardinia 99, Seventh International Waste Management and Landfill Symposium*, 1, 27–36. doi: 10.1002/bate.199904440
 17. Petrova, M. A. (2011). Decontamination of radioactive liquid waste containing cesium -137 and strontium -90 modified clay sorbents. *National Technical University "Kyiv Polytechnic Institute"*, Kyiv, Ukraine, 20.
 18. Webster, C. E., Drago, R. S., Zerner, M. C. (1999). A method for characterizing effective pore sizes of catalysts. *Journal of Physical Chemistry*, 103 (8), 1242–1249. doi: 10.1021/jp984055n
 19. Tan, W. T., Yien Ting, A. S. (2014). Alginate-immobilized bentonite clay: Adsorption efficacy and reusability for Cu(II) removal from aqueous solution. *Bioresource Technology*, 160, 115–118. doi: 10.1016/j.biortech.2013.12.056
 20. Pivato, A., Raga, R. (2006). Tests for the evaluation of ammonium attenuation in MSW landfill leachate by adsorption into bentonite in a landfill liner. *Waste Management*, 26 (2), 123–132. doi: 10.1016/j.wasman.2005.03.009
 21. Alshameri, A., Chunjie, Ya., Yasir, Al-An. (2014). An investigation into the adsorption removal of ammonium by salt activated Chinese (Hulaodu) natural zeolite: Kinetics, isotherms, and thermodynamics. *Journal of the Taiwan Institute of Chemical Engineers*, 45 (5), 554–564. doi: 10.1016/j.jtice.2013.05.008
 22. Arslan, A., Veli, S. (2012). Zeolite 13X for adsorption of ammonium ions from aqueous solutions and hen slaughterhouse wastewaters. *Journal of the Taiwan Institute of Chemical Engineers*, 43, 393–398. doi: 10.1016/j.jtice.2011.11.003

CALCULATION AND ANALYSIS OF PREDICTABLE TECHNOLOGICAL RISK VALUE OF INDUSTRIAL OBJECTS IN STATIONARY OPERATING CONDITIONS (p. 42-46)

Petro Vavulin, Tatyana Boyko

The calculation algorithm of the predictable technological risk value of industrial objects during their operation is described in the paper. The algorithm is based on three methods: the Monte Carlo method, index method and method, based on the reliability theory elements. Using these methods in the present combination allows to avoid the problems, associated with the initial data uncertainty. It should be noted that the initial data uncertainty is a key problem to most common calculation methods.

An example of calculating the technological risk for the system of seven water heaters in the HPP system was considered. The nominal failure probability value of individual elements of the system was calculated by the index method (calculation by the index method includes all the technological risk components, associated with the operating conditions of the object). This allows to avoid the initial data uncertainty problem during the calculation of technological risk of the entire system. The calculated probabilities are the initial data for the Monte Carlo method and the probabilistic method.

After that, computer simulation of the system as a whole was performed by the Monte Carlo method. To obtain accurate results, it is recommended to carry out a sufficiently large number of iterations using the given method. For example, if the nominal element failure probability is 10^{-8} , it is recommended to conduct at least 109 iterations.

As a result, failure probabilities of each element of a complex technological system and the overall system were obtained. To verify the results, the fault tree construction method for the system under

consideration was used. This test showed that the results are accurate, and each of the methods can be used to calculate the technological risk of industrial objects during operation.

Keywords: Monte Carlo method, technological risk assessment, failure probability, reliability theory, simulation, acceptable risk.

References

1. Ostreykovskiy, V. A., Genyush, A. O., Shevchenko, E. N. (2010). *Matematicheskoe modelirovaniye tehnogennogo riska*. Ucheb. posobie. Surgut: ITS SurGU, 83.
2. William, R. D. (2002). *Practical Design of Safety-Critical Computer Systems*. Reliability Press, 166–176.
3. Sinnamon, R. M., Andrews, J. D. (1996). Quantitative Fault Tree Analysis Using Binary Decision Diagrams. *European Journal of Automation*, 30 (8).
4. Boudali, H., Dugan, J. B. (2005). A discrete-time Bayesian network reliability modeling and analysis framework. *Reliability Engineering and System Safety*, 87 (3), 337–349.
5. Boyko, T. V., Bendyug, V. I., Komarista, B. M. (2010). Aspects of the use of ICT in higher education. *Eastern-European Journal of Enterprise Technologies*, 2/10(44), 52–54. Available at: <http://journals.uran.ua/eejet/article/view/2781/2587>
6. Bendyug, V. I. (2005). *Sistema otsinki tehnogennoyi bezpeki promislovih pidpriemstv: metodologiya ta algoritm rozrahunku*. Kiyv, 193.
7. Boyko, T. V. (2009). Osoblivosti vikoristannya metoda «Indeksirizik» dlya otsinki tehnogennoyi bezpeki ob'ektiv. *Eastern-European Journal of Enterprise Technologies*, 6/5(42), 44–47.
8. Smolich, S. V., Smolich, K. S. (2004). *Reshenie gorno-geologicheskikh zadach metodom «Monte-Karlo»*. Ucheb. Posobie. Chita: ChitGU, 103.
9. Egorov, A. F., Savitskaya, T. V. (2006). *Upravlenie bezopasnostyu himicheskikh proizvodstv na osnove novykh informatsionnykh tehnologiy*. Moscow: «HimiyaKolosS», 416.
10. Nazarenko, M. V., Boyko, T. V., Bendyug, V. I. (2011). The features of identification anthropogenic risks of chemical – technological objects on the design stage. *Eastern-European Journal of Enterprise Technologies*, 3/11(51), 13–17. Available at: <http://journals.uran.ua/eejet/article/view/1713/1610>

CESIUM SORPTION INTENSIFICATION BY COMPLEX NATURAL SORBENTS FROM LIQUID RADIOACTIVE MEDIA (p. 47-50)

Igor Petrushka, Yuri Ytchyshyn, Katerina Petrushka

The studies have shown a growth (up to 90 %) in the sorption degree of strontium ions by composite sorbents based on the modified titanium oxide of bentonite rocks and montmorillonite in a ratio of 1:1. Optimum hydrodynamic regimes (350 rev/min), which increase the emergence effect of complex natural sorbents were determined. Intensification of external diffusion of cesium from liquid radioactive waste was calculated using the theory of local isotropic turbulence, taking into account the flow turbulence hydrodynamics and geometric parameters of mixers. The diffusion coefficient of strontium in the model solution, computed using the Wilkie and Chang dependence allows to predict the kinetics of external diffusion mass transfer of cesium ions in liquid medium based on the theoretical values of mass transfer coefficient. For a correlation of experimental and theoretical data of mass transfer coefficient during external diffusion mass transfer process, correction factor k_{β} (1,1–1,25) was calculated, which takes into account the radial distribution heterogeneity of solid dispersion particles in the system center and near the walls of the device depending on the particle size distribution and the size of the device.

Keywords: modified bentonite, adsorbent, liquid radioactive waste, Cs-134, external diffusion.

References

1. Kulsky, L., Stahov, E., Voloshinova, A., Bliznykova, V. (1979). *Cleaning water nuclear power plants*. Kiev Nauka: Dumka, 209.
2. Kuznetsov, Y., Schebetkovsky, V., Trusov, A. (1974). *Basics of water purification from radioactive contamination*. Moscow: Atomizdat, 360.
3. Basharin, A., Vishnevskaya, A., Drugachenok, M., Lebedev, A., Baklai, A. (2003). Sorption release 137-Cs and 90-Sr karbonatosoderzhashchim natural mineral trepel. *Radiochemistry*, 43 (3), 262–264.

4. Gafvert, T., Ellmark, T., Holm, E. (2002). Removal of radionuclides at a waterworks. *Journal of Environmental Radioactivity*, 63 (2), 105–115. doi: 10.1016/S0265-931X(02)00020-6
5. Vorozhtsov, N., Venkataraman, K. (1970). Intermediates (for synthetic dyes). *The chemistry of synthetic dyes*, 3, 85–167.
6. Petrova, M., Flowers, A., Petrushka, I., Krip, I. (2008). Effect of pH and ionic strength salt solutions on sorption extraction of strontium and cesium on the modified clay minerals. *Questions chemistry and chemical technology*, 3, 116–120. doi: 10.1134/S1066362208050123
7. Petrushka, I., Malyovanyy, M., Petrushka, K. (2012). The mechanism of sorption of Cs-137 and Sr-90 radioactive liquid waste Yazivskogo modified clays. *Eastern-European Journal of Enterprise Technologies*, 4/6(58), 28–31. Available at: <http://journals.urau.ua/eejet/article/view/5589/5029>
8. Petrus, R., Akselrud, G., Gumnicki, Y., Piantkowski, W. (1998). *Wymiana masy w układzie „ciało stałe-ciecz”*. Rzeszów, 365.
9. Rudobashta, S. Mass transfer systems in the solid phase. (1980). Edited by prof. Planovskiy A. Moscow: Chemistry, 247.
10. Braginsky, L., Begachev, V., Barabash, V. (1984). *Stirring fluids*. Leningrad: Chemistry, 336.

РАЗРАБОТКА МЕТОДОЛОГИИ ИНТЕГРАЛЬНОГО ОЦЕНИВАНИЯ ЭКОЛОГИЧЕСКОГО СОСТОЯНИЯ ТЕРРИТОРИЙ (p. 51-56)

Victor Belogurov

Ecological state of the territories is usually estimated by determining the belongingness of each of the geosphere ecological state indicators to one of the classes. The developed methodology is characterized by the fact that the estimates are distributed according to the classes not uniformly, but taking into account the normalization principles and Liebig's law; integral estimate is calculated in accordance with the hypothesis on the logistic nature of the ecosystem change.

The methodology allows to determine the integral estimates objectively (without the participation of experts) by calculations according to official data (annual country reports) using a thoroughly

structured procedure, which allows to monitor the contribution of each indicator to the overall estimate. The results are presented in the form of maps and attribute tables for geospheres and territory as a whole, and are suitable for management.

Keywords: ecological state, geospheres, integral estimation, indicators, state space, GIS technology

References

1. Environmental Monitoring and Assessment. Eastern Europe, the Caucasus and Central Asia (2003). GVE/R.04.0.3 United Nations.
2. Directiva Europejskiego Parlamentu i Rady Europejskiego Sojuszu №2000/60/EC (2000), 196
3. Global Assessment of Human Induced Soil Degradation (GLASOD) (1991). Users Guide to the GLOBAL DIGITAL DATABASE, 230.
4. Living Planet Report 2006. WWF International (2007). Gland, Switzerland. Available at: www.panda.org/livingplanet
5. Baranovsky, V. A. (2001). *Ecological geography and ecological cartography*. Kiev: Fitosotsiotsentr, 252.
6. Zakrutkin, V. E. (Ed.) (2000). *Ecological Atlas of the Rostov Region*. Rostov-Don. Izd-vo SKNTs VSh, 120.
7. *Ecological Atlas of Kharkiv Region* (2001). MONOAP- Maydan, 80.
8. Mischenko, L. V. Methodology, methods organizatsii i provedeniya ecological audita teritorij (Karpaty region). Available at: www.info-library.com.ua/libs/stattya/2686-metodologija-metodi
9. Reymers, N. F. (1994). *Ecology: theories, laws, governed, principles and hypotheses*. Moscow: Russia young, 367.
10. Kriterij otsenki ekologicheskoy obstanovki teritorij dlja zon chresvychnajnoj ekologicheskoy situatsij I zon ekologicheskogo bedstvija (1992). Moscow: Minprirody of Russian Federation, 51.
11. Medvedev, V. V., Laktionova, T. M. (Ed.) (1998). *Landed resources of Ukraine*. Kiev: Agrarian science, 318.
12. Belogurov, V. P. (1990). Two varieties of ecological norms. In sb.: *Methodology of the ecological setting of norms. Part 1*. Kharkiv: VNIIVO, 8–9.
13. Golubev, G. N. (1999). *Geoecology. Educationbook*. Moscow: GEOS, 338.
14. Dedju, I. I. (1989). *Ecological Enciklopedichesky Slovarj*. Kishineu, 406.