

IDENTIFICATION OF THE GEOMETRY AND ELASTIC PROPERTIES OF RIGID INCLUSIONS IN THIN PLATE (p. 4-9)

Nataly Guk, Natalia Stepanova

The presence of inclusions in thin-walled structural elements in the course of their operation under mechanical and thermal loads gives rise to the material damage. In publications on this subject, the problem of defect identification is considered in two directions – the location and shape of the defect or the physical properties of rigid inclusions are determined.

The paper proposes a method for simultaneous determination of the location of rigid inclusions and their elastic properties (Young's modulus) in a thin plate. The mathematical model of a plate with the inclusion is built in the framework of the linear theory of elasticity. For quantization of unknown functions, the finite element method is used. The geometric inverse problem is formulated in the conditional-correct statement.

The parameters of rigid inclusions are determined by minimizing the quality functional. Additional conditions are attached to the functional using the Lagrange multipliers. The results of the identification of one or several inclusions of different sizes by the proposed method are presented. In solving the problem for a plate with one rigid inclusion, the error of restoration of the inclusion location does not exceed 3 %, the error of determination of the Young's modulus of this inclusion – 2 %. The error of determination of the Young's modulus for a group of several rigid inclusions is in the range of 4–7 %.

Comparative analysis of numerical experiment results shows that the proposed method allows identifying the location and properties of several rigid inclusions of various sizes.

Solution of the problem of identifying the inclusions, determining their size and elastic properties allows more accurate estimation of the strength characteristics of elements and prediction of the service life of structures.

Keywords: thin plate, rigid inclusion, geometric inverse problem, finite element method.

References

- Goldstein, R. V., Shifrin, E. I., Shushpannikov, P. S. (2007). Application of invariant integrals to the problems of defect identification. *International Journal of Fracture*, 147 (1-4), 45–54. doi: 10.1007/s10704-007-9125-y
- Goldstein, R., Shifrin, E., Shushpannikov, P. (2008). Application of invariant integrals to elastostatic inverse problems. *Comptes Rendus Mecanique*, 336 (1-2), 108–117. doi: 10.1016/j.crme.2007.11.002
- Kang, H., Kim, E., Lee, J.-Y. (2007). Numerical reconstruction of a cluster of small elastic inclusions. *Inverse Problems*, 23 (6), 2311–2324. doi: 10.1088/0266-5611/23/6/002
- Shifrin, E. I., Shushpannikov, P. S. (2015). Identification of finitely many small defects in an anisotropic linearly elastic body from a single static test. *Mechanics of Solids*, 50 (4), 421–431. doi: 10.3103/s0025654415040081
- Ammari, H., Kang, H., Kim, E., Lim, M. (2005). Reconstruction of Closely Spaced Small Inclusions. *SIAM Journal on Numerical Analysis*, 42 (6), 2408–2428. doi: 10.1137/s0036142903422752
- Baratchart, L., Abda, A. B., Hassen, F. B., Leblond, J. (2004). Recovery of pointwise sources or small inclusions in 2D domains and rational approximation. *Inverse Problems*, 21 (1), 51–74. doi: 10.1088/0266-5611/21/1/005
- Kang, H., Kim, E., Lee, J.-Y. (2003). Identification of elastic inclusions and elastic moment tensors by boundary measurements. *Inverse Problems*, 19 (3), 703–724. doi: 10.1088/0266-5611/19/3/314
- Khoddad, M., Ardakani, M. D. (2011). Investigation of Effect of Different Boundary Conditions on the Identification of a Cavity inside Solid Bodies. *Int. J. Adv. Des. Manufact. Tech.*, 4, 9–17.
- Morassi, A., Rosset, E. (2003). Detecting Rigid Inclusions, or Cavities, in an Elastic Body. *Journal of Elasticity*, 73 (1-3), 101–126. doi: 10.1023/b:elas.0000029955.79981.1d
- Ameur, H. B., Burger, M., Hackl, B. (2004). Level set methods for geometric inverse problems in linear elasticity. *Inverse Problems*, 20 (3), 673–696. doi: 10.1088/0266-5611/20/3/003
- Engelhardt, M., Schanz, M., Stavroulakis, G. E., Antes, H. (2006). Defect identification in 3-D elastostatics using a genetic algorithm. *Optimization and Engineering*, 7 (1), 63–79. doi: 10.1007/s11081-006-6591-4

RESEARCH OF THE STRESS-STRAIN STATE OF THE CONTAINER SHIP DECK ELEMENTS USING THE KARMAN DIFFERENTIAL EQUATION SYSTEM (p. 10-19)

Valerij Maltsev, Anatoliy Nyrkov, Sergei Sokolov

The current stage of development of the shipbuilding industry is characterized by the emergence of new types of ships, structurally significantly different from the traditional ones. In this connection, it is necessary to build more rigorous physical models describing the behavior of ship structures under the action of external loads.

Structural mechanics of the ship, as an independent science, began to form at the beginning of the XX century. The founder of this science according to the rule can be considered a Russian scientist and shipbuilder, professor of the Naval Academy and the shipbuilding department of Petrograd Polytechnic Institute. Based on previous knowledge of the theory of elasticity to them the first rules of allowable stresses have been proposed for surface ships, the methods for evaluating the strength and stability of ship floors and reinforced plates were developed.

Currently, structural mechanics of the ship faces a number of problems requiring urgent solutions, such as the desire for maximum reduction of body materials consumption, the emergence of new, more advanced manufacturing processes of the hull. To solve these problems, it is necessary to turn to the theoretical research and use the knowledge gained during the last three centuries, various scientists involved in various developments in the science of strength of materials, theory of elasticity, and theory of plasticity and structural mechanics of the ship.

The importance of building effective and reliable calculation methods to predict the impact of the loading process on the long-term strength of structural materials is caused by the need to ensure long-term durability of structures in the conditions of insufficient and costly experimental studies.

Container shipping today is the most convenient and the most universal means of transportation. A wide variety of types of containers (dry cargo, refrigerated, insulated, flat track, tank containers) ensures not only fast loading and unloading, but also the opportunity to use the maximum vessel capacity.

The software system was studied and defined, which allows determining the deformation of the upper deck of the ship while loading and on the resulting chart voltages to determine possible locations of damage with the aim of preventing them, because any accident on the ship can not only cause human and material losses, but also major environmental disasters.

The practical value of the results of the work lies in the fact that these studies make it possible to assess the actual loading of shipbuilding structures in terms of their operation.

Keywords: ship plate, stress-strain state, Karman differential equation system, finite difference method.

References

- Bojcov, G. V., Palij, O. M., Postnov, V. A., Chuvikovskij, V. S. (1982). Handbook of structural mechanics of the ship plates in three volumes, Vol. 2. Theory of elasticity, plasticity and creep. Numerical methods. Leningrad: "Shipbuilding", 528.
- Collection of normative-methodical materials: Book Eleven (2002). Russian Maritime Register of Shipping, 32–37.
- Goloskokov, D. P. (2016). Model of ship's overlapping's as a constructive-orthotropic plate – Bulletin of the Admiral Makarov State University of Maritime and Inland Shipping, 1 (35), 189–197.
- Baryshnikov, S. O., Sukhoterin, M. V. (2012). Strength, stability, oscillation plane elements of ship structures. Publisher: Shipbuilding, 168.
- Manuhin, V. A., Verbitskaya, M. U. (2013). Analytical solution of the problem of stability equilateral triangular plates – "Sea bulletin", Publisher: OOO Izdatelstvo "MorVest", 1 (10), 61–62.
- Chernyi, S. (2015). The implementation of technology of multi-user client-server applications for systems of decision making support. Metallurgical and Mining Industry", 3, 60–65.
- Chernyi, S., Zhilenkov, A. (2015). Analysis of complex structures of marine systems with attraction methods of neural systems. Metallurgical and Mining Industry, 1, 37–44.
- Atiskov, A. J., Baranova, D. A., Karpov, V. V., Moskalenko, L. P., Semenov, A. A. (2012). Computer technologies of calculation of the shells. Publisher: Saint-Petersburg State University of Architecture and Civil Engineering, 184.
- Alice, M., George, J. P., Mathew, J. J. (2013). Ultimate torsional strength analysis of container ship, International Journal of Engineering Science and Technology, 5 (3), 512–518.
- Han, F. L., Wang, C. H., Hu, A. K., Liu, Y. C. (2014). Fatigue Strength Assessment Analysis of Large Container Ship. Applied Mechanics and Materials, 602-605, 385–389. doi: 10.4028/www.scientific.net/amm.602-605.385
- Domnisoru, L., Rubanenco, I., Amoraritei, M. (2014). Structural Safety Assessment of a 1100 TEU Container Ship, Based on a Enhanced Long Term Fatigue Analysis. Advanced Materials Research, 1036, 935–940. doi: 10.4028/www.scientific.net/amr.1036.935
- ANSYS. Available at: <https://ru.wikipedia.org/wiki/ANSYS>
- Yasnitsky, L. N. (2005). For whom the tolls ANSYS, or why so many were falling aircraft, missiles exploding, collapsing buildings. A new companion, 1 (342), 1–5.
- Malyh, M. D. (2012). Finite Element Method on the example of the first boundary value problem for the Poisson equation. Moscow: Physics Department of Moscow State University.
- Mechanica sive motus scientia analytice exponenta, 2 m. (1850). St. Petersburg, 1736 German translation Wolfers (Wolfers, JP, Greifswald).
- Maltsev, V. A. (2014). Application of the finite element method to the calculation of the stress-strain state of a container deck slabs. Bulletin of the Admiral Makarov State University of Maritime and Inland Shipping, 6 (28), 190–197.

AN EXPERIMENTAL AND THEORETICAL METHOD OF CALCULATING THE DAMPING RATIO OF THE SUCKER ROD COLUMN OSCILLATION (p. 20-25)

Ivan Steliga, Jaroslav Grydzhuk, Andriy Dzhus

Despite the massive use of dynamograms to identify possible faults in downhole sucker rod pumps (DSRPs), frequent analysis of the deviation of the pumping mode from the optimal mode, and attempts to determine the column load of the sucker rod (SR), little if any attention had been given before this study to oscillation processes that significantly affect the column's durability. In view of the expedience of considering the SR column as an oscillation model, the objective of the study consisted in developing a method of determining the column oscillation damping ratio on the basis of the obtained DSRP dynamograms. The study considered the nature of the dissipative forces and their impact on the character of the SR column damping. It has proven a reasonable possibility of studying the intensity of oscillations' damping in defferent sections of the dynamograms. This was done by analysing real estuarine and abyssal dynamograms and approximation of oscillogramed sections in the form of periodic changes in the load factor of oscillations' damping for particular column layouts. The developed method can be applied to analysing dynamograms of a particular well, whereas the determined damping ratios facilitate assessment of the SR column dynamism and establishment of the best modes of the DSRP operation to prevent resonance under actual operating conditions.

Keywords: sucker rod column, dynamogram, oscillation coefficient, load, damping, oscillogram, approximation.

References

- Virnovskiy, A. S. (1971). Teoriya i praktika hlubinonasnoy dobyche nefi. Moscow: Nedra, 184.
- Tripp, H. A. (1988). Mechanical Performance of Fiberglass Sucker-Rod Strings. SPE Production Engineering, 3 (3), 346–350. doi: 10.2118/14346-pa
- Waggoner, J. R. (1997). Insights from the downhole dynamometer database. Sandia National Laboratories Albuquerque, New Mexico. Available at: <http://www.osti.gov/scitech/servlets/purl/456351>
- Hakimyanov, M. I., Pachin, M. G. (2011). Funktsionalnye vozmozhnosti sovremennogo kontrollera avtomatizatsii shtangovyh glubinonasosnyh ustanovok. Neftegazovoe delo, 2, 19–34. Available at: http://ogbus.ru/authors/Hakimyanov/Hakimyanov_5.pdf
- Oliinyk, A. P., Kopei, B. V., Zinchenko, Yu. S., Kopei, V. B. (2011). Vykorystannia yavlyshcha rezonansu dlia komplektuvannia kolony nasosnykh shtanh. Rozvidka ta rozrobka naftovykh i hazovykh rodovyshch, 1 (38), 69–75.
- Jiang, M. Z., Dong, K. X., Xin, M., Liu, M. X. (2012). Dynamic Instability of Slender Sucker Rod String Vibration Characteristic Research. Advanced Materials Research, 550-553, 3173–3179. doi: 10.4028/www.scientific.net/amr.550-553.3173

7. Jiang, M., Cai, Y., Lu, Y., Wang, D. (2013). Research on Wear Law of Rod String in Directional Well. *Journal of Applied Sciences*, 13 (21), 4676–4680. doi: 10.3923/jas.2013.4676.4680
8. Romero, O. J., Almeida, P. (2014). Numerical simulation of the sucker-rod pumping system. *Ingeniería e Investigación*, 34 (3), 4–11. doi: 10.15446/ing.investig.v34n3.40835
9. Lyskanych, M. V., Hrydzuk, Ja. S., Steliga, I. I. (2015). Otsinka koefitsiientu dynamichnosti kolony nasosnykh shtanh ta vyznachennia umov nedopushchennia yii rezonansu. *Vibratsii v tekhnitsi ta tekhnolohiiakh, tezy dop. XIV Mizhnarodnoi nauk.-tekhn. konf., Dnipropetrovsk: NHU*, 84.
10. Chelomey, V.N. (1979). *Vibratsiya v tekhnike: Spravochnik*. In 6 volumes. Vol. 2. *Kolebaniya nelineynykh mekhanicheskikh system*. Moscow: Mashinostroenie, 351.
11. Darkov, A. V., Shpiro, G. S. (1969). *Soprotivlenie materialov*. Moscow: Vysshaya shkola, 734.
12. Sitdikov, M. R. (2012). Ekspluatatsiya tsepnih privodov shtangovykh skvazhinnykh nasosov v OAO ANK «Bashneft». *Neftegazovoe delo*, 6, 265–272. Available at: http://ogbus.ru/authors/SitdikovMR/SitdikovMR_1.pdf
- nasosa. № 2002116886/06; applied: 24.06.2002; published: 27.12.03, 5.
6. Rabinovich, A. I. (1999). Patent 2138691 Ros. Federacija: F04D13/10, F04D1/06, F04D31/00/. *Stupen' pogruzhnogo mnogostupenchatogo nasosa*. № 97120198/06; applied: 25.11.97; published: 27.09.99, 4.
7. d'Agostino, L., Autieri, M. R. V. (2003) Rotodynamic fluid forces on whirling and cavitating radial impellers. *Fifth International Symposium on Cavitation (cav 2003)*. Osaka, Japan.
8. Mihalić, T., Guzović, Z., Predin, A. (2013). Performances and Flow Analysis in the Centrifugal Vortex Pump. *Journal of Fluids Engineering*, 135 (1), 011107. doi: 10.1115/1.4023198
9. Kolisnichenko, E. V. (2007). *Rabochiy protses dinamicheskikh nasosov netraditsionnykh konstruktivnykh shem na gazogidkostnykh smesyah*. Symu : SymGY, 167.
10. Antonenko, S. S., Kolisnichenko, E. V., Naida, M. V. (2010). Metoduka provedennya provedennya eksperimetalne doslidjennya robotu vidtcentrovo-vuhrovuh stypenei na vusokovyazkuh ridunah. *Visnuk Symskogo derjavnogo yuniversytetu. Seriya Tehnichni nauku*, 2, 7–13.
11. Kolisnichenko, E. V., Naida, M. V., Hovanskiy, S. O. (2011). Eksperimetalne doslidjennya robotu nasosa z vidtcentrovo-vuhrovuh stypenei. *Visnuk natsionalnogo tehnicnogo yuniversytetu «KhPI»*, 34, 119–123.
12. Baibakov, O. V. (1981). *Vihrevue gidravlicheskie mashinu*. Moscow: Mashinostroenie, 197.
13. Yahnenko, S. M. (2003). *Gidrodinamicheskie aspektu blochno-modynogo konstruirovaniya dinamicheskikh nasosov*. Sumy.
14. GOST 6134-87. *Nasosu dinamicheskie, metodu isputaniy* (1989). Moscow, 29.
15. Yaremenko, O. V. (1976). *Isputaniya nasosov*. Moscow: Mashinostroenie, 225.

THE ANALYSIS AND COMPARISON EXPERIMENTAL RESEARCH PUMP WITH CENTRIFUGAL-VORTEX STAGES (p. 26-31)

Maxim Naida

The paper is aimed at investigating the operation of the pump with combined centrifugal-vortex stage. The constructed power characteristics show that the pump has rather a high pressure ($H=12$ m) and low power consumption ($N=0.27$ kW) with low fluid supply ($Q=27$ m³/day).

To determine the combined stage usefulness, comparative power characteristics of the pump with combined centrifugal-vortex stage with centrifugal and vortex pumps, having similar geometric dimensions are obtained. The comparative analysis shows that the pressure of the pump with combined centrifugal-vortex stage is 2.5 times higher than that of two pumps.

This data allows a greater understanding of the further study of pump operation with combined centrifugal-vortex stage.

The results of the tests allow concluding that the application range of pumps with combined centrifugal-vortex stage is quite limited: the oil industry, pressure boosting systems, fire suppression systems, as well as washing and sprinkler systems.

Keywords: pump, centrifugal-vortex stage, impeller, pressure characteristics, power, pressure.

References

1. Spasskiy, K. N., Shaumyn, V. V. (1972). *Novie nasosu dly malih podach i vusokih naporov*. Moscow: «Mashinostroenie», 160.
2. Kupryashin, N. N. (1952). *Tsentrobeshno-vihrevoi nasos*. *Vestnik mashinostroenia*. Machine-building newspaper, 3, 24–27.
3. Tihomir, M., Srđan, M., Živko, K. (2013). Improving centrifugal pump by adding vortex rotor. *Tehnicki vjesnik. Technical Gazette*, 20 (2), 305.
4. Zhu, Z., Xie, P., Ou, G., Cui, B., Li, Y. (2008). Design and Experimental Analyses of Small-flow High-head centrifugal-vortex Pump for Gas-Liquid Two-phase Mixture. *Chinese Journal of Chemical Engineering*, 16 (4), 528–534. doi: 10.1016/s1004-9541(08)60116-0
5. Rabinovich, A. I. (2003). Patent 2232297 Ros. Federacija: F04D1/06, F04D13/08/. *Stupen' centrobezno-vihrevogo*

DEVELOPMENT MATHEMATICAL MODEL HYDRAULIC SYSTEM UNIVERSAL HOSE CONCRETE PUMP (p. 32-42)

Denys Chayka, Inga Emeljanova, Pavlo Andrenko

The paper presents a scheme of a new-design universal pistonless concrete pump with a hydraulic drive and provides a basic diagram of its hydraulic system. To maximize energy efficiency, the designed hydraulic circuit is implemented through the following hydraulic devices: high-torque hydraulic motors, a gear pump, a hydraulic cylinder, hydraulic spreaders, a filter, a safety valve, anticavitation and check valves, a flow controller, and pipelines. The key element in the hydraulic circuit of the pistonless pump is high-torque hydraulic motors that have low rotation frequencies and thus would ensure the necessary torque on the rotor of the concrete pump to push the concrete mix. The designed nonlinear mathematical lumped-parameter model of the hydraulic system of the universal hosed concrete pump is based on its decomposition into individual structural elements and a detailed account of variables of the working fluid, which ensures a more precise assessment of the output parameters of the concrete pump. The mathematical model allows determining static and dynamic characteristics of the entire system and its individual components, studying the parameters, and setting new rational parameters.

Keywords: universal hosed concrete pump, hydraulic diagram, mathematical model, high-torque hydraulic motor, working fluid.

References

1. Kuleshkov, J. V., Chernovol, M. I., Bevez, O. V., Titov, Y. A. (2009). Gear pumps with asymmetrychnoy lines zatseplenyya gears. Theory, Constructions and calculation. Kirovograd «CODE», 257.
2. Sveshnikov, V. K. (1995). Machine hydraulic drives: a handbook. Moscow: Engineering, 448.
3. Basta, T. M. (1971). Engineering hydraulics. Moscow: Mechanical Engineering, 672.
4. Popov, D. N. (1987). Dynamics and regulation of hydraulic and pneumatic systems: a textbook for high schools. 2nd edition. Moscow: Mechanical engineering, 464.
5. Strutynsky, V. B. (2001). Mathematical modeling of processes and systems mechanics. Exactly: ZHITI, 612.
6. Lurie, Z. Ya., Chekmasova, I. A. (2002). Dynamics throttle hydraulic unit with flow control valve, throttle, and hydraulic motor load linear motion. News NTU «KhPI», 9 (12), 129–135.
7. Lurye, Z. Ya., Lischenko, I. G. (2004). Optimal design of high-torque motor and evaluation of the dynamic properties of the hydraulic system on its base. Promyslova gidravlika i pneumatics, 1 (3), 30–34.
8. Lurie, Z. Ya., Avrunin, G. A., Chernyak, A. I., Ivanitskaya, E. P. (1998). The dynamics of the hydraulic drive load inertia based on the high-torque motor. Engineering Bulletin, 8, 7–10.
9. Krasowski, E., Daszchenko, A., Glinski, J. (2010). Hydraulika: Maszyny hydraulicznu. Lublin :Polska Akademia Nauk Oddzial w Lublinie, 385.
10. Andrenko, P., Lebedev, A. (2014). Labyrinth screw pump theory. MOTROL: Commission of motorization and energetics in agriculture: Polish Academy of sciences, Lublin, Rzeszow, 16 (6), 35–42.
11. Ryzhakov, A., Nikolenko, I., Dreszer, K. (2009). Selektion of discretely adjustable pump parameters for hydraulic drives of mobile equipment. TEKA Kom. Mot. Energ. Roln, OL.PAN, IX, 267–276.
12. Henikl, J., Kemmetmüller, W., Bader, M., Kugi, A. (2014). Automation and Control Institute. Vienna University of Technology, Vienna, Austria.
13. Panchenko, A. I., Voloshin, A. A. (2011). Mathematical model of hydraulic drive rotary motion. Pratsi Tavriyskogo sovereign Agrotechnological University, 1 (1), 10–21.
14. Panchenko, A. I., Voloshin, A. A. (2015). Study dynamics hydryavlycheskoy Cistemy pump-valve-hydrospanner. Proceedings Tauride Agrotechnological State University, 15 (3), 66–79.
15. Emeljanova, I. A., Anishchenko, A. I., Melencov, N. A., Gordienko, A. T. (2013). Small-sized equipment for transportation mixture of concrete and gunitе-perform works. Scientific journals «Herald MSHU.» Scientific journal of technical, 5, 87–95.
16. Emeljanova, I. A., Onishchenko, A. I., Shevchenko, V. Y., Melencov, N. A. (2013). Universal small-sized equipment for conditions repair and reconstruction of existing buildings and structures for various purposes. Scientific - Production periodical journal «Science in a central Russia», 4, 5–13.
17. Emeljanova, I., Zadorozhny, A., Legeyda, D., Melencov, N. (2014). Definition Rational Gate Frame Size Distribution Unit Double Piston Concrete Pump with Hydraulic Drive. Plenary Session VIII International Conference «Heavy machinery – HM», 9–13.
18. Henikl, J., Kemmetmüller, W., Kugi, A. (2016). Estimation and control of the tool center point of a mobile concrete pump. Automation in Construction, 61, 112–123.
19. Emeljanova, I. A., Chayka, D. O. (2015). Universal hose concrete pump new constructive solutions. Proceedings of the International Scientific – Technical Conference «Interstroyemh – 2015», 81–85.
20. Trofimov, V. A., Yahno, O. M. et. al. (2009). Working fluid hydraulic drive systems: Proc. Benefit, NTU «KPI», 184.
21. Gubarev, A. P. et. al. (2009). Effect of temperature conditions of many leading cyclic volume hydraulic systems for energy consumption. Vestnik NTU «KPI», 59, 216–219.
22. Strutynsky, V. B., Tihenko, V. M. (2009). Stochastic processes in hydrodrives tools. Odessa: Astoprynt, 456.
23. Yevtushenko, A. A., Kolisnichenko, E. V., Sapozhnikov, S. V. (2004). Turbomachines for pumping gas-liquid mixtures. News Sumdu, 13 (72), 45–49.
24. Lurie, Z. Ya., Fedorenko, I. M. (2012). Workflow study mechatronic hydroelectric metallurgical equipment lubrication systems, taking into account the characteristics of the two-phase liquid. MOTROL, 12, 10–25.
25. Prokofiev, V. N., Luzanova, I. A. et. al. (1968). Experimental study of the elastic properties of the two-phase actuating fluid displacement type. Proceedings of the universities, Mechanical Engineering, 2, 87–93.
26. Kononenko, A. P. (2011). Three-dimensional hydraulic machines hydraulic. Donetsk: SHEE «National Technical University», 292.
27. Basta, T. M., Zaichenko, I. Z., Ermakov, V. V. et. al.; Bash-ta, T. M. (Ed.) (1968). Three-dimensional hydraulic actuators, M: Mechanical engineering, 628.
28. Korzeneniowski, R., Pluta, J. (2005). Identyfikacja sil tarcia w serwonapedzie elektropneumatycznym. HYDRAULIC AND PNEUMATICS '2005: international scientific-technical conference. Wroclaw, 280–292.
29. Andrenko, P. M. (2014). Hydraulic devices mechatronic systems: teach. guidances. Kharkiv: Publishing Center of NTU «KhPI», 188.
30. Danilov, Y. A., Kirillov, Yu., Kolpakov, Y. G. (1990). Hardware volume hydraulic drives: Workflows and data. Moscow: Mechanical engineering, 272.

THE METHOD OF CALCULATING THE VELOCITY FIELD AND SHEAR STRESSES IN INCOMPRESSIBLE FLUID (p. 43-48)

Vitaliy Budarin

The velocity field calculation method is based on the use of two special cases of the Newtonian fluid motion equations, not including the Navier-Stokes equations. Two shear stress calculation methods are considered. The first method is the differentiation of the velocity field equation, and the second one requires the solution of the first-order differential equation. The second method provides the distribution of shear stresses for any continuous medium, including the Newtonian fluid.

Calculation equations for a laminar flow in a round pipe are found. It is shown that a parabolic velocity distribution along the radius is a special case of a more general equation.

The factors affecting the shear stresses for the three flow models are found. Stresses are determined by the linear velocity gradients in the laminar flow. In the 3D vortex, they can be found by various equations, which include vorticity. Total stresses for the averaged turbulent flow are calculated by summing the previously found stresses.

The equations of the method are incomplete and may be used for the accurate solution of simple problems.

Keywords: incompressible fluid, Poiseuille, flow regimes, velocity gradient, vorticity.

References

- Loitsyansky, L. G. (1978). *Mechanics of Liquid and Gas*. Moscow: Science, 736.
- Munson, B. R. (2009). *Fundamentals of fluid mechanics*. Wiley, 730.
- Pijush, K. K., Cohen, I. M., David, R. D. (2012). *Fluid mechanics*. Elsevier, 891.
- Shterenliht, D. V. (1991). *Hydraulics: Training*. Moscow: Energoatomizdat, 351.
- Ingel, L. H. (2008). On the theory of rising convective jets. *Russian Academy of Sciences. The physics of the atmosphere and ocean*, 44 (2), 178–185.
- Kumar, J., Umavathi, J., Prema, H. (2011). Free convection of Walter's fluid flow in a vertical double-passage wavy channel with heat source. *International Journal of Engineering, Science and Technology*, 3 (1). doi: 10.4314/ijest.v3i1.67643
- Beskachko, V. P., Bolotnikov, N. A., Tsatsin, P. O. (2006). MHD effects in experiments with the rotating disk in the presence of an axial magnetic field. *YUUGU. Mathematics. Mechanics. Physics*, 7, 187–191.
- Goldshhtik, M. A. (1981). *Vortex flows*. Novosibirsk: Nauka, 366.
- Lubomirski, N. V., Zaitsev, O. N. (2008). Method of calculation of the velocity field interacting rotating flows. *Construction and technogenic safety*, 26, 94–97.
- Watin, N. I., Girgidov, A. A., Strelets, K. I. (2011). Numerical simulation of three-dimensional velocity field in the cyclone. *Journal of Civil Engineering*, 5, 5–9.
- Hachicha, A. A., Rodriguez, I., Castro, J., Oliva, A. (2013). Numerical simulation of wind flow around a parabolic trough solar collector. *Applied Energy*, 107, 426–437. doi: 10.1016/j.apenergy.2013.02.014
- Smith, B. W., Chase, J. G., Nokes, R. I., Shaw, G. M., David, T. (2003). Velocity profile method for time varying resistance in minimal cardiovascular system models. *Physics in Medicine and Biology*, 48 (20), 3375–3387. doi: 10.1088/0031-9155/48/20/008
- Ferziger, J. H. (1998). *Numerical methods for engineering application*. New York: Wiley, 400.
- Smith, B. W., Chase, J. G., Nokes, R. I. (2003). Velocity profile method for time varying resistance in minimal cardiovascular system models. *Physics in Medicine and Biology*, 48 (20), 3375–3387.
- Belyaev, N. M. (1987). *Thermodynamics*. Kyiv: VSch, 344.
- Frick, P. G. (1998). *Turbulence: models and approaches*. Perm, PSTU, 108.
- Mathieu, J. (2000). *An Introduction to Turbulent Flow*. Cambridge University Press, 374.
- Isachenko, V. P. (1981). *Heat transfer*. Moscow: Energy, 417.
- Budarin, V. A. (2015). Transformation of the equation of motion in stresses for an incompressible fluid. *Eastern-European Journal of Enterprise Technologies*, 2/7 (74), 38–41. doi: 10.15587/1729-4061.2015.39886

INVESTIGATION OF THE PROCESS OF THE STABILIZATION OF THE RIGID BODY CARRIER OF THE ROTATIONAL AXIS OF THE PENDULUM AUTOBALANCER (p. 49-63)

Vladimir Pirogov

The paper investigates the conditional stability of the basic steady motions of the spatial model of an isolated system, consisting of a rotating lifting body, a particle, creating its static unbalance and two identical mathematical pendulums, mounted on a longitudinal axis of the lifting body and mov-

ing in the plane of the static unbalance, the relative motion of which is hindered by the viscous resistance forces. It is found that in the case where unbalance is present and pendulums can correct it with a certain margin, there is one basic motion. In the absence of unbalance, there is a one-parameter family of basic motions. In the case of maximum unbalance, which can be corrected by pendulums, there is one basic motion, but it generates a pseudo family of basic motions. Also, it is revealed that some basic motions, if isolated, or a family or a pseudo family of basic motions is conditionally asymptotically stable. In the absence of unbalance, the presence of a single zero root of the characteristic equation does not affect the stability of a one-parameter family of basic motions and is responsible for the transition from one steady motion of a family to another. In the case of maximum unbalance, the presence of a single zero root of the characteristic equation does not affect the stability of the basic motion and is responsible for the transition from one steady motion of a pseudo family to another. Transition processes are oscillatory-damped.

Keywords: lifting body, pendulums, motion stability, spacecraft, passive autobalancer, damper.

References

- Artjuhina, Ju. P., Kargu, L. I., Simaev, V. L. (1979). *Control systems of spacecraft stabilized rotation*. Moscow: Nauka, 296.
- Popov, V. I. (1986). *Systems of orientation and stabilization of spacecraft*. Moscow: Mashinostroenie, 184.
- Huges, P. C. (2004). *Spacecraft Attitude Dynamics*. New York, Dover Publications, 585.
- Zinchenko, O. N. (2011). Small optical satellites DZZ. Available at: <http://www.racurs.ru/?page=710>
- Ovchinnikov, M. Y. (2007). Small this world. *Kompyuterra*, 15, 37–43.
- Small Satellites: A Revolution in Space Science (2014). Available at: <http://www.kiss.caltech.edu/study/smallsat/KISS-SmallSat-FinalReport.pdf>
- Small spacecraft information provision (2010). Moscow: Radiotekhnika, 320.
- Makridenko, L. A., Volkov, S. N., Hodnenko, V. P., et al. (2010). Conceptual questions of creation and application of small satellites. *Questions of Electromechanics. Proceedings VNIEM*, 114 (1), 15–26.
- Gidlund, S. (2005). Design Study for a Formation-Flying Nanosatellite Cluster. Available at: <http://epubl.ltu.se/1402-1617/2005/147/LTU-EX-05147-SE.pdf>
- Sandau, R., Röser, H.-P., Valenzuela, A. (2008). *Small Satellites for Earth Observation: Selected Contributions*. Springer, 406. doi: 10.1007/978-1-4020-6943-7
- Small Spacecraft Technology State of the Art (2014). Available at: https://www.nasa.gov/directorates/spacetech/small_spacecraft/index.html
- Kargu, L. I. (1980). *Systems angular stabilization of spacecraft*. Moscow: Mashinostroenie, 172.
- Gritsenko, A. A. (2001). Using stabilized rotation of small satellites in the satellite communication systems for GEO and HEO orbits. Available at: http://www.spacecenter.ru/Resurses/IEEE_2001_2.doc
- Fonseca, I. M., Santos, M. C. (2002). SACI-2 Attitude Control Subsystem. *INPE*, 3, 197–209.
- Hubert, C., Swanson, D. (2001). Surface Tension Lockup in the IMAGE Nutation Damper – Anomaly and Recovery. Available at: http://image.gsfc.nasa.gov/publication/document/2001_hubert_swanson.pdf

16. Reuter, G. S., Thomson, W. T. (1966). Rotational movement of passive spacecraft. Problems of the orientation of satellites. Moscow: Nauka, 336–350.
17. Likins, P. W. (1966). Effects of energy dissipation on the free body motions of spacecraft, 70.
18. Mirer, S. A., Sarychev, V. A. (1997). Optimal Parameters of a Spin-Stabilized Satellite with a Pendulum-Like Damper. *Cosmic Research*, 35 (6), 609–615.
19. Cloutier, G. J. (1969). Nutation damper instability on spin-stabilized spacecraft. *AIAA Journal*, 7 (11), 2110–2115. doi: 10.2514/3.5565
20. Jr., J. E. C., Thompson, J. A. (1980). Nutation Dampers vs Precession Dampers for Asymmetric Spacecraft. *Journal of Guidance, Control, and Dynamics*, 3 (1), 22–28. doi: 10.2514/6.1978-1401
21. Kane, T. R., Likins, P. W., Levinson, D. A. (1983). *Spacecraft Dynamics*. McGraw-Hill, New York, 436.
22. Thompson, J. M. T. (1985). *Instabilities and Catastrophes in Science and Engineering*. Moscow: Mir, 254.
23. Janssens, F. L., van der Ha, J. C. (2011). On the stability of spinning satellites. *Acta Astronautica*, 68 (7-8), 778–789. doi: 10.1016/j.actaastro.2010.08.008
24. Filimonikhin, G. B., Pirogov, V. V., Filimonikhina, I. I. (2007). Attitude stabilization of the rotational axis of a carrying body by pendulum dampers. *International Applied Mechanics*, 43 (10), 1167–1173. doi: 10.1007/s10778-007-0117-4
25. Filimonikhin, G. B., Pirogov, V. V., Filimonikhina, I. I. (2008). Using passive autobalancing as the angle of nutation dampers rapidly rotating satellites. System design and analysis of aerospace technology: Proceedings. Publishing Dnepropetrovsk National University, VIII, 105115.
26. Filimonikhin, G. B., Pirogov, V. V., Filimonikhina, I. I. (2013). Research of process of the elimination autobalancers of large nutation angles. *Eastern-European Journal of Enterprise Technologies*, 6/7(66), 34–38. Available at: <http://journals.uran.ua/eejet/article/view/18705/17057>
27. Filimonikhin, G. B., Filimonikhina, I. I., Pirogov, V. V. (2014). Stability of Steady-State Motion of an Isolated System Consisting of a Rotating Body and Two Pendulums. *International Applied Mechanics*, 50 (4), 459–469. doi: 10.1007/s10778-014-0651-9
28. Filimonikhin, G. B., Pirogov, V. V. (2005). Stabilization of the Rotation Axis of a Solid by Coupled Perfectly Rigid Bodies. *International Applied Mechanics*, 41 (8), 937–943. doi: 10.1007/s10778-005-0164-7
29. Pirogov, V. V. (2015). Stability investigation of the steady motions of an isolated system, carrying out plane motion. *Eastern-European Journal of Enterprise Technologies*, 5/7 (77), 9–20. doi: 10.15587/1729-4061.2015.49269
30. Filimonikhina, I. I., Filimonikhin, G. B. (2007). Conditions for balancing a rotating body in an isolated system with automatic balancers. *International Applied Mechanics*, 43 (11), 1276–1282. doi: 10.1007/s10778-007-0132-5

IDENTIFICATION OF A MIXTURE OF GRAIN PARTICLE VELOCITY THROUGH THE HOLES OF THE VIBRATING SIEVES GRAIN SEPARATORS (p. 63-69)

**Leonid Tishchenko, Sergei Kharchenko,
Farida Kharchenko, Vadym Bredykhin, Oleg Tsurkan**

The research of the process of sieving of grain mixes in vibrating sieves of grain separators is given. The generalization of

theoretical research allowed obtaining a mathematical model of grain mix dynamics in vibrating sieves, which is based on hydroanalogy and improved by the introduction of bubble fluidized medium. This model is the equation for determining the grain mix velocity components, taking into account the structural and kinematic parameters of sieves and properties of the mix. This identified the possibilities of intensifying the mix sieving in vibrating sieves through the use of epicycloid-shaped holes. The model is tested on the example of the pea mix sieving, resulting in the constructed velocity field and volume efficiency variation patterns in the series round-hole sieves and the developed five-petal epicycloid-shaped hole sieves. It was found that an important parameter in the dynamic processes and the grain mix sieving process is the velocity of its passage through the holes. To increase the modeling accuracy, the technique of identification that was to determine the flow rate of granular medium through the sieve holes was developed. The measurements of the velocity of the mix passage through the sieve holes were carried out. To do this, the flow of the sieved grain mix was determined and attributed to the area of the sieve holes. The load, structural and kinematic parameters of the sieve, including the type of holes was varied. The studies found a significant increase in the velocity of passage of the grain mix through epicycloid-shaped holes of the developed sieves in comparison with series round-hole sieves, which confirms their efficiency. Using these methods provides the real variation ranges of the velocity of passage of the grain mix of different crops through any type of sieve holes.

Keywords: sieving process, efficiency, velocity field, holes, fluidized medium, pea mix, hydroanalogy

References

1. Tishchenko, L., Kharchenko, S., Kharchenko, F., Vasilenko, O., Puha, V. (2014). Separaciya gorohu ta nutu. *The Ukrainian Farmer*, 4, 94–95.
2. Blehman, I. I. (1994). *Vibracionnaya mexanika*. Moscow: Fizmatlit, 400.
3. Gortinskij, V. V. (1980). *Processy separirovaniya na zernopererabatyvayushhix predpriyatiyax*. Moscow: Kolos, 304.
4. Zaika, P. M. (1977). *Dinamika vibracionnyx zernoochistitelnyx mashin*. Moscow: Mashinostroenie, 278.
5. Minyajlo, A. V. (1973). *Issledovanie processa separirovaniya semyan na ploskix gorizontalnyx vibroreshetax*. Kharkiv, 165.
6. Tishchenko, L. N., Ol'shanskii, V. P., Ol'shanskii, S. V. (2011). On velocity profiles of an inhomogeneous vibrofluidized grain bed on a shaker. *Journal of Engineering Physics and Thermophysics*, 84 (3), 509–514. doi: 10.1007/s10891-011-0498-4
7. Tishchenko, L. N., Piven, M. V., Kharchenko, S. A. (2010). Matematicheskaya model protsessa segregatsii zernovyih smesey pri separirovanii ploskimi vibratsionnyimi reshetami. *Mehanizatsiya silskogospodarskogo virobnitstva*, 103, 12–20.
8. Tishchenko, L. N., Mazorenko, D. I., Piven, M. O., Kharchenko, S. A., Bredihin, V. V., Mandryka, A. V. (2010). Modelirovanie processov zernovykh separatorov. Kharkiv: «Miskdruk», 360.
9. Kharchenko, S. (2015). Modeling the dynamics of the grain mixtures with the screening on cylindrical vibrating sieve separators. *TEKA. Commission of motorization and energetics in agriculture*, 15 (3), 87–93.
10. Paolotti, D., Cattuto, C., Marini, U., Marconi, B., Puglisi, A. (2002). Dynamical properties of vibrofluidized granular mixture, 1, 25.
11. Pascoe, R. D., Fitzpatrick, R., Garratt, J. R. (2015). Prediction of automated sorter performance utilising a Monte Carlo simulation of feed characteristics. *Minerals Engineering*, 72, 101–107. doi: 10.1016/j.mineng.2014.12.026

12. Pelevin, A. E. (2011). Probability of particles passing through the sieve openings and separation process in vibrational screening devices. *Izvestiya vuzov, Min J* (1), 119–129.
13. Boac, J. M., Ambrose, R. P. K., Casada, M. E., Maghirang, R. G., Maier, D. E. (2014). Applications of Discrete Element Method in Modeling of Grain Postharvest Operations. *Food Engineering Reviews*, 6 (4), 128–149. doi: 10.1007/s12393-014-9090-y
14. Ma, X.-D., Zhang, Y.-B., Liu, Y., Zheng, X.-W. (2016). Simulation of grain segregation under horizontal rotational oscillations. *Granular Matter*, 18 (1), 1–6. doi: 10.1007/s10035-015-0598-5
15. Tishchenko, L. N., Kharchenko, S. A., Kharchenko, F. M. (2014). Ispolzovanie gidrodinamicheskoy analogii s primeneniem uravnenij Nave-Stoksa dlya resheniya zadach ochistki vozdušnogo potoka v pyleosadochnyx kamerax zernoochistitelnyx separatorov. *Inzheneriya prirodokoristuvannya*, 1, 56–64.
16. Slipchenko, M. V. (2014). Issledovanie ochistki zernovykh smesey pri shode s tarelchatogo razbrasyvatel'ya pnevmosepariruyushchego ustroystva vibrotsentrobezhnogo aparatora. *Motrol. Commission and Energetacs in Agriculture*, 16 (7), 89–91.
17. Rahou, F., Tilmatine, A., Bilici, M., Dascalescu, L. (2013). Numerical simulation of the continuous operation of a tribo-aero-electrostatic separator for mixed granular solids. *Journal of Electrostatics*, 71 (5), 867–874. doi: 10.1016/j.elstat.2013.06.004
18. Akhmadiev, F. G., Gizzatov, R. F. (2013). Separation Processes of Granular Materials by Sizes at the Sieve Classifiers. *Journal of Chemistry and Chemical Engineering*, 1 (7), 56–63.
19. Ravshanov, N., Palvanov, B., Islamov, Y. (2013). Mathematical Model of suspension Filtration and Its Analytical Solution. *European researcher*, 58 (9), 2185–2192.
20. Panasiewicz, M., Sobczak, P., Mazur, J., Zawislak, K., Andrejko, D. (2012). The technique and analysis of the process of separation and cleaning grain materials. *Journal of Food Engineering*, 109 (3), 603–608. doi: 10.1016/j.jfoodeng.2011.10.010
21. Tishchenko, L., Kharchenko, S. (2013). K primeniyu metodov mexaniki sploshnyx sred dlya opisaniya dvizheniya zernovykh smesey na vibroreshetax. *MOTROL. Commission of Motorization and Energetics in Agriculture*, 15 (7), 94–99.
22. Kharchenko, S. A. (2013). Postroenie reshenij uravnenij dinamiki zernovykh smesey na ploskix vibroreshetax. *Konstruyuvannya, virobniectvo ta ekspluatatsiya s.g. mashin*, 43, Part II, 287–292.
23. Kharchenko, S. A., Tischenko, L. N. (2013). Algoritm rascheta effektivnogo koeffitsienta dinamicheskoy vyazkosti puzyirkovoy psevdozhidkosti, modeliruyushchey separiruemuyu zernovuyu smes. *Vibratsiyi v tehniitsi ta tehnologiyah*, 2 (70), 64–72.
24. Yampilov, S. S. (2004). *Texnologicheskie i texnicheskie resheniya problemy ochistki zerna reshetami*. Ulan-Ude, 165.
25. Gaur, P. M., Tripathi, S., Gowda, C. L. L., Ranga Rao, G. V., Sharma, H. C., Pande, S., Sharma, M. (2010). *Chickpea Seed Production Manual*. International Crops Research Institute for the Semi-Arid Tropics, 28.

IDENTIFICATION OF A MIXTURE OF GRAIN PARTICLE VELOCITY THROUGH THE HOLES OF THE VIBRATING SIEVES GRAIN SEPARATORS (p. 70-78)

Vasif Talibov Mamedov, Seyfulla Ramiz oglu Gurbanov

The variational Lagrange principle and the Kantorovich method are applied in calculating the downhole packer seal-

ing process with the influence of low rubber compressibility. The dependence between the sealing ratio and the stress ratio on the geometric parameters of the sealing element of the downhole packer is determined. It is found that the sealing effect of end faces leads to a significant difference in the stress-strain state of the packer seal assembly from uniaxial compression. Rubber is an elastic material in the entire load range. However, with increasing strain there is increasing deviation from the linear relationship between stress and strain, despite the fact that rubber remains an elastic material, and the relationship between stress and strain becomes nonlinear.

The incompressibility should be considered as the property of rubber to maintain a constant volume under any strain. Volume decrease under higher strain is associated with the change in the physical state of rubber due to crystallization. The compressibility effect may become noticeable only in special structures, in downhole packers, so in this case the problem is divided into two: 1) the solution of the problem in the case of an incompressible material; 2) the solution of the problem, corresponding only to the three-dimensional compression, when the strain $E_{ij} = \text{const}$, if loads are large enough and the rubber compressibility has to be taken into account. It is shown that strain in many designs of downhole packers should be written based on precisely this dependence, because the lateral strain in the seals appears constrained so that a large volume of rubber is under uniform compression. In this case, the assumption of absolute incompressibility of rubber can lead to a significant overestimation of the seal rigidity.

Keywords: low-compressibility rubber, downhole packer, Lagrange principle, toughening factor, normal and shear stresses.

References

1. Chervinskij, V. P., Gal'chenko, A. S., Mel'nik, N. V. (2010). About perfection of details compaction of underground downhole equipment complexes. *Eastern-European Journal of Enterprise Technology*, 4/6 (46), 28–30. Available at: <http://journals.urau.ru/eejet/article/view/2995/2798>
2. Polonskij, V. L., Tjurin, A. P. (2012). Osobennosti raboty rezinovykh uplotnenij – pakerov. *Sovremennoe mashinostroenie. nauka i obrazovanie*, 2, 592–597.
3. Uplotheniya i uplotnitel'naja tehnika: Spravochnik. 2nd edition (1994). Moscow: Mashinostroenie, 445.
4. Poturayev, V. N. (1966). Rubber and rubber-metallic machine components. Moscow: "Machinebuilding".
5. Kurenov, M. V., Eliseev, D. V. (2012). Osobennosti ispol'zovaniya razbuhajushhih pakerov dlja razobshheniya gorizonta'nykh uchastkov skvazhin na shel'fe Kaspijskogo morja. *Vestnik AGTU*, 2 (52), 69–71.
6. Avanesov, V. A., Moskaleva, E. M. (2008). Pakery dlja provedeniya tehnologicheskikh operacij i jekspluatatsii skvazhin. *UGTU Uhta*, 91.
7. Han, C., Zhang, J. (2013). Study on well hard shut-in experiment based on similarity principle and erosion of ram rubber. *Engineering Failure Analysis*, 32, 202–208. doi: 10.1016/j.engfailanal.2013.03.016
8. Zhai, C., Hao, Z., Lin, B. (2011). Research on a New Composite Sealing Material of Gas Drainage Borehole and Its Sealing Performance. *Procedia Engineering*, 26, 1406–1416. doi: 10.1016/j.proeng.2011.11.2318
9. Chandrasekaran, V. C. (2010). Rubber Seals for Oil Field Service. *Rubber Seals for Fluid and Hydraulic Systems*, 45–55. doi: 10.1016/b978-0-8155-2075-7.10005-x

10. Liu, Q., Cheng, Y., Yuan, L., Fang, Y., Shi, D., Kong, S. (2014). A new effective method and new materials for high sealing performance of cross-measure CMM drainage boreholes. *Journal of Natural Gas Science and Engineering*, 21, 805–813. doi: 10.1016/j.jngse.2014.10.023
11. Parker's rubber materials extend seal life in harsh environments (2015). *Sealing Technology*, 2015 (7), 2. doi: 10.1016/s1350-4789(15)30185-9
12. Cybin, A. A., Cybin, S. A. (2008). Kreplenie skvazhin i razobshhenie plastov gidravlicheskimii pakerami s metallicheskimii uplotnitel'nymi jelementami. *Nauchno-tehnicheskij zhurnal «Inzhener-neftjanik»*, 4, 21–23.
13. Al-Hiddabi, S. A., Pervez, T., Qamar, S. Z., Al-Jahwari, F. K., Marketz, F., Al-Houqani, S., van de Velden, M. (2015). Analytical model of elastomer seal performance in oil wells. *Applied Mathematical Modelling*, 39 (10-11), 2836–2848. doi: 10.1016/j.apm.2014.10.028
14. Zeng, D., Yang, X., Zhu, D., Zhang, Z., Cao, D., Chong, X., Shi, T. (2012). Corrosion Property Testing of AFLAS Rubber under The Simulation modes of High Acid Gas Wells. *Energy Procedia*, 16, 822–827. doi: 10.1016/j.egypro.2012.01.132
15. Yamabe, J., Nishimura, S. (2012). Hydrogen-induced degradation of rubber seals. *Gaseous Hydrogen Embrittlement of Materials in Energy Technologies*, 769–816. doi: 10.1533/9780857093899.3.769
16. Guan, H., Yang, F., Wang, Q. (2011). Study on evaluation index system of rubber materials for sealing. *Materials & Design*, 32 (4), 2404–2412. doi: 10.1016/j.matdes.2010.12.030
17. Rubber and PEEK polymer-based composite developed for sealing applications (2011). *Sealing Technology*, 2011 (12), 2–3. doi: 10.1016/s1350-4789(11)70407-x
18. Aksenov, A., Kon'shin, V. (2006). Analiz zadach vzaimodejstvija «zhidkost' – konstrukcija» s ispol'zovaniem programmnyh kompleksov ABAQUS i FlowVision. *SAPR i grafika*, 9, 20–24.
19. Kropotin, O. V. (2012). Metodika prognozirovanija nadezhnosti i resursa podvizhnyh germetizirujushhijh ustrojstv s uchetom formoizmenenija jelementov v processe frikcionnogo vzaimodejstvija. *Izvestija Samarskogo nauchnogo centra RAN*, 14 (4 (5)), 1253–1256.
20. Panchenko, A. Ju., Shil'ko, E. V., Astafurov, S. V., Korostelev, S. Ju., Psah'e, S. G. (2008). Razvitie formalizma metoda chastic dlja rascheta uslovij na granice razdela tverdogo tela s zhidkoj sredoj. *Izvestija Tomskogo politehnicheskogo universiteta*, 313 (2), 85–90.
21. Kropotin, O. V., Mashkov, Ju. K., Kurguzova, O. A., Shil'ko, S. V. (2013). Optimizacija konstrukcii germetizirujushhego ustrojstva s ispol'zovaniem metoda issledovanija prostranstva parametrov. *Omskij nauchnyj Vestnik*, 3 (123), 101–104.
22. Koltunov, M. A., Trojanovskij, I. E. (1977). Geometricheskie nelinejnaja zadacha teorii vjazko uprugosti. *Mechanika jelastomerov. Vol. 1. Krasnodar. izv. Kubin. Gos. Un-ta*, 36–46.
23. Kvitka, A. L., Voroshko, P. P., Bobrickaja, S. D. (1977). *Naprjazhenno deformirovanoe sostojanie tel vrashhenija*. Kyiv, Naukova dumka, 208.
24. Sniegs, M. I. (1974). Reshenie nekotoryh osesimmetrichnyh zadach teorii uprugosti dlja neszhimaemogo materiala metodom konechnykh jelementov. *Vopr. Dinamiki i prochnosti*, 30, 116–119.
25. Chernyh, K. F., Shubina, I. M. (1977). *Zakony uprugosti dlja izotronnyh nezhimaemykh materialov V kn: mehanika jelastomerov. Vol. 1. Krasnodar. izv. Kubin. Gos. Un-ta*, 54–64.
26. Glud, S. (1970). *Variacionnye metody v zadachah o sobstvennykh znachenijah*. Moscow: Mir, 328.
27. Il'jushin, A. A., Pobed'ja, B. E. (1970). *Osnovy matematicheskij teorii termovjazkoj uprugosti*. Moscow: Nauka, 280.
28. Moskvitin, V. V. (1972). *Soprotivlenie vjazko uprugijh materialov*. Moscow: Nauka, 263.
29. Reissner, F. (1961). On some variational theorems in elasticity problems of continuum mechanics. *Philadelphia*, 354.
30. Jeglajs, V. O. (1980). *Algoritm intuitivnogo poiska dlja optimizacii slozhnyh sistem. Voprosy Dinamiki i prochnosti*, 28–33.
31. Pavlovskij, A. A., Gluhih, S. A. (1977). *Primenenie variacionnogo principa rejsenera v zadache o kinematicheskom vzbuzhdenii rezinometallicheskogo amortizatora. Voprosy Dinamiki i prochnosti*, 35, 124–130.
32. Mixlin, S. G. (1970). *Variational methods in mathematical physics*. Moscow: Science.

**RESEARCH OF COMPETITIVENESS
VIBROVOLNOVOY CONVEYOR INFRARED DRYER
FOR POSTHARVEST PROCESSING OF GRAIN
(p. 79-85)**

**Igor Palamarchuk, Oleg Tsurkan,
Vladislav Palamarchuk, Sergei Kharchenko**

The expediency and necessity of competitiveness evaluation of new equipment for manufacturers and users are proved. This will help consumers in selecting the right product and encourage manufacturers to produce energy-efficient equipment.

The method and example of the technical level evaluation of the vibrowave infrared conveyor dryer for grain drying in the post-harvest processing by two types of general indicators are presented.

Two types of general indicators are identified according to the criteria of performance, efficiency and steel intensity of the developed machine and grain dryers of the same class.

The research revealed that the developed vibrowave infrared conveyor dryer is competitive and outperforms existing dryers for two types of general indicators. This result is achieved through the use and implementation of continuous processing mode with the minimum power and materials consumption with ensuring the layer-by-layer grain processing uniformity.

The technical level evaluation of the developed machine by several criteria makes it objective and assists consumers in making the right decision when choosing new equipment to improve production.

Keywords: post-harvest processing, infrared dryer, vibrating dryer, grain drying, competitiveness evaluation, general indicators.

References

1. Filosofova, T. G., Byikov, V. A. (2008). *Konkurentsija. Innovatsii. Konkurentosposobnost*. Moscow: YuNITI-DANA, 295.
2. Porter, M. E. (2005). *Konkurentsija*. Moscow: Vilyams, 608.
3. Blonska, V. I., Depa, N. T. (2010). Porivnialna kharakterystyka metodiv otsinky konkurentosposobnosti produktsii. *Naukovyi visnyk NLTU Ukrainy*, 20.15, 115–120.

4. Treshchov, M. M. (2009). Metody otsiniuvannya konkurentospromozhnosti produktsii. *Ekonomichnyi prostir*, 23/1, 118–126.
5. Solomennikova, E. A. (2010). Problemyi issledovaniya konkurentospozobnosti predpriyatiya. *Vestnik NGU*, 10 (4), 116–123.
6. Hunko, I. V., Spirin, A. V., Kholodiuk, O. V. (2006). Nadiinist system ta obgruntuvannya inzhenernykh rishen. *Vinnytsia: VDAU*, 76.
7. Spirin, A. V., Ivanov, M. I., Podolianyn, I. M., Kovalova, I. M. (2007). Otsinka na konkurentospromozhnist doslidnoho zrazka hychkozbyralnoi mashyny BM6-AH z kopiiuvalnym hidropyvodom hychkozrizuvalnoho aparata. *Promyslova hidravlika i pnevmatyka*, 2 (16), 104–110.
8. Spirin, A. V., Solona, O. V., Kylymnyk, V. I. (2005). Otsinka na konkurentozdatnist vibratsiinoho mlyna. *Vibratsii v tekhnitsi i tekhnolohiiakh*, 2 (40), 90–92.
9. Palamarchuk, I. P., Tsurkan, O. V., Palamarchuk, V. I. (2015). Obhruntuvannya konstruktivno-tekhnolohichnoi skhemy infrachervonoj vibrokhylovoi konveiernoi susharky dlia pisliazbyralnoi obrobky sypkoi silskohospodarskoi produktsii. *Zbirnyk naukovykh prats Vinnytskoho natsionalnoho ahrarnoho universytetu. Serii: Tekhnichni nauky*, 1 (1 (89)), 117–123.
10. Bandura, V. M., Tsurkan, O. V., Palamarchuk, V. I. (2015). Eksperymentalnoe yssledovanye tekhnolohycheskykh parametrov protsessa ynfrakrasnoi sushky dvyzhushchehosia shara siria maslychnikh kultur. *MOTROL. Commission of Motorization and Energetics in Agriculture*, 17 (4), 211–214.
11. Palamarchuk, I. P., Tsurkan, O. V., Palamarchuk, V. I. (2015). The analysis of theoretical and experimental research results of infrared vibrowave conveyer dryer main parameters. *TEKA. Commission of Motorization and Power Industry in Agriculture*, 15 (4), 314–323.