

ABSTRACT AND REFERENCES

ECOLOGY

DOI: 10.15587/1729-4061.2018.123979

DEVELOPMENT OF EFFECTIVE TECHNIQUE FOR THE DISPOSAL OF THE PRUNUS ARMENIACA SEED SHELLS

(p. 4-9)

Vita HalyshNational Technical University of Ukraine
"Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-7063-885X>**Iryna Trembus**National Technical University of Ukraine
"Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-6985-4424>**Irina Deykun**National Technical University of Ukraine
"Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-9051-5176>**Alina Ostapenko**National Technical University of Ukraine
"Igor Sikorsky Kyiv Polytechnic Institute", Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-5289-8196>**Alina Nikolaichuk**Chuiko Institute of Surface Chemistry of National Academy of
Sciences of Ukraine, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-9329-7816>**Galina Ilnitska**V. Bakul Institute of Superhard Materials of National Academy of
Sciences of Ukraine, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-5124-1646>

We proposed a new technique for the disposal of solid plant waste in the food industry, specifically solid shell of *Prunus armeniaca* seeds, by oxidative treatment with a hydrogen peroxide solution in an acetic acid medium, which makes it possible to obtain effective sorbent materials. We investigated the effect of oxidant concentration and time of the process on structural and sorption properties of plant sorbents. The experimental-statistical models of the process were obtained by employing a method of mathematical planning based on the mathematical processing of acquired experimental data. The optimal conditions for conducting the process using the generalized Harrington desirability function were determined. It was established that the optimal parameters that make it possible to obtain effective sorbents with the yield, the content of cellulose, lignin, and the efficiency of extracting methylene-blue from an aqueous solution of 50.3 %, 58.2 %, 12.7 % and 91.4 %, respectively, are the concentration of peroxide hydrogen of 9 % and a process time of 120 min. The application of the proposed technology enables efficient disposal of solid plant wastes, and obtaining the sorbents with high sorption characteristics. Such materials could be used in environmental science to solve the problems related to the contamination of water bodies by organic compounds, as well as enterosorbents in medicine and veterinary medicine.

Keywords: shell of *Prunus armeniaca* seeds, oxidative treatment, sorbent, full factorial experiment, optimization.

References

- De Oliveira Barud, H. G., da Silva, R. R., da Silva Barud, H., Ter-cjak, A., Gutierrez, J., Lustri, W. R. et. al. (2016). A multipurpose

natural and renewable polymer in medical applications: Bacterial cellulose. *Carbohydrate Polymers*, 153, 406–420. doi: 10.1016/j.carbpol.2016.07.059

- Ugartondo, V., Mitjans, M., Vinardell, M. (2008). Comparative antioxidant and cytotoxic effects of lignins from different sources. *Bioresource Technology*, 99 (14), 6683–6687. doi: 10.1016/j.biortech.2007.11.038
- Galysh, V., Sevastyanova, O., Kartel, M., Lindström, M. E., Gornikov, Y. (2016). Impact of ferrocyanide salts on the thermo-oxidative degradation of lignocellulosic sorbents. *Journal of Thermal Analysis and Calorimetry*, 128 (2), 1019–1025. doi: 10.1007/s10973-016-5984-7
- Kartel, M., Galysh, V. (2017). New Composite Sorbents for Caesium and Strontium Ions Sorption. *Chemistry Journal of Moldova*, 12 (1), 37–44. doi: 10.19261/cjm.2017.401
- Surovka, D., Pertile, E. (2017). Sorption of Iron, Manganese, and Copper from Aqueous Solution Using Orange Peel: Optimization, Isothermic, Kinetic, and Thermodynamic Studies. *Polish Journal of Environmental Studies*, 26 (2), 795–800. doi: 10.15244/pjoes/60499
- Kasapidou, E., Sossidou, E., Mitlianga, P. (2015). Fruit and Vegetable Co-Products as Functional Feed Ingredients in Farm Animal Nutrition for Improved Product Quality. *Agriculture*, 5 (4), 1020–1034. doi: 10.3390/agriculture5041020
- Sarkar, S., Pal, S., Chanda, S. (2016). Optimization of a Vegetable Waste Composting Process with a Significant Thermophilic Phase. *Procedia Environmental Sciences*, 35, 435–440. doi: 10.1016/j.proenv.2016.07.026
- Šoštarić, T., Petrović, M., Milojković, J., Petrović, J., Stanojević, M., Lačnjevac, Č., Stojanović, M. (2015). Biosorption of methylene blue by waste apricot shells from food industry. *Journal of Engineering & Processing Management*, 7 (1), 107–114. doi: 10.7251/jepmen1507107s
- Ozdemir, I., Şahin, M., Orhan, R., Erdem, M. (2014). Preparation and characterization of activated carbon from grape stalk by zinc chloride activation. *Fuel Processing Technology*, 125, 200–206. doi: 10.1016/j.fuproc.2014.04.002
- Galysh, V. V., Kartel', N. T., Milyutin, V. V., Bakalinskaya, O. N. (2014). Sintez i svoystva lignocellyulozno-neorganicheskikh biosorbentov. *Energotehnologii i resursoberezhenie*, 3, 28–34.
- Conrad, E. K., Nnaemeka, O. J., Chris, A. O. (2015). Adsorption removal of Methylene Blue from aqueous solution using agricultural waste: equilibrium, kinetic and thermodynamic studies. *American Journal of Chemistry and Materials Science*, 2 (3), 14–25.
- Smitha, T., Thirumalisamy, S., Manonmani, S. (2012). Equilibrium and Kinetics Study of Adsorption of Crystal Violet onto the Peel of *Cucumis sativa* Fruit from Aqueous Solution. *E-Journal of Chemistry*, 9 (3), 1091–1101. doi: 10.1155/2012/457632
- Mamleeva, N. A., Kharlanov, A. N., Lunin, V. V. (2012). Delignification of deciduous wood under the action of hydrogen peroxide and ozone. *Russian Journal of Physical Chemistry A*, 87 (1), 28–34. doi: 10.1134/s0036024413010123
- Montgomery, D. C. (2017). *Design and analysis of experiments*. Wiley, 630.
- Obolenskaya, A. V., Shchegolev, V. P., Akim, G. L. et. al. (1965). *Prakticheskie raboty po himii drevesiny i cellyulozy*. Moscow: Lesnaya promyshlennost', 412.
- Trautmann, H., Weihs, C. (2005). On the distribution of the desirability index using Harrington's desirability function. *Metrika*, 63 (2), 207–213. doi: 10.1007/s00184-005-0012-0

DOI: 10.15587/1729-4061.2018.122000

MATHEMATICAL MODEL OF THE REVERSE WATER POSTPURIFICATION AT MINING ENTERPRISES WHEN USING ELECTROMAGNETIC FOCUSING OF CONTAMINANTS (p. 10-16)

Oleg Terentiev

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-7849-5929>

Kostiantyn Tkachuk

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0001-5230-9980>

Oksana Tverda

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0003-3163-0972>

Anton Kleshchov

National Technical University of Ukraine
«Igor Sikorsky Kyiv Polytechnic Institute», Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-9412-4156>

This study addresses the post-purification of reverse water by the electromagnetic focusing of charged particles in contaminants of polychlorinated biphenyls at mining enterprises. We established functional dependences of the Larmor radius of focusing of contaminant ions on operating parameters of the electromagnetic post-purification system (current strength of the focusing coil, length of the focusing coil), which allowed us to justify the required current of 0.025 A in the focusing coil for the post-purification of a liquid from polychlorinated biphenyls. The developed model of the electromagnetic system for water post-purification from the ions in contaminants made it possible to select the required Larmor radius for focusing the polychlorinated biphenyls in order to remove them effectively from a flow of liquid. As a result of post-purification, the contaminants are focused along the axis of the main flow that enables their removal through an additional branch pipe. Under the effect of the orbital moment that occurs due to magnetic induction, the motion vector of contaminants changed, and they are focused in the center of the fluid flow. We established the logarithmic dependence of height of the focusing paraboloid, which decreases from 0.057 m to 0.032 m with an increase in current of the focusing coil from 0.01 A to 0.1 A. This is due to an increase in the kinetic energy, transmitted by the charged particles, and an increase in the centripetal force. Determining the height of the focusing paraboloid makes it possible to effectively place the equipment for the removal of contaminations from the flow, and purify it.

Keywords: electromagnetic post-purification of liquid, Larmor radius, charged particles, focusing of contaminant impurities.

References

1. RECP conception. Resource Efficient and Cleaner Production Centre. Available at: <http://recpc.kpi.ua/ua/pro-nas-2/kontseptsiya-rechv/>
2. Vygovska, D., Vyhovsky, D., Pikulova, T. (2012). Mine water purification in case of mine “Bilozerska”. Herald of Donetsk mining University, 1-2, 117–125.
3. Pannov, V., Nifontov, Y., Panin, A. (2008). Theoretical Basis for Environment Protection. Moscow: Academy, 313.
4. Tsybul'sky, A., Chernyaev, A. (2014). Electrophysical water treatment methods. Industrial ecology, 2, 27–31.
5. Ambashta, R. D., Sillanpää, M. (2010). Water purification using magnetic assistance: A review. Journal of Hazardous Materials, 180 (1-3), 38–49. doi: 10.1016/j.jhazmat.2010.04.105
6. Surendran, U., Sandeep, O., Joseph, E. J. (2016). The impacts of magnetic treatment of irrigation water on plant, water and soil characteristics. Agricultural Water Management, 178, 21–29. doi: 10.1016/j.agwat.2016.08.016
7. Law On National Program “Drinking Water of Ukraine for 2006–2020” (2005). Holos Ukrainy, 69, 10–12.
8. Terentiev, O., Mozharovska, O., Vorfolomeiyev, A. (2008). Ways and Means for Treatment of Operational Liquid of Coal Mining Equipment. Visnyk NTUU “KPI”. Series: Coal Mining, 16, 73–79.
9. Mozharovska, O. (2009). Management of Liquid Environment State for Increasing Quality of Coal Mining Equipment Operation. In: “Power engineering. Ecology. A Human Being”, 185–188.
10. Terentiev, O., Mozharovska, O., Vorfolomeiyev, A. (2009). Identification of Distribution of Magnetic Induction of “Magnetic Trap” for Capturing Ions of Impurities in Liquid I Delivery Pipe and its Practical Application. Naukovi Visti NTUU “KPI”, 1, 121–127.
11. Meireles, M., Prat, M., Estachy, G. (2015). Analytical modeling of steady-state filtration process in an automatic self-cleaning filter. Chemical Engineering Research and Design, 100, 15–26. doi: 10.1016/j.cherd.2015.04.030
12. Mo, Y., Chen, J., Xue, W., Huang, X. (2010). Chemical cleaning of nanofiltration membrane filtrating the effluent from a membrane bioreactor. Separation and Purification Technology, 75 (3), 407–414. doi: 10.1016/j.seppur.2010.09.011
13. Chang, H., Liang, H., Qu, F., Ma, J., Ren, N., Li, G. (2015). Hydraulic cleaning water contaminated with humid acid. Journal of Environmental Sciences, 219–225.
14. Guedes-Alonso, R., Ciofi, L., Sosa-Ferrera, Z., Santana-Rodríguez, J. J., Bubba, M. del, Kabir, A., Furton, K. G. (2016). Determination of androgens and progestogens in environmental and biological samples using fabric phase sorptive extraction coupled to ultra-high performance liquid chromatography tandem mass spectrometry. Journal of Chromatography A, 1437, 116–126. doi: 10.1016/j.chroma.2016.01.077
15. Huang, S., Park, H.-W., Jo, Y.-M., Park, Y.-K., Kim, Y.-C. (2014). Application of magnetic field to iron contained dust capture. Journal of the Korean Oil Chemists' Society, 31 (1), 59–65. doi: 10.12925/jkocs.2014.31.1.59
16. Pa, P. S. (2008). Design of Finish System Using Rotational Magnetic-Assistance in Ultrasonic Electrochemical Finishing of Freeform-Surfaces. Advanced Materials Research, 47-50, 45–48. doi: 10.4028/www.scientific.net/amr.47-50.45
17. Shinjo, T. (Ed.) (2014). Nanomagnetism and spintronics. London: Elsevier, 2014. 372. doi: 10.1016/c2013-0-00584-1
18. Influence of Magnetic Field on Water Characteristics. Ukraine Scientific Portal. Available at: <http://labprice.ua/statti/naukovo-prochudesni-vlastivosti-vodi/vpliv-magnitnogo-polya-na-vlastivosti-vodi/>
19. Huo, S., Li, C., Xi, B., Yu, Z., Yeager, K. M., Wu, F. (2017). Historical record of polychlorinated biphenyls (PCBs) and special occurrence of PCB 209 in a shallow fresh-water lake from eastern China. Chemosphere, 184, 832–840. doi: 10.1016/j.chemosphere.2017.06.073
20. Anisina, I., Bashurin, V., Zhmailo, V., Shirokov, A. (2011). The dynamics of relativistic electrons generated by a local source in magneto-plasma trap. Questions of Atomic Science and Technology. Series: Pure and applied physics, 3, 94–108.
21. Terentiev, O., Tkachuk, K., Tverda, O., Kleshchov, A. (2016). Electromagnetic focusing of impurities in water purification. Eastern-European Journal of Enterprise Technologies, 4 (10 (82)), 10–15. doi: 10.15587/1729-4061.2016.75251

22. Wieser, M. E., Holden, N., Coplen, T. B., Böhlke, J. K., Berglund, M., Brand, W. A. et. al. (2013). Atomic weights of the elements 2011 (IUPAC Technical Report). Pure and Applied Chemistry, 85 (5), 1047–1078. doi: 10.1351/pac-rep-13-03-02
23. Kikoin, I. K. (Ed.) (1976). Physical Values Tables. Moscow: Atomizdat, 1008.
24. Ferromagnetic, Paramagnetic and Diamagnetic bodies. Everything about Relay Protection. Available at: http://rza.org.ua/elteh/read/61--Ferromagnitnie--paramagnitnie-i-diamagnitnie-tela_61.html
25. Bashta, T. (1971). Machine Building Hydraulics. Moscow: Mashynostroeniye, 672.
26. Sibikin, Y. (2014). Reference Book for a Construction Electrician. Moscow – Berlin: Direct – Media, 331.
27. Yavorskiy, B., Detlaf, A. (1985). Handbook of Physics. Moscow: Nauka, 512.
28. Knoepfel, H. (2008). Magnetic Fields: A Comprehensive Theoretical Treatise for Practical Use. John Wiley & Sons, 643.
29. Yezhov, S., Makarets, M., Romanenko, O. (2008). Classic Mechanincs. Kyiv: PPC “Kyivskiy Uiversitet”, 480.
30. Vinokurov, V. (2014). Modeling of Destruction of Geomaterials Particles in Centrifugal Mills. Modern Problems of Science and Education, 6. Available at: <http://www.science-education.ru/ru/article/view?id=16488>

DOI: 10.15587/1729-4061.2018.124045

**RESEARCH INTO EMISSIONS OF NITROGEN OXIDES
WHEN CONVERTING THE DIESEL ENGINES TO
ALTERNATIVE FUELS (p. 16-22)**

Sviatoslav Kryshchop

Nadvirna College of National Transport University, Nadvirna,
Ukraine

ORCID: <http://orcid.org/0000-0001-7899-8817>

Myroslav Panchuk

Ivano-Frankivsk National Technical University of Oil and Gas,
Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0002-4898-2707>

Bohdan Dolishnii

Ivano-Frankivsk National Technical University of Oil and Gas,
Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0002-4591-5381>

Liudmyla Kryshchop

Ivano-Frankivsk National Technical University of Oil and Gas,
Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0002-5274-0217>

Mariia Hnyp

Ivano-Frankivsk National Technical University of Oil and Gas,
Ivano-Frankivsk, Ukraine

ORCID: <http://orcid.org/0000-0003-3662-0941>

Olena Skalatska

Odessa I. I. Mechnikov National University, Odessa, Ukraine

ORCID: <http://orcid.org/0000-0003-1439-8753>

We conducted theoretical and experimental research into emissions of nitrogen oxides in exhaust gases of the diesel engines, re-equipped for gas.

The research is important because the emissions of nitrogen oxides in the exhaust gases are one of the biggest environmental problems at the present stage of development of designs for internal combustion engines. Therefore, reducing the emissions of nitrogen oxides in diesel engines by re-equipping them to gas fuel is an impor-

tant task for specialists in design and operation of internal combustion engines.

The result of theoretical research is the mathematical model that we constructed in order to calculate emissions of nitrogen oxides in the exhaust gases of diesel engines and the engines, converted to gas fuel. Based on experimental research, we have established dependences of emissions of nitrogen oxides in exhaust gases of the diesel engines, re-equipped for gas, on loading and the crankshaft rotation frequency. Studies have shown that diesel engines, which are converted to alternative gas fuel, reduce emissions of nitrogen oxides in the exhaust gases in a range from 13.9 % to 47.1 % depending on engine rotation and load. The results obtained make it possible to reduce the emissions of harmful substances in exhaust gases of automobile engines and optimize design of the systems for exhaust gases recirculation.

Keywords: alternative fuels, diesel engine, nitrogen oxides, engine re-equipped for gas fuel.

References

1. Bondarenko, V., Svietskina, O., Sai, K. (2017). Study of the formation mechanism of gas hydrates of methane in the presence of surface-active substances. Eastern-European Journal of Enterprise Technologies, 5 (6 (89)), 48–55. doi: 10.15587/1729-4061.2017.112313
2. Panchuk, M., Kryshchop, S., Shlapak, L. et. al. (2017). Main trends of biofuels production in Ukraine. Transport Problems, 12 (4), 15–26.
3. Skriabyn, M. (2008). Influence of the setting angle of the fuel injection advance on the combustion characteristics and the content of nitrogen oxides in the diesel cylinder with turbocharging and intercooling of the charge air 4 CHN 11,0/12,5. Improving the performance of internal combustion engines. Materials II All-Russian Scient. Pract. Conf. “Science-Technology-Resource-saving”, 5, 194–197.
4. Lykhanov, V., Anfylatov, A. (2015). Change in the formation of nitrogen oxides in the diesel cylinder when working on methanol. Tractors and agricultural machinery, 4, 3–5.
5. Lopatyn, O. (2008). Influence of methanol application on the combustion process parameters, volume content and mass concentration of nitrogen oxides in the diesel cylinder 10,5/12,0 when working with the DST depending on the angle of rotation of the crankshaft in the rated mode. Improving the performance of internal combustion engines. Materials II All-Rus. Scient. Pract. Conf. “Science-Technology-Resource-saving”, 5, 137–144.
6. Lyhanov, V. (2016). The effect of the use of methanol and MERR on the mass concentration of nitrogen oxides in the cylinder of a diesel engine of 10,5/12,0 when operating with a DST in the maximum torque regime. Improving the performance of internal combustion engines. Materials IX All-Russian Scient. Pract. Conf. “Science-Technology-Resource-saving”, 12, 195–198.
7. Kanilo, P. M., Sarapina, M. V. (2012). The Future of Motor Transport – Alternative Fuels and Carcinogenic Safety. Automobile transport, 31, 40–49.
8. Vasenin, A. (2016). The KamAZ engine 820.61–260: features of the power system and typical faults. Young scientist, 14, 128–131.
9. Kryshchop, S., Kryshchop, L., Melnyk, V., Dolishnii, B., Prunko, I., Demianchuk, Y. (2017). Experimental Research on Diesel Engine Working on a Mixture of Diesel Fuel and Fusel Oils. Transport Problems, 12 (2), 53–63.
10. Salimzyanova, A. (2012). Reduction of atmospheric pollution with the addition of alcohols as fuel in the engine. Science, education, production in solving environmental problems (Ecology-2012): Sat. sci. articles of the IX-th International Scientific-Tech. Conf., I, 170–175.
11. E, J., Zuo, W., Gao, J., Peng, Q., Zhang, Z., Hieu, P. M. (2016). Effect analysis on pressure drop of the continuous regeneration-diesel particulate filter based on NO₂ assisted regeneration. Applied

- Thermal Engineering, 100, 356–366. doi: 10.1016/j.applthermaleng.2016.02.031
12. Basu, R. (2017). Evaluation of some renewable energy technologies. *Mining of Mineral Deposits*, 11 (4), 29–37. doi: 10.15407/mining11.04.029
 13. Louis, C., Liu, Y., Tassel, P., Perret, P., Chaumont, A., André, M. (2016). PAH, BTEX, carbonyl compound, black-carbon, NO₂ and ultrafine particle dynamometer bench emissions for Euro 4 and Euro 5 diesel and gasoline passenger cars. *Atmospheric Environment*, 141, 80–95. doi: 10.1016/j.atmosenv.2016.06.055
 14. O'Driscoll, R., ApSimon, H. M., Oxley, T., Molden, N., Stettler, M. E. J., Thiagarajah, A. (2016). A Portable Emissions Measurement System (PEMS) study of NO_x and primary NO₂ emissions from Euro 6 diesel passenger cars and comparison with COP-ERT emission factors. *Atmospheric Environment*, 145, 81–91. doi: 10.1016/j.atmosenv.2016.09.021
 15. Iwasaki, M., Shinjoh, H. (2010). A comparative study of “standard”, “fast” and “NO₂” SCR reactions over Fe/zeolite catalyst. *Applied Catalysis A: General*, 390 (1-2), 71–77. doi: 10.1016/j.apcata.2010.09.034
 16. Iwasaki, M., Yamazaki, K., Shinjoh, H. (2009). Transient reaction analysis and steady-state kinetic study of selective catalytic reduction of NO and NO+NO₂ by NH₃ over Fe/ZSM-5. *Applied Catalysis A: General*, 366 (1), 84–92. doi: 10.1016/j.apcata.2009.06.036
 17. Grossale, A., Nova, I., Tronconi, E., Chatterjee, D., Weibel, M. (2008). The chemistry of the NO/NO₂-NH₃ “fast” SCR reaction over Fe-ZSM5 investigated by transient reaction analysis. *Journal of Catalysis*, 256 (2), 312–322. doi: 10.1016/j.jcat.2008.03.027
 18. Ruggeri, M. P., Grossale, A., Nova, I., Tronconi, E., Jirglova, H., Sobalik, Z. (2012). FTIR in situ mechanistic study of the NH₃/NO/NO₂ “Fast SCR” reaction over a commercial Fe-ZSM-5 catalyst. *Catalysis Today*, 184 (1), 107–114. doi: 10.1016/j.cattod.2011.10.036
 19. Kim, D. H., Mudiyansele, K., Szányi, J., Zhu, H., Kwak, J. H., Peden, C. H. F. (2012). Characteristics of Pt-K/MgAl₂O₄ lean NO_x trap catalysts. *Catalysis Today*, 184 (1), 2–7. doi: 10.1016/j.cattod.2011.11.024

DOI: 10.15587/1729-4061.2018.122425

TWOSTAGE TREATMENT OF SOLID WASTE LEACHATES IN AERATED LAGOONS AND AT MUNICIPAL WASTEWATER TREATMENT PLANTS (p. 23-30)

Myroslav Malovany

Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-3868-1070>

Volodymyr Zhuk

Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-2275-0799>

Vira Sliusar

Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0002-7438-4428>

Andriy Sereda

Lviv Polytechnic National University, Lviv, Ukraine
ORCID: <http://orcid.org/0000-0003-2694-2939>

The two-stage technology of treatment of the leachates of the municipal solid waste (MSW) dumps in aerated lagoons and at municipal wastewater treatment plants (WWTP) has been studied. The study objective was to develop a technology that can be implemented at existing MSW dumps and landfills. Static and dynamic modes of implementation of both stages of the technology were investigated on the model units. Static 16-day mode was experimentally studied in the aerated lagoon conditions. As a result, we have managed to

achieve almost a 2-fold reduction of COD and more than a 3-fold decrease in concentration of ammonium ions.

Dynamic mode studies have established that the optimal time of leachate staying in the reactor was 10 days. Change of the relative concentration of ammonium nitrogen in the leachate largely depends on the process temperature, so in real conditions, it is necessary to adjust the modes of realization of the individual stages depending on the ambient temperature. It has been established that for treatment of leachate at municipal WWTP in a static mode at the value of the ratio of leachate dilution with municipal sewage of 1:1000, the maximum effect of treatment of both from ammonium ions and COD was achieved. The study of leachate treatment at municipal WWTP in a dynamic mode has confirmed stability of maintaining the treatment indicators in time. By implementation of the two-stage technology of leachate treatment, it will be possible to minimize environmental hazard from surface and ground water contamination in the zone of influence of MSW dumps and landfills.

Keywords: leachate of municipal solid waste dumps, aerated lagoon, biological treatment, immobilization of biocenosis.

References

1. Metodichni rekomendatsiyi iz zbyrannia, utylizatsiyi ta zneshkodzhennia filtratu polihoniv pobutovykh vidkhodiv. Zatverdzeni nakazom Ministerstva rehionalnoho rozvytku, budivnytstva ta zhytlovo-komunalnoho hospodarstva Ukrainy No. 421 vid 20.08.2012 r.
2. Dushkin, S. S., Kovalenko, A. N., Degtyar', M. V., Shevchenko, T. A. (2011). Resursoberegayushchie tekhnologii ochistki stochnyh vod. Kharkiv: HNAGH, 146.
3. Gomez, E., Rani, D. A., Cheeseman, C. R., Deegan, D., Wise, M., Boccaccini, A. R. (2009). Thermal plasma technology for the treatment of wastes: A critical review. *Journal of Hazardous Materials*, 161 (2-3), 614–626. doi: 10.1016/j.jhazmat.2008.04.017
4. Mashal, A., Abu-Daherieh, J., Graham, W. et. al. (2012). Landfill leachate treatment using plasma-Fenton's process. Sixth Jordan International Chemical Engineering Conference. Amman, Jordan, 256–259.
5. Dzhamalova, G. A. (2015). Matematicheskoe planirovanie emissii biogaza i fil'trata v protsesse intensivnogo anaerobnogo razlozheniya tvorlyh bytovykh othodov v bioreaktore. *Sovremennye problemy nauki i obrazovaniya*, 2-2, 44–50.
6. Govahi, S., Karimi-Jashni, A., Derakhshan, M. (2011). Treatability of landfill leachate by combined upflow anaerobic sludge blanket reactor and aerated lagoon. *International Journal of Environmental Science and Technology*, 9 (1), 145–151. doi: 10.1007/s13762-011-0021-7
7. Gao, J., Oloibiri, V., Chys, M., Audenaert, W., Decostere, B., He, Y. et. al. (2014). The present status of landfill leachate treatment and its development trend from a technological point of view. *Reviews in Environmental Science and Bio/Technology*, 14 (1), 93–122. doi: 10.1007/s11157-014-9349-z
8. Hasar, H., Unsal, S. A., Ipek, U., Karatas, S., Cinar, O., Yaman, C., Kinaci, C. (2009). Stripping/flocculation/membrane bioreactor/reverse osmosis treatment of municipal landfill leachate. *Journal of Hazardous Materials*, 171 (1-3), 309–317. doi: 10.1016/j.jhazmat.2009.06.003
9. Payandeh, P. E., Mehrdadi, N., Dadgar, P. (2017). Study of Biological Methods in Landfill Leachate Treatment. *Open Journal of Ecology*, 07 (09), 568–580. doi: 10.4236/oje.2017.79038
10. Shmandiy, V. M., Bezdenezhnykh, L. A., Kharlamova, E. V. (2012). The use of waste-derived adsorbents for improvement of the human environment. *Gigiena i sanitaria*, 6, 44–45.
11. Calli, B., Mertoglu, B., Roest, K., Inanc, B. (2006). Comparison of long-term performances and final microbial compositions of an-

- aerobic reactors treating landfill leachate. *Bioresource Technology*, 97 (4), 641–647. doi: 10.1016/j.biortech.2005.03.021
12. Sawaitayothin, V., Polprasert, C. (2007). Nitrogen mass balance and microbial analysis of constructed wetlands treating municipal landfill leachate. *Bioresource Technology*, 98 (3), 565–570. doi: 10.1016/j.biortech.2006.02.002
 13. Robinson, H. D., Grantham, G. (1988). The treatment of landfill leachates in on-site aerated lagoon plants: Experience in Britain and Ireland. *Water Research*, 22 (6), 733–747. doi: 10.1016/0043-1354(88)90184-4
 14. Mehmood, M. K., Adetutu, E., Nedwell, D. B., Ball, A. S. (2009). In situ microbial treatment of landfill leachate using aerated lagoons. *Bioresource Technology*, 100 (10), 2741–2744. doi: 10.1016/j.biortech.2008.11.031
 15. Maehlum, T. (1995). Treatment of landfill leachate in on-site lagoons and constructed wetlands. *Water Science Technology*, 32 (3), 129–135. doi: 10.1016/0273-1223(95)00613-3
 16. Moroz, O. I., Malovanyi, M. S., Zhuk, V. M., Sliusar, V. T., Sereda, A. S., Marakhovska, S. B. et al. (2017). Analiz perspektyv aerobnoho ochyshchennia infiltrativ smittiezvalyshch ta polihoniv tverdykh pobutovykh vidkhodiv. *Naukovyi visnyk NLTU Ukrainy*, 27 (3), 83–88.
 17. *Metodyka fotometrychnoho vyznachennia amoniy ioniv z reaktivom Neslera v stichnykh vodakh: KND 211.1.4.030-95 (1995)*. Kyiv, 16.
 18. DSTU ISO 6060:2003. *Yakist vody. Vyznachannia khimichnoi potreby v kysni (ISO 6060:1989, IDT) (2004)*. Kyiv: Derzhspozhyvstandart Ukrainy, 6.

DOI: 10.15587/1729-4061.2018.121727

DEVELOPMENT OF THE TECHNIQUE FOR RESTRICTING THE PROPAGATION OF FIRE IN NATURAL PEAT ECOSYSTEMS (p. 31-37)

Konstantin Mygalenko

National University of Civil Protection of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0002-7125-8442>

Vitaliy Nuyanzin

National University of Civil Protection of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0003-4785-0814>

Aleksandr Zemlianskyi

National University of Civil Protection of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0002-1305-0387>

Andrii Dominik

Lviv State University of Life Safety, Lviv, Ukraine

ORCID: <http://orcid.org/0000-0003-0139-2002>

Serhii Pozdiev

National University of Civil Protection of Ukraine,
Cherkasy, Ukraine

ORCID: <http://orcid.org/0000-0002-9085-0513>

In order to reduce the scale of peat fires, we suggest using fire barriers made of mineralized materials. The incombustible materials are proposed, specifically sand and bentonite clay, to be used for filling up artificial slits cut in a peat layer. Construction of anti-fire barriers requires a one-time expenditure, in contrast to the existing techniques for fire prevention that require continuous pumping of water in order to increase moisture content in peat.

Mathematical modeling of thermal processes in the system peat layer–fire barrier was performed. The time of reaching the

dangerous temperature by the protected layer, for the barriers made of river sand with a thickness of 300 mm, and for those made of bentonite clay with a thickness of 180 mm, is not less than 1 day. Given this, we have proven the effectiveness of the proposed barriers.

By using mathematical modeling of the processes of fire development, a parabolic dependence was built of the thickness of fire protection barrier b , mm, on time τ , hours, required to protect an object. We established parameters for regression dependences of thickness of a barrier on the time required to protect a peat layer.

The result of present research is the proposed technique for designing fire protection barriers made of river sand and bentonite clay, based on the obtained patterns and regression dependences.

Research results could be used in the process of designing fire protection barriers for actual peatlands.

Keywords: temperature of peat layer, mineral fire barrier, fire safety of peat.

References

1. Analiz masyvu kartok obliku pozhezh (POG_STAT) za 12 misiatsiv 2016 roku. Available at: http://indicz.dsns.gov.ua/files/2017/2/2/AD_12_2016.pdf
2. Hayasaka, H., Noguchi, I., Putra, E. I., Yulianti, N., Vadrevu, K. (2014). Peat-fire-related air pollution in Central Kalimantan, Indonesia. *Environmental Pollution*, 195, 257–266. doi: 10.1016/j.envpol.2014.06.031
3. Davies, G. M., Gray, A., Rein, G., Legg, C. J. (2013). Peat consumption and carbon loss due to smouldering wildfire in a temperate peatland. *Forest Ecology and Management*, 308, 169–177. doi: 10.1016/j.foreco.2013.07.051
4. Blake, D., Hinwood, A. L., Horwitz, P. (2009). Peat fires and air quality: Volatile organic compounds and particulates. *Chemosphere*, 76 (3), 419–423. doi: 10.1016/j.chemosphere.2009.03.047
5. Prat-Guitart, N., Rein, G., Hadden, R. M., Belcher, C. M., Yearley, J. M. (2016). Effects of spatial heterogeneity in moisture content on the horizontal spread of peat fires. *Science of The Total Environment*, 572, 1422–1430. doi: 10.1016/j.scitotenv.2016.02.145
6. Ramadhan, M. L., Palamba, P., Imran, F. A., Kosasih, E. A., Nugroho, Y. S. (2017). Experimental study of the effect of water spray on the spread of smoldering in Indonesian peat fires. *Fire Safety Journal*, 91, 671–679. doi: 10.1016/j.firesaf.2017.04.012
7. Rakowska, J., Prochaska, K., Twardochleb, B., Rojewska, M., Porycka, B., Jaszkievicz, A. (2014). Selection of surfactants as main components of ecological wetting agent for effective extinguishing of forest and peat-bog fires. *Chemical Papers*. 2014. Vol. 68, Issue 6. P. 823–833. doi: 10.2478/s11696-013-0511-9
8. Myhalenko, K. I., Lenartovych, Ye. S., Semerak, M. M., Myhalenko, O. I. (2000). *Poshyrennia pidzemnoi pozhezhi na torfianykakh r. Tiasmyn. Pozhezhna bezpeka*, 17, 138–142.
9. Tihonov, A. N., Samarskiy, A. A. (1977). *Urvneniya matematicheskoy fiziki*. Moscow: Nauka, 735.
10. Samarskiy, A. A. (1971). *Vvedenie v teoriyu raznostnykh skhem*. Moscow: Nauka, 554.
11. Samarskiy, A. A., Vabishchevich, P. N. (2003). *Vychislitel'naya teploperedacha*. Moscow: Editorial URSS, 784.
12. Vlasova, E. A., Zarubin, V. S., Kuvyrkin, G. N.; Zarubin, V. S., Krishchenko, A. P. (Eds.) (2001). *Priblizhennyye metody matematicheskoy fiziki*. Moscow: MG TU im. Baumana, 700.
13. Gurvich, L. V., Veyts, I. V., Medvedev, V. A. et al. (1978). *Termodinamicheskie svoystva individual'nykh veshchestv. Spravochnoe izdanie. Vol. 1. Kn. 2*. Moscow: Nauka, 328.
14. Ibrahim, A. M., Mubarak, H. M. (2009). Finite Element Modeling of Continuous Reinforced Concrete Beam with External Pre-stressed. *European Journal of Scientific Research*, 30 (1), 177–186.

15. Demidov, P. G., Shandyba, V. A., Shcheglov, P. P. (1981). *Gorenje i svoystva goryuchih veshchestv*. Moscow: Himiya, 272.
16. Drits, V. A., Kossovskaya, A. G. (1990). *Glinistye mineraly: smektity, smeshanosloynnye obrazovaniya*. Moscow: Nauka, 214.
17. ANSYS, ANSYS 9.0 Manual Set, ANSYS Inc., Southpoint, 275 Technology Drive, Canonsburg, PA 15317, USA.
18. Golovanov, A. N., Yakimov, A. S., Abramovskih, A. A., Sukov, Ya. V. (2008). O matematicheskom modelirovanii protsessov zazhiganiya i tleniya torfa. *Teplofizika i aeromekhanika*, 15 (4), 1–9.
19. Saharov, A. S., Kislookiy, V. M., Kirichevskiy, V. V. et. al.; Saharov, A. S., Al'tenbah, I. A. (Eds.) (1982). *Metod konechnykh elementov v mekhanike tverdyh tel*. Moscow: Nauka, 480.

DOI: 10.15587/1729-4061.2018.123455

COMPUTER MODELING OF WATER CLEANING IN WETLAND TAKING INTO ACCOUNT OF SUFFUSION AND COLMATATION (p. 38-43)

Viktor Moshynskiy

National University of Water and Environmental Engineering, Rivne, Ukraine

ORCID: <http://orcid.org/0000-0002-1661-6809>

Victor Fylypchuk

National University of Water and Environmental Engineering, Rivne, Ukraine

ORCID: <http://orcid.org/0000-0001-5763-5398>

Natalia Ivanchuk

National University of Water and Environmental Engineering, Rivne, Ukraine

ORCID: <http://orcid.org/0000-0002-7170-7068>

Petro Martyniuk

National University of Water and Environmental Engineering, Rivne, Ukraine

ORCID: <http://orcid.org/0000-0002-2750-2508>

The mathematical model of filtering with regard to colmatation and suffusion in the system bioplato-filter 2. This saturated porous medium is considered in terms of a complex heterogeneous system “fill”-concentration of pollutants in porous liquid-concentration of colmatating particles. Mutual influences of system parameters are taken into account through:

- 1) the dynamic change of the porosity of the backfill in the process of filtering;
- 2) nonlinear dependence coefficient filter porosity of backfill;
- 3) dependence of velocity of filtration coefficient of filtering and gradient heads, and hence – and porosity.

Taking into account the following interplays allowed to increase the adequacy of mathematical models for the study of physical processes, however, led to the necessity of the study of nonlinear boundary value problems for systems of differential equations in partial derivatives. Nonlinearity of the boundary value problem does not allow to speak about her analytical solutions. Numerical solutions of the problems found by the method of finite elements with a software implementation of the relevant algorithms in FreeFem ++.

Computer modeling showed that when taking into account nonlinear dependence coefficient of filtration from the concentration of colmatating particles and dynamic changes of porosity in the process of filtering, predictive performance bioplato for six months reduced by 25%. Therefore, it is necessary to develop engineering solutions for reducing the influence of the colmatation-suffusion processes on the processes of filtering. The forecasting work bioplato relevant conduct on the design stage in order to implement predictive calculations. It is done by means of mathematical and computer modeling.

Keywords: bioplato-filter, the problem of filtration, colmatation, suffusion, finite element method, FreeFem ++.

References

1. Healy, M., Cawley, A. M. (2002). Nutrient Processing Capacity of a Constructed Wetland in Western Ireland. *Journal of Environment Quality*, 31 (5), 1739. doi: 10.2134/jeq2002.1739
2. Gleichman-Verheyc, E. G., Putten, W. H., Vander, L. (1992). Alvalwaterzuivering met helofytenfilters, een haalbaarheidsstudie. *Tijdschr. watervoorz. en Afvalwater*, 3, 56–60.
3. Zavatskiy, S. V., Kotelchuk, L. S., Kotelchuk, A. L. (2012). Bioengineering structures for low-waste sewage treatment. *Construction, engineering systems and communications*, 1 (3), 57–63.
4. Filipchuk, V. L., Kuriluk, M. S., Filipchuk, L. V., Kuriluk, O. M., Krylyuk, V. M., Pochtar, O. V. (2016). Purification of muddy waters in filtration regenerative wetland. *Bulletin of the Engineering Academy of Ukraine*, 3, 150–155.
5. Filipchuk, V. L., Bondar, O. I., Kuriluk, M. S., Ayaya, A., Krivoshey, P. P., Kuriluk, O. M., Pochtar, O. V. (2016). Water purification in filtration regenerative wetland. *Bulletin NUWEE*, 2 (74), 193–204.
6. Hosokova, Y., Miyoshi, E., Fukukawa, K. (1991). Characteristics of the process of purification of coastal waters by reed beds. *Rept. Partand Harbour. Res.*, 30 (11), 206–257.
7. Blankenberg, A.-G. B., Braskerud, B. C. (2002). «LIERDAMMEN» – a wetland testfield in Norway. Retention of nutrients, pesticides and sediments from a agriculture runoff: *Diffuse Pollut. Conf. Dublin*, 128–130.
8. Drenko, A. A., Kotsar, E. M. (2006). The use of higher aquatic plants in the practice of wastewater treatment and surface runoff. *Plumbing, heating, air conditioning*, 4, 12–15.
9. Liang, Y., Yeh, T.-C. J., Wang, Y.-L., Liu, M., Wang, J., Hao, Y. (2017). Numerical simulation of backward erosion piping in heterogeneous fields. *Water Resources Research*, 53 (4), 3246–3261. doi: 10.1002/2017wr020425
10. Sibille, L., Lominé, F., Poullain, P., Sail, Y., Marot, D. (2014). Internal erosion in granular media: direct numerical simulations and energy interpretation. *Hydrological Processes*, 29 (9), 2149–2163. doi: 10.1002/hyp.10351
11. Medvid, N. V. (2015). Investigation of the influence of the conduit and the washout zone on the processes of filtration consolidation of the ground dam using the finite element method. *Bulletin NUWEE. Series: Technical sciences*, 4 (72), 132–142.
12. Dobronravov, O. O., Cremez, V. S. (2006). Modeling of groundwater filtration taking into account the suffusion and colmatation. *Problems of water supply, drainage and hydraulics*, 7, 141–146.
13. Kapranov, U. I., Tropin, N. M. (2011). The structure of the colmatation layer in the vicinity of the moving boundary. *Applied Mechanics and Technical Physics*, 52 (6), 77–91.
14. Alem, A., Ahfir, N.-D., Elkawafi, A., Wang, H. (2014). Hydraulic Operating Conditions and Particle Concentration Effects on Physical Clogging of a Porous Medium. *Transport in Porous Media*, 106 (2), 303–321. doi: 10.1007/s11242-014-0402-8
15. Seetha, N., Mohan Kumar, M. S., Majid Hassanizadeh, S. (2015). Modeling the co-transport of viruses and colloids in unsaturated porous media. *Journal of Contaminant Hydrology*, 181, 82–101. doi: 10.1016/j.jconhyd.2015.01.002
16. Chetti, A., Benamar, A., Hazzab, A. (2016). Modeling of Particle Migration in Porous Media: Application to Soil Suffusion. *Transport in Porous Media*, 113 (3), 591–606. doi: 10.1007/s11242-016-0714-y
17. Berres, S., Bürger, R., Wendland, W. L. (2006). *Mathematical Models for the Sedimentation of Suspensions*. *Lecture Notes in Applied and Computational Mechanics*, 28, 7–44. doi: 10.1007/978-3-540-34961-7_1

18. Zhang, M., He, F., Zhao, D., Hao, X. (2017). Transport of stabilized iron nanoparticles in porous media: Effects of surface and solution chemistry and role of adsorption. *Journal of Hazardous Materials*, 322, 284–291. doi: 10.1016/j.jhazmat.2015.12.071
19. Chrysikopoulos, C. V., Katzourakis, V. E. (2015). Colloid particle size-dependent dispersivity. *Water Resources Research*, 51 (6), 4668–4683. doi: 10.1002/2014wr016094
20. Francisca, F. M., Glatstein, D. A. (2010). Long term hydraulic conductivity of compacted soils permeated with landfill leachate. *Applied Clay Science*, 49 (3), 187–193. doi: 10.1016/j.clay.2010.05.003
21. Gerus, V. A., Kutya, T. V., Martynyuk, P. M. (2016). Generalization of the equation of filtration and heat and mass transfer in the case of suffusion processes. *Mathematical and computer modeling. Series: Technical sciences*, 14, 48–63.
22. Safonyk, A. P. (2015). Modelling the filtration processes of liquids from multicomponent contamination in the conditions of authentication of mass transfer coefficient. *International Journal of Mathematical Models and Methods in Applied Sciences*, 9, 189–192.
23. Sergienko, I. V., Skopetskyi, V. V., Deineka, V. S. (1991). *Mathematical modeling and research of processes in heterogeneous environments*. Kyiv: Naukova Dumka, 432.
24. Vlasyuk, A. P., Martynyuk, P. M., Medvid, N. V. (2017). Mathematical modeling of consolidation and filtration destruction of soils in the bases of hydraulic engineering and power structures. Rivne: NUWEE, 423.
25. *Engineering geology and environmental protection* (2010). Vinnitsa: VNTU, 262.

DOI: 10.15587/1729-4061.2018.121615

A STUDY OF ENVIRONMENTALLY FRIENDLY RECYCLING OF TECHNOGENIC CHROMIUM AND NICKEL CONTAINING WASTE BY THE METHOD OF SOLID PHASE EXTRACTION (p. 44-49)

Stanislav Hryhoriev

Zaporizhzhya National University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0002-1170-6856>

Artem Petryshchev

Zaporizhzhya National Technical University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0003-2631-1723>

Ganna Shyshkanova

Zaporizhzhya National Technical University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0002-0336-2803>

Tetyana Zaytseva

Oles Honchar Dnipro National University, Dnipro, Ukraine
ORCID: <http://orcid.org/0000-0002-6346-3390>

Oleksandr Frydman

Oles Honchar Dnipro National University, Dnipro, Ukraine
ORCID: <http://orcid.org/0000-0002-5135-5448>

Kristina Krupcy

Zaporizhzhya National University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0003-1522-1060>

Andrey Andreev

Zaporizhzhya National University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0002-5390-6813>

Alexander Katschan

Zaporizhzhya National Technical University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0001-8194-5572>

Yuliya Petrusha

Zaporizhzhya National University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0003-3041-2877>

Dmytro Stepanov

Zaporizhzhya National Technical University, Zaporizhzhya, Ukraine
ORCID: <http://orcid.org/0000-0003-1780-3611>

The study has revealed the regularities of the effect produced by increasing the content of scale of steel 12Cr18Ni10Ti in the charge from 5 to 75 mass % on the contents of the products of carbon thermal reduction of oxide waste of corrosion-resistant steels. The concentration of Ni is increased from 0.8 to 7.0 mass % when the Cr content ranges from 15.9 to 17.1 mass %. The concentration of Cr in the extraction products within the range of 16.1–17.1 mass% is provided with the content of scale of 95Cr18 steel in the charge in the range from 5 to 55 mass %. It has been found that metallization products mainly consist of a solid solution of alloying elements in α -Fe. Fe_3O_4 , Fe_3C , and Fe_2C were also identified. The microstructure of the extraction products is spongy and disordered. The particles are sintered, with varying Cr and Ni contents in the ranges of 7.47 to 18.03 mass % and 2.97–10.40 mass %, respectively. The study has helped achieve environmentally safe conditions for solid-phase extraction of chrome and nickel containing industrial wastes from the production of corrosion-resistant steels with the return of the alloyed product to the welding industry.

Keywords: waste processing, corrosion-resistant steel, carbon thermal reduction, phase analysis, microstructure, resource efficiency.

References

1. Puchol, R. Q., Sosa, E. R., González, L. O., Castañeda, Y. P., Sierra, L. Y. (2016). New conception of the reutilization of solid waste from Cuban nickeliferous hydrometallurgical industry. *Centro Azucar*, 43 (4), 1–15.
2. Pincovschi, I., Neacsu, N., Modrogan, C. (2017). The Adsorption of Lead, Copper, Chrome and Nickel Ions from Waste Waters in Agricultural Argillaceous Soils. *Revista de Chimie*, 68 (4), 635–638.
3. Madebwe, V., Madebwe, C., Munodawafa, A., Mugabe, F. (2017). Analysis of the Spatial and Temporal Variability of Toxic Heavy Metal Concentrations in Ground Water Resources in Upper Sanyati Catchment, Midlands Province, Zimbabwe. *IARD International Journal of Geography and Environmental Management*, 3 (1), 23–37.
4. Rubezhniak, I. H. (2016). Porivnialna otsinka normatyviv zabrudnennia gruntiv vazhkymy metalamy v Ukraini ta krainakh EU. *Naukovyi visnyk Natsionalnoho universytetu bioresursiv i pryrodokorystuvannia Ukrainy. Seriya: Biolohiya, biotekhnolohiya, ekolohiya*, 234, 228–238.
5. Atanassov, I. (2008). New bulgarian soil pollution standards. *Bulgarian Journal of Agricultural Science*, 14, 68–75.
6. Eastmond, D. A., MacGregor, J. T., Slesinski, R. S. (2008). Trivalent Chromium: Assessing the Genotoxic Risk of an Essential Trace Element and Widely Used Human and Animal Nutritional Supplement. *Critical Reviews in Toxicology*, 38 (3), 173–190. doi: 10.1080/10408440701845401
7. Itankar, N., Patil, Y. (2014). Management of Hexavalent Chromium from Industrial Waste Using Low-cost Waste Biomass. *Procedia – Social and Behavioral Sciences*, 133, 219–224. doi: 10.1016/j.sbspro.2014.04.187
8. Chervona, Y., Arita, A., Costa, M. (2012). Carcinogenic metals and the epigenome: understanding the effect of nickel, arsenic, and chromium. *Metallomics*, 4 (7), 619. doi: 10.1039/c2mt20033c
9. Ryabchikov, I. V., Belov, B. F., Mizin, V. G. (2014). Reactions of metal oxides with carbon. *Steel in Translation*, 44 (5), 368–373. doi: 10.3103/s0967091214050118
10. Mechachti, S., Benchiheb, O., Serrai, S., Shalabi, M. (2013). Preparation of iron Powders by Reduction of Rolling Mill Scale. *International Journal of Scientific & Engineering Research*, 4 (5), 1457–1472.

11. Roshchin, V. E., Roshchin, A. V., Ahmetov, K. T., Povolotskiy, V. D., Goyhenberg, Yu. N. (2015). Formirovaniye metallicheskoy i karbidnykh faz pri poluchenii uglerodistogo ferrohroma: teoriya i eksperiment. *Problemy chernoy metallurgii i materialovedeniya*, 1, 5–18.
12. Kolesnikov, A. S., Nazarbekova, S. P., Baibolov, K. S., Dzholdasova, S. A. (2017). Thermodynamic simulation of chemical and phase transformations in the $\text{Fe}_2\text{O}_3\text{-NiO-CoO-C}$. *Izvestiya Vuzov Tsvetnaya Metallurgiya (Proceedings of Higher Schools Nonferrous Metallurgy)*, 3, 37–44. doi: 10.17073/0021-3438-2017-3-37-44
13. Kovalov, A. M., Petryshchev, A. S., Hryhorev, S. M. (2010). Analiz termodinamichnoi rivnovahy v systemi Ni-Co-O-C-H stosovno tekhnolohiyi metalizatsiyi metalooksydneykh tekhnolohiykh vidkhodiv pretsyziynykh splaviv typu NK. *Naukovi pratsi Donetskoho natsionalnoho tekhnichnoho universytetu. Seriya: Metalurhiya*, 12, 7–15.
14. Pan, J., Zheng, G., Zhu, D., Zhou, X. (2013). Utilization of nickel slag using selective reduction followed by magnetic separation. *Transactions of Nonferrous Metals Society of China*, 23 (11), 3421–3427. doi: 10.1016/s1003-6326(13)62883-6
15. Simonov, V. K., Grishin, A. M. (2015). Termodinamicheskii analiz i osobennosti kinetiki vosstanovleniya Cr_2O_3 uglerodom samostoyatel'no i v potoke SO, N₂. *Elektrometallurgiya*, 9, 9–18.
16. Akimov, E. V., Senin, A. V., Roshchin, V. E. (2013). Termodinamicheskii analiz polucheniya nizkouglerodistogo ferrohroma s primeneniem modeli assotsirovannykh rastvorov. *Vestnik Yuzhno-Ural'skogo gosudarstvennogo universiteta. Seriya: Metallurgiya*, 13 (1), 182–185.
17. Simonov, V. K., Grishin, A. M. (2012). Termodinamicheskii analiz i osobennosti mekhanizma tverdogaznogo vosstanovleniya Cr_2O_3 uglerodom. Ch. 1. *Elektrometallurgiya*, 9, 21–26.
18. Simonov, V. K., Grishin, A. M. (2012). Termodinamicheskii analiz i osobennosti mekhanizma tverdogaznogo vosstanovleniya Cr_2O_3 uglerodom. Ch. 2. *Elektrometallurgiya*, 10, 13–18.
19. Zhao, L., Wang, L., Chen, D., Zhao, H., Liu, Y., Qi, T. (2015). Behaviors of vanadium and chromium in coal-based direct reduction of high-chromium vanadium-bearing titanomagnetite concentrates followed by magnetic separation. *Transactions of Nonferrous Metals Society of China*, 25 (4), 1325–1333. doi: 10.1016/s1003-6326(15)63731-1

DOI: 10.15587/1729-4061.2018.122419

EXPERIMENTAL STUDY OF THE FLUCTUATIONS OF GAS MEDIUM PARAMETERS AS EARLY SIGNS OF FIRE
(p. 50-55)

Boris Pospelov

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0002-0957-3839>

Vladimir Andronov

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0001-7486-482X>

Evgeniy Rybka

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0002-5396-5151>

Vadym Popov

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0003-4182-9248>

Andrey Romin

National University of Civil Protection of Ukraine, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0002-3974-6702>

The results of the experimental study of fluctuations of dynamics of hazardous factors of gaseous medium at early ignition of com-

combustible materials in the chamber, simulating pressurized premises, are presented. The authors considered a non-traditional approach to research into dynamics of hazardous factors, based on current window estimation of the Pearson lag correlations for fluctuations of the main parameters of gaseous medium as non-stationary processes. In contrast to the known approaches, a given approach makes it possible to perform reliable localization in time of an early ignition of materials in premises.

It was established that early ignition of materials has a significant effect on correlations of temperature fluctuations, concentrations of carbon monoxide and smoke in gaseous medium. It was shown that correlations of fluctuations of carbon monoxide and smoke concentrations are most informative for localization of early ignitions. Temperature fluctuations are more informative at localization of early ignition of alcohol and paper. The results of current window evaluation of the Pearson lag correlations show that in the absence of ignitions, fluctuations can be considered uncorrelated. In this case, existence of ignition leads to occurrence of non-stationary fluctuations of correlations.

It is indicated that fluctuations of parameters of gaseous medium in the general case are described by autoregression processes of higher order, depending both on the type of combustible material and the stage of ignition development. A sustainable sign of early ignition of combustible materials in the simulation chamber is a significant increase in the correlation interval of non-stationary temperature fluctuations, as well as concentrations of carbon monoxide and smoke in gaseous medium. In equilibrium of gas medium, fluctuations of its parameters have a much smaller correlation interval, characteristic for uncorrelated processes.

Keywords: fire, early ignition, gaseous medium, simulation chamber, correlations of fluctuations, window estimation.

References

1. Poulsen, A., Jomaas, G. (2011). Experimental Study on the Burning Behavior of Pool Fires in Rooms with Different Wall Linings. *Fire Technology*, 48 (2), 419–439. doi: 10.1007/s10694-011-0230-0
2. Wu, Y., Harada, T. (2004). Study on the Burning Behaviour of Plantation Wood. *Scientia Silvae Sinicae*, 40, 131.
3. Zhang, D., Xue, W. (2010). Effect of Heat Radiation on Combustion Heat Release Rate of Larch. *Journal of West China Forestry Science*, 39, 148.
4. Ji, J., Yang, L., Fan, W. (2003). Experimental Study on Effects of Burning Behaviours of Materials Caused by External Heat Radiation. *Journal of Combustion Science and Technology*, 9, 139.
5. Peng, X., Liu, S., Lu, G. (2005). Experimental Analysis on Heat Release Rate of Materials. *Journal of Chongqing University*, 28, 122.
6. Andronov, V., Pospelov, B., Rybka, E. (2016). Increase of accuracy of definition of temperature by sensors of fire alarms in real conditions of fire on objects. *Eastern-European Journal of Enterprise Technologies*, 4 (5 (82)), 38–44. doi: 10.15587/1729-4061.2016.75063
7. Andronov, V., Pospelov, B., Rybka, E. (2017). Development of a method to improve the performance speed of maximal fire detectors. *Eastern-European Journal of Enterprise Technologies*, 2 (9 (86)), 32–37. doi: 10.15587/1729-4061.2017.96694
8. Pospelov, B., Andronov, V., Rybka, E., Skliarov, S. (2017). Design of fire detectors capable of self-adjusting by ignition. *Eastern-European Journal of Enterprise Technologies*, 4 (9 (88)), 53–59. doi: 10.15587/1729-4061.2017.108448
9. Pospelov, B., Andronov, V., Rybka, E., Skliarov, S. (2017). Research into dynamics of setting the threshold and a probability of ignition detection by selfadjusting fire detectors. *Eastern-European Journal of Enterprise Technologies*, 5 (9 (89)), 43–48. doi: 10.15587/1729-4061.2017.110092

10. Shi, M., Bermak, A., Chandrasekaran, S., Amira, A., Brahim-Belhouari, S. (2008). A Committee Machine Gas Identification System Based on Dynamically Reconfigurable FPGA. *IEEE Sensors Journal*, 8 (4), 403–414. doi: 10.1109/jsen.2008.917124
11. Skinner, A. J., Lambert, M. F. (2006). Using Smart Sensor Strings for Continuous Monitoring of Temperature Stratification in Large Water Bodies. *IEEE Sensors Journal*, 6 (6), 1473–1481. doi: 10.1109/jsen.2006.881373
12. Cheon, J., Lee, J., Lee, I., Chae, Y., Yoo, Y., Han, G. (2009). A Single-Chip CMOS Smoke and Temperature Sensor for an Intelligent Fire Detector. *IEEE Sensors Journal*, 9 (8), 914–921. doi: 10.1109/jsen.2009.2024703
13. Aspey, R. A., Brazier, K. J., Spencer, J. W. (2005). Multiwavelength sensing of smoke using a polychromatic LED: Mie extinction characterization using HLS analysis. *IEEE Sensors Journal*, 5 (5), 1050–1056. doi: 10.1109/jsen.2005.845207
14. Heskestad, G., Newman, J. S. (1992). Fire detection using cross-correlations of sensor signals. *Fire Safety Journal*, 18 (4), 355–374. doi: 10.1016/0379-7112(92)90024-7
15. BS EN 54-30:2015. Fire detection and fire alarm systems. Multi-sensor fire detectors. Point detectors using a combination of carbon monoxide and heat sensors.
16. BS EN 54-31:2014. Fire detection and fire alarm system. Multi-sensor fire detectors. Point detectors using a combination of smoke, carbon monoxide and optionally heat sensors.
17. Gottuk, D. T., Wright, M. T., Wong, J. T., Pham, H. V., Rose-Pehrsson, S. L., Hart, S. et. al. (2002). Prototype Early Warning Fire Detection Systems: Test Series 4 Results. NRL/MR/6180-02-8602. Naval Research Laboratory.
18. McGrattan, K., Hostikka, S., McDermott, R., Floyd, J., Weinschenk, C., Overholt, K. (2016). Fire Dynamics Simulator Technical Reference Guide. Vol. 3. National Institute of Standards and Technology.
19. Andronov, V., Pospelov, B., Rybka, E., Skliarov, S. (2017). Examining the learning fire detectors under real conditions of application. *Eastern-European Journal of Enterprise Technologies*, 3 (9 (87)), 53–59. doi: 10.15587/1729-4061.2017.101985
20. Pospelov, B., Rybka, E., Meleshchenko, R., Gornostal, S., Shcherbak, S. (2017). Results of experimental research into correlations between hazardous factors of ignition of materials in premises. *Eastern-European Journal of Enterprise Technologies*, 6 (10 (90)), 50–56. doi: 10.15587/1729-4061.2017.117789

DOI: 10.15587/1729-4061.2018.123929

ELECTROEXTRACTION OF HEAVY METALS FROM WASTEWATER FOR THE PROTECTION OF NATURAL WATER BODIES FROM POLLUTION (p. 55-61)

Nikolai Gomelya

National Technical University of Ukraine “Igor Sikorsky Kyiv Polytechnic Institute”, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0003-1165-7545>

Ganna Trohymenko

National University of Shipbuilding, Mykolaiv, Ukraine
ORCID: <http://orcid.org/0000-0002-0835-3551>

Olena Hlushko

National Technical University of Ukraine “Igor Sikorsky Kyiv Polytechnic Institute”, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-1053-1775>

Tatiana Shablii

National Technical University of Ukraine “Igor Sikorsky Kyiv Polytechnic Institute”, Kyiv, Ukraine
ORCID: <http://orcid.org/0000-0002-6710-9874>

The most promising methods of eluates recycling are electrolysis and electro dialysis. It is possible to obtain metals and purified regeneration solutions for repeated regeneration in case of application of electrochemical methods. The processes of electrolysis of solutions of cadmium and zinc sulfates and chlorides in electrolyzers of different types were explored, the influence of conditions of electrolysis on effectiveness of extraction and separation of metals, obtaining inorganic acids for repeated usage in regeneration processes was determined.

Single- and double-chamber electrolyzers, in which cathode was made of stainless steel and titanium anode was covered with ruthenium oxide, were used. Cathodic and anodic areas in double-chamber electrolyzers were separated by the anion exchange membrane MA-41.

Solution of cadmium sulfate or of zinc sulfate was found in the cathodic chamber in double-chamber electrolyzers. Solution of sulfuric acid with concentration of 50 mg-equiv./dm³ was in the anodic chamber.

It is recommended to carry out electrolysis for two hours when using a single-chamber electrolyser at a voltage of 5 V with the purpose of removing cadmium from sulfuric acid solution and reusing regeneration solution of sulfuric acid. Almost complete removal of cadmium ions and concentration of sulfuric acid in anolyte is achieved in case of using a double-chamber electrolyser. However, in terms of power saving, release of cadmium should be performed in single-chamber electrolyzers.

However, it is recommended to perform zinc removal from eluates in double-chamber electrolyzers. In this case, zinc ions are almost completely removed within four hours at voltage of 25 V. The maximum current efficiency is 42–80 %.

Conditions of separation of zinc and cadmium in the eluate are associated with acidity of the solutions. A stage-by-stage removal of metals – cadmium followed by zinc, is observed during electrolysis of the mixture of cadmium and zinc chlorides in a single-chamber electrolyser. Current efficiency of metals is 30–68 %. In the case of electrolysis of a mixture of zinc and cadmium sulfates, only cadmium (B=100 %) is removed from the solution, while zinc ions completely remain in solution. Zinc is released only at the transfer of the electrolyte to a double-chamber electrolyser.

Keywords: ion exchange, electrochemical methods of water treatment, wastewater, used regeneration solution.

References

1. Duffus, J. H. (2002). „Heavy metals“ a meaningless term? (IUPAC Technical Report). *Pure and Applied Chemistry*, 74 (5), 793–807. doi: 10.1351/pac200274050793
2. Gomelya, N., Ivanova, V., Galimova, V., Nosachova, J., Shablii, T. (2017). Evaluation of cationite efficiency during extraction of heavy metal ions from diluted solutions. *Eastern-European Journal of Enterprise Technologies*, 5 (6 (89)), 4–10. doi: 10.15587/1729-4061.2017.109406
3. Shumilova, A. A., Trohymenko, A. G. (2012). Issledovanie vliyaniya evtrofikatsii na povtornoie zagryaznenie Bugskogo limana tyazhelymi metallami. *Visnyk Natsionalnoho universytetu korablebuduvannia*, 1, 56–62.
4. Stanko, O. M. (2012). Vazhki metaly u vodi: zabrudnennia richky Dnister za ostanni 10 rokov (terytoriya Lvivskoi oblasti). *Suchasni problemy toksykolohiyi*, 3-4, 58–63.
5. Stepanenko, T. I., Lenskiy, V. G., Demidov, I. A. (2013). Problemy ochistki stochnyh vod ot ionov tyazhelyh metallov v promyshlennyh centrakh. *Stroitel'stvo, materialovedenie, mashinostroenie. Seriya: Bezopasnost' zhiznedeyatel'nosti*, 71 (1), 205–209.
6. Ahmad, M., Usman, A. R. A., Lee, S. S., Kim, S.-C., Joo, J.-H., Yang, J. E., Ok, Y. S. (2012). Eggshell and coral wastes as low cost sorbents for the removal of Pb²⁺, Cd²⁺ and Cu²⁺ from aqueous so-

- lutions. *Journal of Industrial and Engineering Chemistry*, 18 (1), 198–204. doi: 10.1016/j.jiec.2011.11.013
7. Misdan, N., Lau, W. J., Ong, C. S., Ismail, A. F., Matsuura, T. (2015). Study on the thin film composite poly(piperazine-amide) nanofiltration membranes made of different polymeric substrates: Effect of operating conditions. *Korean Journal of Chemical Engineering*, 32 (4), 753–760. doi: 10.1007/s11814-014-0261-6
 8. Malin, V. P., Homelia, M. D., Halimova, V. M. (2016). Efektyvnist zastosovannia kationitu KU-2-8 pry vyluchenni ioniv midi z vody v prysutnosti ioniv zhorstkosti. *Problemy vodopostachannia, vodovidvedennia ta hidravliki*, 26, 45–55.
 9. Barloková, D., Ilavský, J. (2010). Removal of iron and manganese from water using filtration by natural materials. *Polish Journal of Environmental Study*, 19 (6), 1117–1122.
 10. Melnyk, L., Bessarab, O., Matko, S., Malovanyy, M. (2015). Adsorption of Heavy Metals Ions from Liquid Media by Palygorskite. *Chemistry & Chemical Technology*, 9 (4), 467–470. doi: 10.23939/chcht09.04.467
 11. Sadreeva, D. R., Ling Maung Maung, Farnosova, E. N. (2015). Ochistka stochnyh vod ot tyazhelyh metallov metodom nanofil'tracii. *Uspekhi v himii i himicheskoy tekhnologii*, 29 (2), 116–118.
 12. Fu, F., Wang, Q. (2011). Removal of heavy metal ions from wastewaters: A review. *Journal of Environmental Management*, 92 (3), 407–418. doi: 10.1016/j.jenvman.2010.11.011
 13. Barakat, M. A. (2011). New trends in removing heavy metals from industrial wastewater. *Arabian Journal of Chemistry*, 4 (4), 361–377. doi: 10.1016/j.arabjc.2010.07.019
 14. Makarenko, I. M. (2014). Electrochemical desalination of solutions, containing hardness ions. *Eastern-European Journal of Enterprise Technologies*, 4 (6 (70)), 48–53. doi: 10.15587/1729-4061.2014.26243
 15. Gomelya, N. D., Glushko, E. V., Trohimenko, A. G., Butchenko, L. I. (2017). Elektroliticheskoe izvlechenie ionov tyazhelyh metallov iz solyanokislyh rastvorov. *Energotekhnologii i resursoberezhenie*, 1, 60–67.
 16. Pikkering, U. F. (1977). *Sovremennaya analiticheskaya himiya*. Moscow: Himiya, 560.

DOI: 10.15587/1729-4061.2018.123559

RESEARCH INTO THE INFLUENCE OF VERTICAL DRAINAGE ELEMENTS ON THE OPERATIONAL EFFICIENCY OF RAPID FILTERS (p. 62-69)

Stepan Epoyan

Kharkiv National University of Civil Engineering and Architecture, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0003-4551-1309>

Andrey Karahiaur

Kharkiv National University of Civil Engineering and Architecture, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0002-8868-3189>

Vladlen Volkov

Kharkiv National University of Civil Engineering and Architecture, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0001-8419-9878>

Svetlana Babenko

Kharkiv National University of Civil Engineering and Architecture, Kharkiv, Ukraine
ORCID: <http://orcid.org/0000-0001-7918-1737>

To improve the efficiency of removal of suspended solids at rapid filters, we designed improved structure of the device. The improvement is based on the application, simultaneously with a granular filter layer, of vertical drainage elements with porous fibrous shells.

Such a solution makes it possible to shift part of the load to the shells of drainage elements, reduce colmatation and head losses in a granular filter layer, as well as to more evenly distribute contaminants along its height. This increases the duration of operation of the filter under filtering mode and brings down the cost of regeneration of a filter layer. A filtration equation was derived to describe parallel filtration of a low-concentrated suspension through a granular medium and a fibrous medium. The mathematical model also includes equations of mass transfer, mass exchange and dependences to account for the impact of colmatation and parameters of filtering media. For a granular filter layer, we considered filtering with a gradual blocking of pores; for a porous shell – the formation of a sediment layer at its surface. Using a mathematical model, we conducted numerical experiments. The following significant parameters for the filter with improved design were determined: equivalent diameter of particles in a filter layer, working height of the vertical drainage element, duration of washing a porous fibrous shell. We give examples of calculations for determining the values of basic parameters at which the effectiveness of application of vertical drainage elements is maximal.

Keywords: rapid filter, vertical drainage element, porous fibrous shell.

References

1. Zhurba, M. G., Sokolov, L. I., Govorova, G. M. (2010). *Water supply. Designing systems and structures. Vol. 2. Purification and conditioning of natural waters*. Moscow: Publishing house of the Association of Construction Universities, 552.
2. Huck, P. M., Sozanski, M. M. (2012). *Designing and Optimizing Drinking Water Treatment Processes – A Guide to Conducting Investigations*. IWA Publishing, 200.
3. Grabovsky, P. A., Larkina, G. M., Progulny, V. I. (2012). *Washing of water purification filters*. Odessa: Optimum, 240.
4. Kulikov, N. I., Naimanov, A. Y., Omelchenko, N. P., Chernyshev, V. N. (2009). *Theoretical basis of water purification*. Donetsk: Publishing house Nouvelage (Donetsk branch), 298.
5. Gurinchik, N. A. (2014). Investigation of the influence of the composition of a media of a contact clarifier using a mathematical model. *Municipal economy of cities*, 114, 105–108.
6. Adelman, M., Liu, M., Cordero, A., Ayala, J. (2010). *Stacked Rapid Sand Filtration*. Cornell University. Available at: <https://confluence.cornell.edu/display/AGUACLARA/Stacked+Rapid+Sand+Filtration+Summer+2010+Reflection+Report+1>
7. Karahiaur, A. S., Volkov, V. N. (2017). Mathematical modeling of the operation rapid filter with the bypass of part of the flow to the lower layers. *Scientific Bulletin of Civil Engineering*, 90 (4), 180–187.
8. Schevchuk, O. O. (2006). Mathematical description of multistage filtration. *Filtration and Separation: the 2nd European Conf. Compiegne*, 259–265.
9. Pabolkov, V. V. (2015). Improvement of the work of rapid filters of water treatment facilities during preparation of drinking water. *Kharkiv: KhNUCA*, 20.
10. Sabiri, N.-E., Monnier, E., Raimbault, V., Massé, A., Séchet, V., Jaouen, P. (2016). Effect of filtration rate on coal-sand dual-media filter performances for microalgae removal. *Environmental Technology*, 38 (3), 345–352. doi: 10.1080/09593330.2016.1193224
11. Zhang, G., Kang, X., Zhang, P., Zeng, G. (2011). Pilot study of low-temperature low-turbidity reservoir water treatment using dual-media filtration with micro-flocculation. *2011 International Conference on Multimedia Technology*. doi: 10.1109/icmt.2011.6002915
12. Odira, P. M. A., Ndiba, P. K. (2007). Performance of Crushed Coconut Shell Dual Media Filter. *Journal of Civil Engineering Research and Practice*, 4 (2). doi: 10.4314/jcerp.v4i2.29176
13. Jusoh, A., Rajiah, M. N. A., Nora'aini, A., Azizah, E. (2011). Determination of head loss progress in dual-media BOPS-sand filter

- using numerical modeling incorporated with matrix approach. *Desalination and Water Treatment*, 32 (1-3), 33–41. doi: 10.5004/dwt.2011.2675
14. Sanyaolu, B. O. (2010). Comparative performance of a charcoal dual media filter and a conventional rapid sand filter. *Journal of Natural Sciences Engineering and Technology*, 9 (1), 137–146.
 15. Soyer, E. (2016). Performance comparison of granular media filter beds. *Desalination and Water Treatment*, 57 (52), 24867–24881. doi: 10.1080/19443994.2016.1150206
 16. Schöntag, J. M., Sens, M. L. (2015). Effective production of rapid filters with polystyrene granules as a media filter. *Water Science and Technology: Water Supply*, 15 (5), 1088–1098. doi: 10.2166/ws.2015.072
 17. Gawade, S., Misal, S. (2016). Analysis of PVC rapid sand filter. *Imperial Journal of Interdisciplinary Research*, 2 (9), 1370–1373.
 18. Bugay, N. G., Krivonog, A. I., Krivonog, V. V. (2007). Contact reagent purification of water by filters of fibrous-porous polyethylene. *Applied hydromechanics*, 9 (1), 8–22.
 19. Epoyan, S., Karahiaur, A., Volkov, V., Yarkin, V. (2016). Improving the efficiency of filter structures using drainage systems made of porous polymer materials. *MOTROL. Commission of motorization and energetics in agriculture*, 18 (6), 102–109.
 20. Polyakov, V. L. (2009). Filtration of a suspension with variable content of suspended particles through a uniform filter medium at a nonlinear mass-exchange kinetics. *Reports of the National Academy of Sciences of Ukraine*, 12, 61–68.
 21. Noskov, M. D., Zaytseva, M. S., Istomin, A. D., Lukashevich, O. D. (2008). Mathematical modeling of the operation of rapid filters. *Vestnik of TSUAB*, 2, 126–138.
 22. Shilin, B. I., Ulianov, A. A. (2016). Development of porous structure model of fibrous materials of filters of volumetric type for clearing of surface water. *Biospheric compatibility: human, region, technologies*, 4 (16), 71–78.
 23. Nabovati, A., Llewellyn, E. W., Sousa, A. C. M. (2009). A general model for the permeability of fibrous porous media based on fluid flow simulations using the lattice Boltzmann method. *Composites Part A: Applied Science and Manufacturing*, 40 (6-7), 860–869. doi: 10.1016/j.compositesa.2009.04.009
 24. Volkov, V. M., Epoyan, S. M., Karahiaur, A. S., Babenko, S. P. (2017). Using polymeric shells of the drainage systems of rapid filters for tertiary treatment. *Municipal economy of cities*, 139, 135–142.
 25. Oleynik, A. Ya., Tugay, A. M. (2001). Modeling of the processes of colmatage and suffosion in the filter zone of wells. *Reports of the National Academy of Sciences of Ukraine*, 9, 190–194.