

DOI: 10.15587/1729-4061.2019.169258

### RATIONALE FOR CREATING DETONATION CO<sub>2</sub> LASER FOR RADIOACTIVE SURFACE DECONTAMINATION (p. 6-12)

**Alexander Galak**National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, UkraineORCID: <http://orcid.org/0000-0002-2590-9291>**Oleh Kravchuk**

Odessa Military Academy, Odessa, Ukraine

ORCID: <http://orcid.org/0000-0002-7590-4210>**Serhii Petrukhin**National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, UkraineORCID: <http://orcid.org/0000-0003-4228-4622>**Alexey Klimov**National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, UkraineORCID: <http://orcid.org/0000-0003-0727-2976>**Serhii Kasian**National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, UkraineORCID: <http://orcid.org/0000-0003-4948-4029>**Aleksii Blekot**Ivan Chernyakhovsky National Defense University of Ukraine,  
Kyiv, UkraineORCID: <http://orcid.org/0000-0002-1623-8940>**Anatolii Nikitin**Ivan Chernyakhovsky National Defense University of Ukraine,  
Kyiv, UkraineORCID: <http://orcid.org/0000-0003-1487-0616>**Volodymyr Kotsiuruba**Ivan Chernyakhovsky National Defense University of Ukraine,  
Kyiv, UkraineORCID: <http://orcid.org/0000-0001-6565-9576>

The laser decontamination method is based on the evaporation of oxide films under the influence of radiation. With the evaporation mechanism, laser radiation should heat the upper layer of the film to the boiling point during the pulse and evaporate it. It is relevant because of the growing environmental requirements in the world, which makes it possible to create a compact, energy-efficient laser installation. Unlike existing energy-efficient laser units, the detonation laser system will significantly affect and quickly decontaminate radioactive surfaces due to the evaporation of oxide films under the influence of radiation. Detonation technologies are critical and can be used for pulse detonation systems, such as pulse detonation engines, detonation lasers, magnetohydrodynamic generators with detonation combustion of fuel, volume explosion initiation systems. The introduction of these systems in armaments and military equipment can substantially change the scope of their application. The average laser power can exceed 100 kW and above. At the same time, the use of the mixture as a power source makes the system not only compact, but also light in weight with respect to the existing similar systems. The wavelength will be 10.6 μm due to radiation in the far infrared region. That is, combined power plants will provide not only

actuation, but also electric power supply of machines. This will allow the creation of power detonation units with a periodic initiation frequency of at least 100 Hz, which will work on a liquefied mixture and insignificant use of oxygen in the incendiary portion.

**Keywords:** spark discharge, pre-ionization, current-conducting channel, lasers, detonation, decontamination, laser radiation, voltage.

#### References

- Galak, A. V. (2014). The applying of the detonation carbon oxygen lasers for deactivation. *Zbirnyk naukovykh prats Kharkivskoho universytetu Povitrianykh syl*, 1, 241–245.
- Veiko, V. P., Shakhno, E. A., Smirnov, V. N., Myaskovskii, A. M., Borovskikh, S. S., Nikishin, G. D. (2007). Laser decontamination of metallic surfaces. *Journal of Optical Technology*, 74 (8), 536. doi: <https://doi.org/10.1364/jot.74.000536>
- Blohin, O. A., Vostrikov, V. G., Krasnyukov, A. G. et. al. (2001). Mobil'nyy lazerniy kompleks dlya avariynno vosstanovitel'nykh rabot v gazovoy promyshlennosti. *Gazovaya promyshlennost'*, 33–34.
- Stem, R. C., Pdsner, J. A. (1985). Atomic Vapor Laser Isotope Separation. *First International Laser Science Conference*, 8.
- Pat. No. US5624654 A. Gas generating system for chemical lasers (1996). No. 5,624,654 USA. declared: 13.05.1996; published: 29.04.1997.
- Savina, M., Xu, Z., Wang, Y., Reed, C., Pellin, M. (2000). Efficiency of concrete removal with a pulsed Nd:YAG laser. *Journal of Laser Applications*, 12 (5), 200. doi: <https://doi.org/10.2351/1.1309551>
- Latham, W. P., Rothenflue, J. A., Helms, C. A., Kar, A., Carroll, D. L. (1998). Cutting performance of a chemical oxygen-iodine laser. *Gas and Chemical Lasers and Intense Beam Applications*. doi: <https://doi.org/10.1117/12.308059>
- Pat. No. 5011049/25 Frantsiya. Sposob dezaktivatsii poverhnosti, raspolozhennoy v zone radioaktivnogo zagryazneniya yadernoy ustanovki (1992). No. 2084978; declared: 24.03.1992; published: 20.07.1997, Bul. No. 16.
- Miljanic, S., Stjepanovic, N., Trtica, M. (2000). An attempt to use a pulsed CO<sub>2</sub> laser for decontamination of radioactive metal surfaces. *Journal of the Serbian Chemical Society*, 65 (5-6), 445–450. doi: <https://doi.org/10.2298/jsc0006445m>
- Potiens, A. J., Dellamano, J. C., Vicente, R., Ruele, M. P., Wetter, N. U., Landulfo E. (2014). Laser decontamination of the radioactive lightning rods. *Radiation Physics and Chemistry*, 95, 188–190. doi: <https://doi.org/10.1016/j.radphyschem.2013.03.043>
- Kumar, A., Prakash, T., Prasad, M., Shail, S., Bhatt, R. B., Behere, P. G., Biswas, D. J. (2017). Laser assisted removal of fixed radioactive contamination from metallic substrate. *Nuclear Engineering and Design*, 320, 183–186. doi: <https://doi.org/10.1016/j.nucengdes.2017.06.003>
- Delaporte, P., Gastaud, M., Marine, W., Sentis, M., Uetez, O., Thouvenot, P. et. al. (2002). Radioactive oxide removal by XeCl laser. *Applied Surface Science*, 197–198, 826–830. doi: [https://doi.org/10.1016/s0169-4332\(02\)00456-7](https://doi.org/10.1016/s0169-4332(02)00456-7)
- Delaporte, P., Gastaud, M., Marine, W., Sentis, M., Uetez, O., Thouvenot, P. et. al. (2003). Dry excimer laser cleaning applied to nuclear decontamination. *Applied Surface Science*, 208–209, 298–305. doi: [https://doi.org/10.1016/s0169-4332\(02\)01360-0](https://doi.org/10.1016/s0169-4332(02)01360-0)
- Dzhidzhoev, M. S. (1971). Detonatsionnyy gazodinamicheskiy lazer. *Pis'ma v ZhETF*, 13, 73–76.
- Bazhenova, T. V., Golub, V. V. (2003). Ispol'zovanie gazovoy detonatsii v upravlyaemom chastotnom rezhime (obzor). *Fizika goreniya i vzryva*, 4, 3–21.

16. Korytchenko, K. V., Galak, A. V. (2011). Uovershenstvovannyi metod rascheta dinamiki vvoda energii v iskrovoy kanal po krivoy razryadnogo toka. *Prikladnaya radioelektronika*, 10 (1), 51–59.
17. Gelfand, B. E. (2002). Predely detonatsii vozdushnykh smesy dvukh-komponentnymi gazoobraznymi goryuchimi veschestvami. *Fizika goreniya i vzryva*, 38 (5), 101–104.
18. Korytchenko, K. V., Bolyuh, V. F., Galak, A. V. (2011). Eksperimental'noe issledovanie effektivnosti vvoda energii v gazonom razryade s predionizatsiey. *Prikladnaya radioelektronika*, 10 (3), 361–367.
19. Korytchenko, K. V., Bolyukh, V. F., Galak, O. V. (2011). Validation of dynamics of energy input into a gas-discharge channel by modeling of spark-discharge gas detonation initiation. *Elektrotehnika i elektromekhanika*, 3, 70–73.
20. Galak, A. V., Karlov, D. V., Chernyviskiy, O. U., Sinko, A. G. (2013). The ways of development of laser weapon yesterday, today, tomorrow. *Nauka i tekhnika Povitrianykh Syl Zbroinykh Syl Ukrainy*, 4 (13), 123–130.
21. Galak, A. V. (2014). Prospects of development of pulse detonation engines. Difficulties of their realization. *Systemy ozbroieniya i viyskova tekhnika*, 2, 73–76.

DOI: 10.15587/1729-4061.2019.168712

**DETERMINING HIGH QUASIHYDROSTATIC PRESSURE UP TO 7 hPa AT A TEMPERATURE TO 1,400 °C USING RESISTIVE SENSORS (p. 13-20)**

**Sergey Ivakhnenko**

V. Bakul Institute for Superhard Materials of the National Academy of Sciences of Ukraine, Kyiv, Ukraine  
**ORCID:** <http://orcid.org/0000-0001-9243-9982>

**Valentyn Lysakovskiy**

V. Bakul Institute for Superhard Materials of the National Academy of Sciences of Ukraine, Kyiv, Ukraine  
**ORCID:** <http://orcid.org/0000-0003-4306-9115>

**Oleksandr Savitskiy**

V. Bakul Institute for Superhard Materials of the National Academy of Sciences of Ukraine, Kyiv, Ukraine  
**ORCID:** <http://orcid.org/0000-0002-2092-8450>

**Andrii Burchenia**

V. Bakul Institute for Superhard Materials of the National Academy of Sciences of Ukraine, Kyiv, Ukraine  
**ORCID:** <http://orcid.org/0000-0003-2463-0202>

A differential method for measuring high quasi-hydrostatic pressures for six-punch pressing installations has been constructed by building a load-carrying characteristic  $p=f(Q)$ , where  $p$  is the value for pressure in a quasi-hydrostatic cell of high-pressure,  $Q$  is the force of the press. Pressure in the cell is measured by using the measurement of a temperature difference between the polymorphic transformations into  $Co(\alpha \rightarrow \beta)$  and  $Fe(\alpha \rightarrow \gamma)$ , melting of Cu and Ag; the measurements are performed by resistometry. The initial data used were the lines of polymorphic transitions in iron (BCC–FCC) and cobalt (FCC–HCP) within the ranges  $p=4\text{--}7$  hPa and  $T=500\text{--}700$  °C, examined in detail earlier in the  $p$ ,  $T$ -diagrams, as well as copper and silver melting curves at  $p=4\text{--}7$  and  $T=1,150\text{--}1,400$  °C.

The database of initial data is represented in the analytical form, which has made it possible to use them to determine pressure in the cell at high temperatures based on the values for magnitudes of the differential temperature difference  $\Delta T_d$ , which was measured experimentally for the  $Co^{\alpha-\beta}$ – $Fe^{\alpha-\gamma}$  and  $Ag^L$ – $Cu^L$  sensors, designed in the current paper; we have described the features in assembling dif-

ferential sensors and their electrical connections in order to perform the process of measuring the magnitudes for  $\Delta T_d$ . We have designed structures for the high-pressure cells to conduct experiments on measuring  $\Delta T_d$  using thermocouples and a circuit that registers a change in the resistance of sensors at phase transformations.

The procedure applied has made it possible to determine pressure in the quasi-hydrostatic cells of six-punch setups by building load characteristics. The main benefits of the devised method for measuring quasi-hydrostatic pressures by resistometry are its relative simplicity and a significant increase in the accuracy of pressure determination. The latter is achieved through the mutual elimination of corrections of pressure impact and parasitic components for the magnitude of thermo-EMF of thermocouples in determining the values for a temperature of phase transformations in the resistive sensors Co–Fe and Ag–Cu.

The data obtained could be used for monitoring and measuring pressures in the cells of six-punch pressing installations with a plunger diameter of 560–950 mm.

**Keywords:** high quasi-hydrostatic pressures, six-punch high-pressure unit, resistive pressure sensor.

**References**

1. Novikov, N. V. (1986). *Sinteticheskie sverhtverdye materialy*. Vol. 1. Sintez sverhtverdykh materialov. Kyiv: Naukova dumka, 280.
2. Wang, Y., Durham, W. B., Getting, I. C., Weidner, D. J. (2003). The deformation-DIA: A new apparatus for high temperature triaxial deformation to pressures up to 15 GPa. *Review of Scientific Instruments*, 74 (6), 3002–3011. doi: <https://doi.org/10.1063/1.1570948>
3. Kawazoe, T., Nishiyama, N., Nishihara, Y., Irifune, T. (2010). Pressure generation to 25 GPa using a cubic anvil apparatus with a multi-anvil 6-6 assembly. *High Pressure Research*, 30 (1), 167–174. doi: <https://doi.org/10.1080/08957950903503912>
4. Tonkov, E. Yu. (1979). *Fazovye diagrammy elementov pri vysokom davlenii*. Moscow: Nauka, Glavnaya redaktsiya fiziko-matematicheskoy literatury, 192.
5. Liebermann, R. C. (2011). Multi-anvil, high pressure apparatus: a half-century of development and progress. *High Pressure Research*, 31 (4), 493–532. doi: <https://doi.org/10.1080/08957959.2011.618698>
6. Stupnikov, V. A., Bulychev, B. M. (2012). *Vysokie davleniya v himii*. *Almaz i almazopodobnye materialy, tekhnicheskie i sinteticheskie aspekty*. Moscow: MGU im. M. V. Lomonosova, 112.
7. Bogdanov, S. P. (2008). Rol' razmera kristallitov grafitopodobnogo nitrda bora pri nukleatsii kubicheskogo nitrda bora. *Fizika i himiya stekla*, 34 (2), 274–280.
8. Cubic Press Machine Catalog. Guilin Guiye Machinery Co., Ltd. Available at: <https://glguiye.en.made-in-china.com/Product-Catalogs/>
9. *Metodika differentsial'nogo termicheskogo analiza pri davleniyah do 8GPa* (1989). Kyiv, 16.
10. Getting, I. C., Kennedy, G. C. (1970). Effect of Pressure on the emf of Chromel-Alumel and Platinum-Platinum 10% Rhodium Thermocouples. *Journal of Applied Physics*, 41 (11), 4552–4562. doi: <https://doi.org/10.1063/1.1658495>
11. Hanneman, R. E., Strong, H. M. (1966). Pressure Dependence of the emf of Thermocouples. *Journal of Applied Physics*, 37 (2), 612–614. doi: <https://doi.org/10.1063/1.1708224>
12. Pat. No. 132612 UA. Sposib kalibruvannya vysokoho tysku do 6,5HPa v konteinerakh iz kvazihidrostatychnymy peredavalnymy seredovyshchamy shestypuansonnnykh kubichnykh presiv (2019). MPK B01J 3/06. No. u201806114; declared: 01.06.2018; published: 11.03.2019, Bul. No. 5.
13. Sonin, V. M., Sokol, A. G. (1993). *Razrabotka DTA na monogopuansonnnykh aparate vysokogo davleniya*. *Eksperimental'nye issle-*

- dovaniya kristallizatsii almaza v metallicheskih sistemah. Novosibirsk, 78–82.
14. Novikov, N. V., Ivahenko, C. A., Chipenko, G. V., Belousov, I. S. (1990). Izmerenie vysokih kvazigidrostaticeskikh davleniy do 7 GPa differentsial'nym metodom pri temperaturah do 1400 °C. Dokl. AN SSSR, 311 (6), 1368–1371.
  15. Ivahnenko, S. I., Chipenko, G. V., Belouov, I. S., Zanevskiy, O. A. (1987). Izmerenie davleniya differentsial'nym metodom po krivym plavleniya svintsa i tsinka. Obrabotka materialov pri vysokom davlenii. Sbornik nauchnykh trudov AN USSR, IPM AN USSR.
  16. Claussen, W. F.; Giardini, A. A., Lloyd, E. C. (Eds.) (1963). High Pressure Measurement. Washington: Butterworths, 125.
  17. Kenedi, D., N'yuton, R. V.; Vinogradov, A. P. (Ed.) (1966). Tverdye tela pod vysokim davleniem. Moscow: Mir, 167.
  18. Kaufman, L., Clougherty, E. V., Weiss, R. J. (1963). The lattice stability of metals – III. Iron. Acta Metallurgica, 11 (5), 323–335. doi: [https://doi.org/10.1016/0001-6160\(63\)90157-3](https://doi.org/10.1016/0001-6160(63)90157-3)
  19. Bundy, F. P., Strong, H. M. (1962). Behavior of Metals at High Temperatures and Pressures. Solid State Physics, 81–146. doi: [https://doi.org/10.1016/s0081-1947\(08\)60456-7](https://doi.org/10.1016/s0081-1947(08)60456-7)
  20. Akella, J., Kennedy, G. C. (1971). Melting of gold, silver, and copper-proposal for a new high-pressure calibration scale. Journal of Geophysical Research, 76 (20), 4969–4977. doi: <https://doi.org/10.1029/jb076i020p04969>
  21. Batavin, V. V., Kontsevoy, Yu. A., Fedorovich, Yu. V. (1985). Izmernie parametrov poluprovodnikovyykh materialov i struktur. Moscow: Radio i svyaz', 264.

DOI: 10.15587/1729-4061.2019.167046

#### IDENTIFICATION OF ENERGY EFFICIENCY OF ORE GRINDING AND THE LINER WEAR BY A THREE-PHASE MOTION OF BALLS IN A MILL (p. 21-28)

**Vasyl Kondratets**

Central Ukrainian National Technical University,  
Kropyvnytskyi, Ukraine  
ORCID: <http://orcid.org/0000-0002-1411-168X>

**Anatolii Matsui**

Central Ukrainian National Technical University,  
Kropyvnytskyi, Ukraine  
ORCID: <http://orcid.org/0000-0001-5544-0175>

**Volodymyr Yatsun**

Central Ukrainian National Technical University,  
Kropyvnytskyi, Ukraine  
ORCID: <http://orcid.org/0000-0003-4973-3080>

**Mihail Lichuk**

Central Ukrainian National Technical University,  
Kropyvnytskyi, Ukraine  
ORCID: <http://orcid.org/0000-0003-4357-2626>

We have analytically derived an equation that relates the technological parameters of a ball mill, grinding material, to the parameters of a rod primary converter of energy efficiency of ore grinding. By using a method of applying a basic rod primary converter with a large cross-sectional area, at the side end of which large pieces of ore are destroyed at balls impacts, and an additional rod converter with identical parameters and a smaller cross-sectional area, which interacts only with balls, we have achieved invariance in determining the energy efficiency of ore grinding by a ball mill to a change in the motion speed of grinding bodies. We have analytically derived a mathematical model of energy-saving ore grinding by a ball mill with a three-phase motion of grinding bodies, invariant to a change in the length of rods during wear. The model can estimate

the energy efficiency of grinding larger pieces of ore based on the resulting volume of crushed large-lump material. The mathematical model includes such constants as the cross-sectional areas of rod primary converters, the initial length of rod primary converters, the length of a basic section of strain gauges arrangement, the value for Young's modulus of the primary converters' material, as well as the changing constants that are defined by the ground material. In addition, the dependence has been derived analytically for determining the length of a main rod primary converter, based on which one can estimate the height of a liner, which wears out in the course of operation.

We have devised a functional circuit for the automated control system of energy efficiency of ore grinding by a ball mill that makes it possible to obtain estimation parameters using modern microprocessor tools. According to the devised circuit, one can build algorithms for determining the volume of ore to be crushed, as well as the thickness of a liner in a ball mill, which open up an avenue for developing software products.

Computer simulation has proven the possibility of applying the proposed method in order to estimate energy efficiency of ore grinding by a ball mill with a three-phase ball motion. We have established high sensitivity of the proposed approach to a deviation in energy efficiency of ore grinding from the best value. A possibility to estimate the parameter with a relative error of  $\pm 2.5\%$  has been confirmed.

**Keywords:** energy efficiency, automated control, ore grinding, ball mill, elastic converters.

#### References

1. Shinkorenko, S. F. (2002). Gidromekhanika rabochey sredy sharovykh mel'nic mokrogo izmel'cheniya. Gorniy zhurnal, 7, 19–24.
2. Naumenko, Yu. V. (2014). Osnovy teoriiy rezhymiv roboty baraban-nykh mlyniv. Rivne: NUVHP, 336.
3. Sanfratello, L., Caprihan, A., Fukushima, E. (2006). Velocity depth profile of granular matter in a horizontal rotating drum. Granular Matter, 9 (1-2), 1–6. doi: <https://doi.org/10.1007/s10035-006-0023-1>
4. Yang, R. Y., Yu, A. B., McElroy, L., Bao, J. (2008). Numerical simulation of particle dynamics in different flow regimes in a rotating drum. Powder Technology, 188 (2), 170–177. doi: <https://doi.org/10.1016/j.powtec.2008.04.081>
5. McElroy, L., Bao, J., Yang, R. Y., Yu, A. B. (2009). A soft-sensor approach to flow regime detection for milling processes. Powder Technology, 188 (3), 234–241. doi: <https://doi.org/10.1016/j.powtec.2008.05.002>
6. Kondratets, V. (2014). Adaptive control of ore pulp thinning in ball mills with the increase of their productivity. Metallurgical and Mining Industry, 6, 12–15.
7. Morozov, V. V., Topchaev, V. P., Ulitenko, K. Ya., Ganbaatar, Z., Delgerbat, L. (2013). Razrabotka i primeneniye avtomatizirovannykh sistem upravleniya processami obogascheniya poleznykh iskopaemykh. Moscow: Izd. dom «Ruda i Metally», 512.
8. Tang, J., Yu, W., Chai, T., Liu, Z., Zhou, X. (2016). Selective ensemble modeling load parameters of ball mill based on multi-scale frequency spectral features and sphere criterion. Mechanical Systems and Signal Processing, 66-67, 485–504. doi: <https://doi.org/10.1016/j.ymssp.2015.04.028>
9. Pedrayes, F., Norniella, J. G., Melero, M. G., Menéndez-Aguado, J. M., del Coz-Díaz, J. J. (2018). Frequency domain characterization of torque in tumbling ball mills using DEM modelling: Application to filling level monitoring. Powder Technology, 323, 433–444. doi: <https://doi.org/10.1016/j.powtec.2017.10.026>
10. Roux, J. D. le, Craig, I. K. (2017). Requirements for estimating the volume of rocks and balls in a grinding mill. IFAC-PapersOnLine, 50 (1), 1169–1174. doi: <https://doi.org/10.1016/j.ifacol.2017.08.403>

11. Rezaeizadeh, M., Fooladi, M., Powell, M. S., Mansouri, S. H., Weerasekara N. S. (2010). A new predictive model of lifter bar wear in mills. *Minerals Engineering*, 23 (15), 1174–1181. doi: <https://doi.org/10.1016/j.mineng.2010.07.016>
12. Pivnyak, G. G., Vaysberg, L. A., Kirichenko, V. I., Pilov, P. I., Kirichenko, V. V. (2007). *Izmel'chenie. Energetika i tekhnologiya*. Moscow: Izd. dom «Ruda i metally», 296.
13. Nikitin, S. V., Karelina, M. Yu. (2014). *Prikladnaya mekhanika. Ch. 1. Soprotivlenie materialov*. Moscow: MADI, 244.
14. Andreev, S. E., Perov, V. A., Zverevich, V. V. (1980). *Droblenie, izmel'chenie i grohochenie poleznykh iskopaemykh*. Moscow: Nedra, 415.
15. Deshko, Yu. I., Kreymer, M. B., Kryhtin, G. S. (1966). *Izmel'chenie materialov v cementnoy promyshlennosti*. Moscow: Stroyizdat, 270.
16. Bogdanov, V. S., Hahalev, P. A. (2014). Vliyanie profilya konusno-volnistoy futerovki barabannykh mel'nic na energeticheskije pokazately sharovoy zagruzki. *Cement i ego primenenie*, 2, 93–97.
17. Motra, H. B., Hildebrand, J., Dimmig-Osburg, A. (2014). Assessment of strain measurement techniques to characterise mechanical properties of structural steel. *Engineering Science and Technology, an International Journal*, 17 (4), 260–269. doi: <https://doi.org/10.1016/j.jestch.2014.07.006>
18. Yurdem, H., Degirmencioglu, A., Cakir, E., Gulsoylu, E. (2019). Measurement of strains induced on a three-bottom moldboard plough under load and comparisons with finite element simulations. *Measurement*, 136, 594–602. doi: <https://doi.org/10.1016/j.measurement.2019.01.011>
19. Zhou, K., Wu, Z. Y. (2017). Strain gauge placement optimization for structural performance assessment. *Engineering Structures*, 141, 184–197. doi: <https://doi.org/10.1016/j.engstruct.2017.03.031>

**DOI: 10.15587/1729-4061.2019.170341**  
**USING THE INTENSITY OF ABSORBED GAMMA RADIATION TO CONTROL THE CONTENT OF IRON IN ORE (p. 29-35)**

**Albert Azaryan**

Kryvyi Rih National University, Kryvyi Rih, Ukraine  
**ORCID:** <http://orcid.org/0000-0002-1381-579X>

**Andrey Gritsenko**

Kryvyi Rih National University, Kryvyi Rih, Ukraine  
**ORCID:** <http://orcid.org/0000-0003-4526-5486>

**Annait Trachuk**

Kryvyi Rih National University, Kryvyi Rih, Ukraine  
**ORCID:** <http://orcid.org/0000-0001-6241-1575>

**Vadim Serebrenikov**

Donetsk National University of Economics and Trade named after Mikhail Tugan-Baranovsky, Kryvyi Rih, Ukraine  
**ORCID:** <http://orcid.org/0000-0002-5490-5601>

**Dmitriy Shvets**

Kryvyi Rih National University, Kryvyi Rih, Ukraine  
**ORCID:** <http://orcid.org/0000-0001-5126-6405>

The paper reports results of mathematical modeling of the intensity of absorbed gamma radiation for determining the iron content in IOR. It was shown that to enhance the accuracy of rapid control of the iron content in IOR, it is advisable to use absorbed gamma radiation. This approach is the improvement of the nuclear-physical method for determining the iron content in IOR. Reflected gamma radiation is used in the existing nuclear-physical methods for determining the iron content in IOR. The gamma-gamma method, the feature of which is the use of “soft” gamma radiation, is used in this method. This leads to the fact that the irradiated surface reflects only

a small part of the original flux of gamma radiation. As a result, measuring the intensity of the scattered gamma radiation is characterized by substantial relative errors and, consequently, low-precision of rapid control of iron content in IOR. The use of absorbed gamma radiation as the main part of gamma radiation, makes it possible to significantly reduce the relative error of measurement of the intensity of gamma radiation, that is, to enhance the accuracy of rapid control of the iron content in IOR.

The work considered the method of “central geometry” for measuring the intensity of gamma radiation as the most common. This method makes it possible to take into consideration in the mathematical model the dependence of the intensity of absorbed gamma radiation not only on the properties of irradiated surface of rock mass, but also on the geometric parameters in measurement. The main feature of the model is the use of albedo parameter, which allows linking the scattered and absorbed gamma radiation. Representation of the synthesized model in the dimensionless form enabled both simplification of calculations, and generalization of the results of mathematical modeling of the intensity of absorbed gamma radiation. In order to compare the values of intensities of reflected and absorbed gamma-radiation in terms of central geometry, the appropriate numerical calculations were performed. The results of the conducted calculations proved the effectiveness of using absorbed gamma radiation to determine the iron content in IOR. Thus, in the range of 50–60 percent of the iron content, the sensitivity of absorbed gamma-radiation is considerably higher (by two times) than sensitivity of scattered gamma radiation.

**Keywords:** rapid control, absorbed, scattered gamma-quanta, nuclear-physical method, detector, albedo.

#### References

1. Ibraheem, A. A., Alghatani, F. (2018). Analysis of alpha particles scattered from  $^{32}\text{S}$  at 386 MeV. *AIP Conference Proceedings*, 1976, 020022. doi: <https://doi.org/10.1063/1.5042389>
2. Kiran, K. U., Ravindraswami, K., Eshwarappa, K. M., Somashekharappa, H. M. (2015). Experimental and simulated study of detector collimation for a portable 3”×3” NaI(Tl) detector system for in-situ measurements. *Journal of Radiation Research and Applied Sciences*, 8 (4), 597–605. doi: <https://doi.org/10.1016/j.jrras.2015.07.006>
3. Çelik, N., Çevik, U., Çelik, A. (2012). Effect of detector collimation on the measured mass attenuation coefficients of some elements for 59.5–661.6keV gamma-rays. *Nuclear Instruments and Methods in Physics Research Section B: Beam Interactions with Materials and Atoms*, 281, 8–14. doi: <https://doi.org/10.1016/j.nimb.2012.04.003>
4. Makek, M., Bosnar, D., Pavelić, L. (2019). Scintillator Pixel Detectors for Measurement of Compton Scattering. *Condensed Matter*, 4 (1), 24. doi: <https://doi.org/10.3390/condmat4010024>
5. Diaz-H, K. V., Cristancho, F. (2016). Effect of sample thickness on 511 keV single Compton-scattered gamma rays. *AIP Conference Proceedings*, 1753, 080001. doi: <https://doi.org/10.1063/1.4955371>
6. Flechas, D., Sarmiento, L. G., González, N., Gómez-Muñoz, J., Garzón, C., Fajardo, E., Cristancho, F. (2016). The application possibilities of the gamma-ray Compton backscattering technique. *AIP Conference Proceedings*, 1529, 40. doi: <https://doi.org/10.1063/1.4804078>
7. Azaryan, A. A., Azaryan, V. A., Trachuk, A. A., Gritsenko, A. N., Serebrenikov, V. M. (2018). Mathematical model of interaction of gamma radiation with rocks as a source of information on the content of iron in the logging of blast holes. *XXXIII Mizhnarodna konferentsiya «Rozvytok nauky v XXI stolitti»*. Kharkiv, 40–48.
8. Azaryan, A., Gritsenko, A., Trachuk, A., Shvets, D. (2018). Development of the method to operatively control quality of iron ore raw materials at open and underground extraction. *Eastern-European*

- Journal of Enterprise Technologies, 5 (5 (95)), 13–19. doi: <https://doi.org/10.15587/1729-4061.2018.144003>
9. Azaryan, A. A., Dryga, V. V., Tsybulevskiy, Yu. E. (2005). Issledovanie avtogeneratednogo metoda kontrolya sodержaniya zheleza magnitnogo v produktah obogascheniya. *Kachestvo mineral'nogo syr'ya*, 117–123.
  10. Morkun, V., Morkun, N., Pikilnyak, A. (2015). The study of volume ultrasonic waves propagation in the gas-containing iron ore pulp. *Ultrasonics*, 56, 340–343. doi: <https://doi.org/10.1016/j.ultras.2014.08.022>
  11. Shayakhmetov, B., Issagulov, A., Baisanov, A., Karakeyeva, G., Issagulova, D. (2014). Studying phase structure of burned ferrous manganese ores by method of nuclear gamma-resonance spectroscopy. *Metalurgiya*, 53 (2), 231–234.
  12. Manjunatha, M., Kumar, R., Anupama, A. V., Khopkar, V. B., Damle, R., Ramesh, K. P., Sahoo, B. (2019). XRD, internal field-NMR and Mössbauer spectroscopy study of composition, structure and magnetic properties of iron oxide phases in iron ores. *Journal of Materials Research and Technology*, 8 (2), 2192–2200. doi: <https://doi.org/10.1016/j.jmrt.2019.01.022>
  13. Mashkovich, V. P., Kudryavtseva, A. V. (1995). *Zaschita ot ioniziruyuschih izlucheniya*. Moscow: Energoatomizdat, 495.
  14. Azaryan, A. A., Serebrennikov, V. M. (1988). *Matematicheskoe modelirovanie yadernofizicheskikh metodov analiza hromovykh rud*. Gorniy zhurnal, 6, 25–27.
  15. Dzyublik, A. Ya., Sadykov, E. K., Petrov, G. I., Arinin, V. V., Vagizov, F. H., Spivak, V. Yu. (2013). Mossbauer forward scattering spectra of ferromagnets in radio-frequency magnetic field. *Yaderna fizyka ta enerhetyka*, 13 (1), 73–82. Available at: [http://nbuv.gov.ua/UJRN/yadf\\_2013\\_13\\_1\\_12](http://nbuv.gov.ua/UJRN/yadf_2013_13_1_12)
  16. Shipachev, V. S. (1981). *Kurs vysshey matematiki*. Moscow: Izd-vo Mosk. un-ta, 280.
  17. Guhman, A. A. (1973). *Vvedenie v teoriyu podobiya*. Moscow: Vysshaya shkola, 296.
  18. Sedov, L. I. (1987). *Metody podobiya i razmernosti v mekhanike*. Moscow: Nauka, 432.
  19. Makarov, E. G. (2009). *Mathcad: Uchebnyy kurs*. Sankt-Peterburg: Piter, 384.
  20. Lutsenko, I., Oksanych, I., Shevchenko, I., Karabut, N. (2018). Development of the method for modeling operational processes for tasks related to decision making. *Eastern-European Journal of Enterprise Technologies*, 2 (4 (92)), 26–32. doi: <https://doi.org/10.15587/1729-4061.2018.126446>
  21. Lutsenko, I., Fomovskaya, E., Oksanych, I., Vikhrova, E., Serdiuk, O. (2017). Formal signs determination of efficiency assessment indicators for the operation with the distributed parameters. *Eastern-European Journal of Enterprise Technologies*, 1 (4 (85)), 24–30. doi: <https://doi.org/10.15587/1729-4061.2017.91025>
  22. Azaryan, A. (2015). Research of influence of monocrystal thickness NAJ(TL) on the intensity of the integrated flux of scattered gamma radiation. *Metallurgical and Mining Industry*, 2, 43–46.
  23. Azaryan, A., Gritsenko, A. (2011). Mobile station for logging of blast holes. *Novi tehnologii*, 4, 52–55.
  24. Azaryan, A., Azaryan, V. (2015). Use of Bourger-Lambert-Bera law for the operative control and quality management of mineral raw materials. *Metallurgical and Mining Industry*, 1, 4–8.
  25. Shvets, D. V. (2018). *Avtomaticheskoe upravlenie protsessom izmel'cheniya magnetitovykh rud na osnove opredeleniya ih prochnosti*. Sbornik nauchnykh trudov "Kachestvo mineral'nogo syr'ya", 2.
  26. Azaryan, A., Pikilnyak, A., Shvets, D. (2015). Complex automation system of iron ore preparation for beneficiation. *Metallurgical and mining industry*, 8, 64–66.
  27. Morkun, V., Morkun, N., Tron, V., Hryshchenko, S. (2017). Investigation of the effect of characteristics of gascontaining suspensions on the parameters of the process of ultrasonic wave propagation. *Eastern-European Journal of Enterprise Technologies*, 6 (5 (90)), 49–58. doi: <https://doi.org/10.15587/1729-4061.2017.118943>
  28. Porkuyan, O. V., Sotnikova, T. G. (2010). Kombinirovanny metod opredeleniya otноситel'nogo sodержaniya magnetita v tverdoy faze zhelezorudnoy pul'py. *Vestnik Nats. tekhn. un-ta "KhPI"*, 12, 29–36.
  29. Val'ter, A. K., Zalyubovskiy, I. I. (1991). *Yadernaya fizika*. Kharkiv: Osnova, 480.
  30. Tatarnikov, A. P. (1974). *Yadernofizicheskie metody obogascheniya poleznykh iskopaemykh*. Moscow: Atomizdat, 145.
  31. Plaksin, I. N., Starchik, L. P. (1966). *Yaderno-fizicheskie metody kontrolya veschestvennogo sostava: yadernye reaktsii i aktivatsionnyy analiz*. Moscow: Nauka, 204.
  32. Yakubovich, A. L., Zaytsev, E. I., Przhiyalgovskiy, S. M. (1982). *Yaderno-fizicheskie metody analiza gornyykh porod*. Moscow: Energoatomizdat, 264.
  33. Frolov, V. V. (1976). *Yaderno-fizicheskie metody kontrolya delyaschihsvya veschestv*. Moscow: Atomizdat, 128.

DOI: 10.15587/1729-4061.2019.171445

### STUDYING ADDITIONAL MEASUREMENT ERRORS FROM CONTROL TOOLS USING AN INTEGRAL FUNCTIONAL METHOD (p. 36-43)

Yosyf Stentsel

Volodymyr Dahl East Ukrainian National University,  
Severodonetsk, Ukraine  
ORCID: <http://orcid.org/0000-0003-0161-1172>

Olga Porkuian

Volodymyr Dahl East Ukrainian National University,  
Severodonetsk, Ukraine  
ORCID: <http://orcid.org/0000-0002-4046-0998>

Konstantyn Litvinov

Volodymyr Dahl East Ukrainian National University,  
Severodonetsk, Ukraine  
ORCID: <http://orcid.org/0000-0001-5409-4135>

Tetiana Sotnikova

Volodymyr Dahl East Ukrainian National University,  
Severodonetsk, Ukraine  
ORCID: <http://orcid.org/0000-0001-6929-7672>

Our research has established that under industrial conditions the correction to the result of current measurements when an influencing parameter deviates from the rated value is rarely introduced. In a general case, the procedure for determining an additional measurement error implies that the measured values for an influencing parameter are applied to determine the degree of its deviation while a correction to the current measurement result is calculated as the product of this degree by its rated value.

In a general case, a procedure for determining an additional measurement error includes two stages. At the first stage, the measured values for an influencing parameter are used to determine the degree of its deviation from the rated value. At the second stage, correction is calculated as the product of this degree by the rated value for an additional error.

Such a technique to calculate a correction is time consuming and insufficiently precise, as it does not take into consideration the non-linear dependence of the additional error on a change in the influencing parameter, as well as the current value for the output signal of control tool. To determine the actual value for an influencing parameter and the additional measurement error under industrial operation of control tools, an integral functional method has been proposed. The method implies determining the difference of areas under the nominal and actual acreage static characteristics,

limited to a range of measurement. The difference of areas is a function of the output signal of a control tool, a measured parameter and a change in the influencing parameter. It has been shown that the proposed method makes it possible to calculate the actual values for a technological parameter based on its measured and influencing parameters only. We have established regularities between the actual value for a measured parameter, the current value for the output signal from a control tool, and the measured value for an influencing parameter. The proposed method is important and valuable in the operation of computer-integrated control systems of technological parameters, as it makes it possible to determine the actual values for a measured parameter based on relevant algorithms without calculating corrections.

**Keywords:** control tool, additional error, influencing parameter, integral functional, measurement, static characteristics.

### References

1. DSTU 2681-94. Metrolohiya. Terminy ta vyznachennia (1995). Kyiv: Derzhstandart Ukrainy, 66.
2. Petrychenko, H., Nazarenko, L., Hots, N. (2014). Metodyka vyznachennia temperaturnoi zalezhnosti popravok dlia zmnshennia diyi vplyvnykh faktoriv na rezultaty vymirennia temperatury za in-frachervonym vyprominenniam v umovakh vyrobnytstva. *Metrolohiya ta prylady*, 4 (48), 8–12.
3. Calibration of Low-Temperature Infrared Thermometers (2009). MSL Technical Guide 22. Available at: <https://pdfs.semanticscholar.org/408a/354c752a4124f68369fa671d93f5acfa7fc.pdf>
4. Pistun, Ye., Matiko, F., Roman, V., Stetsenko, A. (2014). Doslidzhennia pokhybky ultrazvukovykh vytratimiriv za umov spotvorenoi struktury potoku na osnovi CFD-modeliuvannia. *Metrolohiya ta prylady*, 4 (48), 13–23.
5. Turkowski, M., Szufleński, P. (2013). New criteria for the experimental validation of CFD simulations. *Flow Measurement and Instrumentation*, 34, 1–10. doi: <https://doi.org/10.1016/j.flowmeasinst.2013.07.003>
6. Random Number Generation and Testing. Available at: <http://csrc.nist.gov/groups/ST/toolkit/rng/index.html>
7. Kondrashov, S., Opryshkina, M., Matsak, O. (2015). Kontrol metrolohichnoho stanu system z nelineynymy pervynnymy peretvoriuvachamy za dopomohoiu testovykh vplyviv. *Metrolohiya ta prylady*, 2, 33–41.
8. Volodarskiy, E., Koshevaya, L., Dobrolyubova, M. (2017). Ot-senivanie kachestva mnogoparametricheskogo tekhnologicheskogo protsessa pri korrelyatsii ego pokazately. *Metrolohiya ta prylady*, 5, 20–24.
9. ISO\IEC 17025-2005. General requirements for the competence of testing and calibration laboratories (2005). International Organization for Standardization.
10. Montgomery, D. C. (2009). Introduction to Statistical Quality Control. John Wiley & Sons, 754.

**DOI:** 10.15587/1729-4061.2019.168446

### DETERMINING THE REGIONS FOR EFFICIENT USE OF ELECTROJET LOWTHRUST ENGINES (p. 43-50)

**Aleksey Sidorov**

Oles Honchar Dnipro National University, Dnipro, Ukraine

**ORCID:** <http://orcid.org/0000-0003-2400-0841>

**Viktor Pererva**

Oles Honchar Dnipro National University, Dnipro, Ukraine

**ORCID:** <http://orcid.org/0000-0001-8803-5360>

This work addresses the issues on determining the optimal regions for using propulsion system for spacecraft at low near-Earth

orbits. An analysis of spacecraft launches over the past 5 years has been performed. The result of analyzing the launches is the type of spacecraft, selected for subsequent calculations, specifically a remote sensing satellite at low near-Earth orbit. We have solved the problem on determining parameters for the trajectory of a spacecraft motion, exposed to external non-permanent forces. Based on an analysis of the external influence, the scope of possible future application of spacecraft propulsion systems has been defined. A comparative analysis has been performed for the mass criterion of efficiency of using propulsion systems based on the chemical mono-component and electro-jet engines in order to solve tasks on maintaining the circular orbit parameters over a long time.

For orbit altitudes below 300 km, as was established based on the calculation results, the application of a propulsion system proved to be inefficient due to the need for a large reserve of fuel aboard and a large required engine thrust. For satellites at circular orbits from 350 to 450 km, a propulsion system that includes the Hall-effect-based engine ST-25, manufactured by SETS, proved to be more effective than the chemical propulsion unit. Application of chemical engines to maintain the orbit parameters at altitude above 500 km would be preferable to electro-jet ones due to a relatively small mass of the chemical propulsion system and a sufficient resource of engines operation in order to maintain the orbit.

We have obtained parameters for the propulsion system that uses the Hall-effect-based engine ST-25 in order to maintain orbital parameters within different ranges of altitudes, solar activity, and geometrical parameters for a satellite. The result of calculation is the determined necessary resource of operation and the fuel stock to maintain parameters of the orbit.

The calculation results obtained could be used to design new satellites and to modify satellite platforms.

**Keywords:** flight dynamics, low orbits, electro-jet engine, mono-component engine, maintaining the orbit.

### References

1. UCS Satellite Database. Available at: <https://www.ucsusa.org/nuclear-weapons/space-weapons/satellite-database>
2. NASA Space Science Data Coordinated Archive, NASA's archive for space science mission data. Available at: <https://nssdc.gsfc.nasa.gov>
3. Salmin, V. V., Volotsuev, V. V., Shikhanov, S. V. (2013). Spacecraft preset orbital parameters control by means of thrusters. *Vestnik Samarskogo gosudarstvennogo aerokosmicheskogo universiteta*, 4 (42), 248–254. Available at: <https://cyberleninka.ru/article/n/podderzhanie-zadannyh-orbitalnyh-parametrov-kosmicheskogo-apparata-s-pomoschyu-dvigatelay-maloy-tyagi>
4. BGT-X5 Green Monopropellant Thruster. Busek. Available at: [http://www.busek.com/index\\_htm\\_files/70008517E.pdf](http://www.busek.com/index_htm_files/70008517E.pdf)
5. Krejci, D., Lozano, P. (2018). Space Propulsion Technology for Small Spacecraft. *Proceedings of the IEEE*, 106 (3), 362–378. doi: <https://doi.org/10.1109/jproc.2017.2778747>
6. SPS25 propulsion system. Available at: <https://sets.space/sps25/>
7. Mammarella, M., Fusaro, R., Andreussi, T., Paissoni, C. A., Viola, N. et. al. (2018). Mission Scenarios for High-Power Electric Propulsion Space Propulsion 2018. Conference: Space Propulsion 2018. Available at: [https://www.researchgate.net/publication/325119863\\_MISSION\\_SCENARIOS\\_FOR\\_HIGH-POWER\\_ELECTRIC\\_PROPULSION\\_SPACE\\_PROPULSION\\_2018](https://www.researchgate.net/publication/325119863_MISSION_SCENARIOS_FOR_HIGH-POWER_ELECTRIC_PROPULSION_SPACE_PROPULSION_2018)
8. Pererva, V. A., Karpovich, E. V., Fedosov, A. V. (2016). Development of penetration zone size prediction technique for hollow-cathode welding technology of spherical titanium tanks. *Eastern-European Journal of Enterprise Technologies*, 1 (5 (79)), 47–52. doi: <https://doi.org/10.15587/1729-4061.2016.59790>
9. Zakharenkov, L. E., Kim, V., Lovtsov, A. S., Semkin, A., Solodukhin, A. E. (2018). Modern trends and development prospects

of thrusters with closed electron drift. Conference: Space Propulsion 2018. Available at: [https://www.researchgate.net/publication/330116874\\_MODERN\\_TRENDS\\_AND\\_DEVELOPMENT\\_PROSPECTS\\_OF\\_THRUSTERS\\_WITH\\_CLOSED\\_ELECTRON\\_DRIFT](https://www.researchgate.net/publication/330116874_MODERN_TRENDS_AND_DEVELOPMENT_PROSPECTS_OF_THRUSTERS_WITH_CLOSED_ELECTRON_DRIFT)

10. Peter, T., Dyer, A., Ryan, E., Garcia, C. et. al. (2018). Initial investigation of alternative propellants for use with a low-power cylindrical hall thruster. In Space Propulsion 2018, 12. Available at: <https://eprints.soton.ac.uk/426412/>
11. Andreussi, T., Cifali, G., Giannetti, V., Piragino, A., Ferrato, E., Rossodivita, A., Andrenucci, M. (2017). Development and experimental validation of a hall effect thruster RAM-EP concept. 35th International Electric Propulsion Conference Georgia Institute of Technology. Available at: [https://iepc2017.org/sites/default/files/speaker-papers/iepc-2017-377\\_ram\\_final.pdf](https://iepc2017.org/sites/default/files/speaker-papers/iepc-2017-377_ram_final.pdf)
12. Yermoshkin, Yu. M. (2011). Electric propulsions rational application range on the applied spacecrafts. *Sibirskiy zhurnal nauki i tekhnologii*, 2 (35), 109–113. Available at: <https://cyberleninka.ru/article/n/oblasti-ratsionalnogo-primeneniya-elektroreaktivnyh-dvigatelnyh-ustanovok-na-kosmicheskikh-apparatah-prikladnogo-naznacheniya>
13. Maslova, A. I., Pirozhenko, A. V. (2009). *Izmeneniya plotnosti atmosfery pri dvizhenii kosmicheskikh apparatov na nizkikh okolozemnykh orbitah. Kosmichna nauka i tekhnolohiya*, 1, 13–18.
14. Ishkov, S. A. (2016). Efficiency of using electric propulsion engines for the task of keeping in a near-circular orbit. *VESTNIK of the Samara State Aerospace University*, 15 (1), 55–63. doi: <https://doi.org/10.18287/2412-7329-2016-15-1-55-63>
15. Ishkov, S. A. (2017). Optimization of Design Parameters of Spacecraft Equipped with Electro Rocket Low-thrust Engine and Calculation its Applying Area at Low Earth Orbit. *Procedia Engineering*, 185, 239–245. doi: <https://doi.org/10.1016/j.proeng.2017.03.306>
16. Dron', N. M., Kondrat'ev, A. I., Hit'ko, A. V., Horol'skiy, P. G. (2008). *Kontseptsiya ispol'zovaniya elektroraketnyh dvigatelyu na mikrosputnikah. Aviatcionno-kosmicheskaya tekhnika i tekhnologiya*, 9, 39–43.
17. Alpatov, A. P. (2016). *Dinamika kosmicheskikh letatel'nykh apparatov*. Kyiv: Naukova dumka, 487.
18. Montenbruck, O., Gill, E. (2005). *Satellite Orbits: Models, Methods and Applications*. Springer, 369.
19. Curtis, H. D. (2014). *Orbital Mechanics for Engineering Students*. Butterworth-Heinemann, 768. doi: <https://doi.org/10.1016/c2011-0-69685-1>

DOI: 10.15587/1729-4061.2019.167198

**IMPROVEMENT OF AN ENGINEERING PROCEDURE FOR CALCULATING THE NONISOTHERMAL TRANSPORTATION OF A GASLIQUID MIXTURE (p. 51-60)**

**Mykhailo Fyk**

National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-5154-6001>

**Volodymyr Biletskyi**

National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0003-2936-9680>

**Ilya Fyk**

National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0002-7453-5636>

**Volodymyr Bondarenko**

Dnipro University of Technology, Dnipro, Ukraine

ORCID: <http://orcid.org/0000-0001-7552-0236>

**Al-Sultan Mohammed Bassam**

National Technical University «Kharkiv Polytechnic Institute»,  
Kharkiv, Ukraine

ORCID: <http://orcid.org/0000-0001-7754-0118>

The study that we conducted into the process of transportation of a gas-condensate mixture from a well bottom to the separation production plant has revealed the features of isothermal and non-isothermal flow. It was proved that during non-isothermal flow, hydraulic losses in the product pipeline are significantly affected by throttle effect and energy accommodation effect. The influence of velocity and volumetric flow rate of the gas-liquid mixtures on hydraulic resistance and pressure drop on a section of product pipeline, taking into consideration non-isothermal flow was analyzed. It was found that the assessment of hydraulic resistance and pressure drop in the proposed dependences converges with standardized ones by 95 %. The result was obtained based on the developed system of equations of the mathematical model for non-isothermal non-stationary one-dimensional motion of the gas-liquid mixture of hydrocarbons in the pipeline. The proposed system beneficially differs from the known ones by the fact that it takes into consideration the inner convective heat exchange, estimated by the combined effect of Joule-Thomson.

A distinctive feature of the improved procedure for calculation was the introduction of temperature correction and accommodation coefficient in the calculation of hydraulic resistance of a pipeline as a system with distributed parameters. Due to this, it became possible to improve the procedure for the calculation of non-isothermal transportation of a homogeneous gas-condensate mixture. Based on the analysis of calculation curves by the known procedures (formulas of Thomas Colebrooke, Leibenson and VNII-gas) for isothermal and non-isothermal processes and the proposed procedure, rational areas of their applications were shown. All calculations were performed at the velocity of a gas-liquid flow within the range 0–50 m/s, pipe roughness of 0.01–0.05 mm and their diameter of 100–300 mm, the data from actual production pipelines of Novotroitsk oil-gas condensate field were used. Comparison of the theoretical and industrial experiments showed sufficient for engineering practice accuracy of calculation of pressure drop on the stretches of oil and gas lead lines and allowed recommending the developed analytical dependences for the introduction in industrial engineering.

**Keywords:** non-isothermal fluid, pipeline transportation, gas-liquid mixture of hydrocarbons, hydraulic losses, coefficient of hydraulic resistance.

**References**

1. Yakupov, R. R., Yarkeeva, N. R. (2018). Optimization of gas wells operation at the yamburg gas field. *Petroleum Engineering*, 16 (3), 41–49. doi: <https://doi.org/10.17122/ngdelo-2018-3-41-49>
2. Xia, C., Liu, L., Zhang, L., Peng, X. (2016). Optimization techniques for the secondary development of old gas fields in the Sichuan Basin and their application. *Natural Gas Industry B*, 3 (6), 595–606. doi: <https://doi.org/10.1016/j.ngib.2017.05.010>
3. Shen, Y., Luan, G., Ge, H., Yang, X., Liu, Q., Guo, X. (2017). Optimization of coiled-tubing drainage gas recovery technology in tight gas field. *Advances in Mechanical Engineering*, 9 (5), 1687814017711333. doi: <https://doi.org/10.1177/1687814017711333>
4. Lurie, M. V. (2008). *Modeling of Oil Product and Gas Pipeline Transportation*. Weinheim: WILEY-VCH Verlag GmbH & Co. KGaA, 214. doi: <https://doi.org/10.1002/9783527626199>
5. Novickiy, N. N., Suharev, M. G., Tevyashev, A. D. et. al. (2010). *Truboprovodnye sistemy energetiki: Matematicheskoe modelirovanie i optimizaciya*. Novosibirsk: Nauka, 419.

6. Kang, J. Y., Lee, B. S. (2017). Optimisation of pipeline route in the presence of obstacles based on a least cost path algorithm and laplacian smoothing. *International Journal of Naval Architecture and Ocean Engineering*, 9 (5), 492–498. doi: <https://doi.org/10.1016/j.ijnaoe.2017.02.001>
7. Aalto, H. (2008). Optimal Control of Natural Gas Pipeline Networks: A Real-Time, Model-Based, Receding Horizon Optimisation Approach. VDM Verlag, 188.
8. Arya, A. K., Honwad, S. (2018). Multiobjective optimization of a gas pipeline network: an ant colony approach. *Journal of Petroleum Exploration and Production Technology*, 8 (4), 1389–1400. doi: <https://doi.org/10.1007/s13202-017-0410-7>
9. Ehrhardt, K., Steinbach, M. C. (2005). Nonlinear Optimization in Gas Networks. Modeling, Simulation and Optimization of Complex Processes. Springer, 139–148. doi: [https://doi.org/10.1007/3-540-27170-8\\_11](https://doi.org/10.1007/3-540-27170-8_11)
10. Trapeznikov, S. Yu. (2011). Issledovanie koefitsienta gidravlicheskogo soprotivleniya pri neizotermicheskom dvizhenii vysokovyazkoy nefti po truboprovodu. *Elektronniy nauchniy zhurnal «Neftegazovoe delo»*, 2, 304–310.
11. Mikolajková, M., Saxén, H., Pettersson, F. (2018). Mixed Integer Linear Programming Optimization of Gas Supply to a Local Market. *Industrial & Engineering Chemistry Research*, 57 (17), 5951–5965. doi: <https://doi.org/10.1021/acs.iecr.7b04197>
12. Kryzhanivskiy, Ye. et. al. (2006). Enerhetichna bezpeka derzhavy: vysokoeffektivni tekhnolohiyi vydobuvannya, postachannya i vykorystannya pryrodnoho hazu. Kyiv: Interpres LTD, 281.
13. Hiller, B., Koch, T., Schewe, L., Schwarz, R., Schweiger, J. (2018). A system to evaluate gas network capacities: Concepts and implementation. *European Journal of Operational Research*, 270 (3), 797–808. doi: <https://doi.org/10.1016/j.ejor.2018.02.035>
14. Kondratev, A. S., Nha, T. L., Shvydko, P. P. (2017). The Colebrook-White general formula in pipe flow for arbitrary sand roughness of pipe wall. *Fundamental research*, 1, 74–78.
15. Fyk, M., Fyk, I., Biletsky, V., Olynyk, M., Kovalchuk, Y., Hnieushev V., Shapchenko Y. (2018). Theoretical and applied aspects of using a thermal pump effect in gas pipeline systems. *Eastern-European Journal of Enterprise Technologies*, 1 (8 (91)), 39–48. doi: <https://doi.org/10.15587/1729-4061.2018.121667>
16. Boiko, V. S., Boiko, R. V. (2010). Vydobuvannya i transportuvannya hidratoutvoriuvalnykh pryrodnykh ta naftovykh haziv. Ivano-Frankivsk: «Nova zoria», 747.
17. Savić, V., Karanović, V., Knežević, D., Lovrec, D., Jovanović, M. (2009). Determination of Pressure Losses in Hydraulic Pipeline Systems by Considering Temperature and Pressure. *Strojniški vestnik*, 55 (4), 237–243.
18. Fyk, M. I. (2014). Utochnennia rozrakhunku efektyvnosti roboty DKS v umovakh faktychnykh termohradientiv ta suchasnykh pokryttiv NKT. *Naftohazova haluz Ukrainy*, 1, 25–28.
19. Boiko, V. S. (2012). Tekhnolohiya vydobuvannya nafty. Ivano-Frankivsk: Nova Zoria, 827.
20. Garris, N. A., Rusakov, A. I., Lebedeva, A. A. (2018). Balanced heat exchange of oil pipeline in permafrost calculation and thawing halo radius determination. *Petroleum Engineering*, 16 (5), 73–80. doi: <https://doi.org/10.17122/ngdelo-2018-5-73-80>
21. Rzaev, A., Rasulov, S., Pashaev, F., Sali, M. (2017). Features of distribution of temperature along the length of oil pipeline. *Perm Journal of Petroleum and Mining Engineering*, 16 (2), 158–163. doi: <https://doi.org/10.15593/2224-9923/2017.2.6>
22. Gricenko, A. I., Aliev, Z. S., Ermilov, O. M., Remizov, V. V., Zotov, G. A. (1995). Rukovodstvo po issledovaniyu skvazhin. Moscow: Nauka, 523.
23. Morozova, N. V., Korshak, A. A. (2007). Problema rascheta poter' napora po formule Leybenzona v zone smeshannogo treniya turbulentnogo rezhima. *Zapiski Gornogo instituta*, 170, 124–126.
24. Bilyushov, V. M. (1984). Matematicheskaya model' obrazovaniya gidratov pri techenii vlazhnogo gaza v trubah. *Inzhenerno-fizicheskii zhurnal*, 46 (1), 57–63.
25. Haaland, S. E. (1983). Simple and Explicit Formulas for the Friction Factor in Turbulent Pipe Flow. *Journal of Fluids Engineering*, 105 (1), 89–90. doi: <https://doi.org/10.1115/1.3240948>
26. Beletskij, V. S., Borejko, M. K., Sergeev, P. V. (1992). Study of changes in the electrokinetic properties of oxidized coal during its hydrotransport. *Solid Fuel. Chemistry*, 4, 108–111.